

DIN EN ISO 11890-2:2013-07 (E)

Paints and varnishes - Determination of volatile organic compound (VOC) content - Part 2: Gas-chromatographic method (ISO 11890-2:2013)

Contents		Page
Foreword		3
1	Scope	4
2	Normative references	4
3	Terms and definitions	4
4	Principle	5
5	Required supplementary information	5
6	Apparatus	5
6.1	Gas chromatograph	5
6.2	Sample injection system	6
6.3	Oven	6
6.4	Detector	6
6.5	Capillary column	7
6.6	Qualitative-analysis equipment	7
6.7	Injection syringe	7
6.8	Chart recorder	7
6.9	Integrator	7
6.10	Sample vials	7
6.11	Gas filters	7
6.12	Gases	7
7	Reagents	8
7.1	Internal standard	8
7.2	Calibration compounds	8
7.3	Dilution solvent	8
7.4	Marker compound	8
8	Sampling	8
9	Procedure	8
9.1	Density	8
9.2	Water content	9
9.3	Gas-chromatographic conditions	9
9.4	Qualitative analysis of product	9
9.5	Calibration	9
9.6	Sample preparation	10
9.7	Quantitative determination of compound content	10
10	Calculation	11
10.1	General	11
10.2	Method 1: VOC content, as a percentage by mass, of the product "ready for use"	11
10.3	Method 2: VOC content, in grams per litre, of the product "ready for use"	12
10.4	Method 3: VOC content, in grams per litre, of the product "ready for use" less water	12
10.5	Method 4: VOC content, in grams per litre, of the product "ready for use" less water and less exempt compounds (only required if national legislation applies)	13

11	Expression of results	13
12	Precision	13
12.1	General	13
12.2	Repeatability limit r	13
12.3	Reproducibility limit R	14
13	Test report	14
	Annex A (normative) Required supplementary information	15
	Annex B (informative) Examples of gas-chromatographic conditions	16
	Bibliography	20