

# ISO 4624:2016-03 (E)

## Paints and varnishes - Pull-off test for adhesion

---

<b>Contents</b>		<b>Page</b>
Foreword .....		iv
Introduction .....		v
<b>1</b>	<b>Scope .....</b>	<b>1</b>
<b>2</b>	<b>Normative references .....</b>	<b>1</b>
<b>3</b>	<b>Principle .....</b>	<b>1</b>
<b>4</b>	<b>Apparatus .....</b>	<b>2</b>
<b>5</b>	<b>Adhesives .....</b>	<b>4</b>
<b>6</b>	<b>Sampling .....</b>	<b>4</b>
<b>7</b>	<b>Test panels .....</b>	<b>5</b>
7.1	Substrate .....	5
7.2	Preparation and coating .....	5
7.3	Drying and conditioning .....	5
7.4	Thickness of coating .....	5
<b>8</b>	<b>Procedure .....</b>	<b>5</b>
8.1	Number of determinations .....	5
8.2	Ambient conditions .....	5
8.3	Adhesive .....	5
8.4	Test assemblies .....	5
8.4.1	Method A: General method (using two dollies) for testing both rigid and deformable substrates .....	5
8.4.2	Method B: Method for testing from one side only, using a single dolly (suitable for rigid substrates only) .....	6
8.4.3	Method C: Method using dollies, one as a painted substrate .....	7
8.5	Measurement .....	7
8.5.1	Breaking strength .....	7
8.5.2	Nature of the fracture .....	8
<b>9</b>	<b>Calculation and expression of results .....</b>	<b>8</b>
9.1	Breaking strength .....	8
9.2	Nature of failure .....	9
9.3	Example .....	9
<b>10</b>	<b>Precision .....</b>	<b>9</b>
<b>11</b>	<b>Test report .....</b>	<b>9</b>
Bibliography .....		11