

# DIN EN ISO 1518-2:2019-10 (E)

## Paints and varnishes - Determination of scratch resistance - Part 2: Variable-loading method (ISO 1518-2:2019)

---

<b>Contents</b>		Page
<b>European foreword</b> .....		<b>3</b>
<b>Foreword</b> .....		<b>4</b>
<b>1</b>	<b>Scope</b> .....	<b>5</b>
<b>2</b>	<b>Normative references</b> .....	<b>5</b>
<b>3</b>	<b>Terms and definitions</b> .....	<b>5</b>
<b>4</b>	<b>Principle</b> .....	<b>5</b>
<b>5</b>	<b>Apparatus</b> .....	<b>6</b>
<b>6</b>	<b>Sampling</b> .....	<b>7</b>
<b>7</b>	<b>Test panels</b> .....	<b>7</b>
	7.1 Substrate .....	7
	7.2 Preparation and coating .....	8
	7.3 Drying and conditioning .....	8
	7.4 Thickness of coating .....	8
<b>8</b>	<b>Procedure</b> .....	<b>8</b>
	8.1 Test conditions .....	8
	8.2 Preparation for the test .....	8
	8.3 Determination .....	8
<b>9</b>	<b>Expression of results</b> .....	<b>9</b>
<b>10</b>	<b>Precision</b> .....	<b>9</b>
<b>11</b>	<b>Test report</b> .....	<b>10</b>
<b>Bibliography</b> .....		<b>11</b>