

DIN EN ISO 6504-3:2020-04 (E)

Paints and varnishes - Determination of hiding power - Part 3: Determination of hiding power of paints for masonry, concrete and interior use (ISO 6504-3:2019)

Contents		Page
European foreword		3
Foreword		4
Introduction		5
1 Scope		6
2 Normative references		6
3 Terms and definitions		6
4 Symbols and abbreviated terms		7
5 Principle		9
6 Apparatus		9
7 Sampling		11
8 Procedure and calculation		12
8.1 Preparation of substrate		12
8.1.1 Method A (foil)		12
8.1.2 Method B and Method C (black and white charts)		12
8.2 Preparation of coated foils or black and white charts		12
8.3 Determination of the spreading rate of the test specimen		12
8.3.1 Calculation of the surface mass density		12
8.3.2 Determination of the density		14
8.3.3 Determination of the non-volatile matter		14
8.3.4 Calculation of the theoretical dry- or wet-film thickness (method A, method B and method C)		14
8.3.5 Calculation 1 – Determination of the theoretical spreading rate by calculation from the non-volatile matter content determined in accordance with ISO 3251 and the density of the coating material (see ISO 3233-3) (method A and method B)		15
8.3.6 Calculation 2 – Determination of the theoretical spreading rate calculated with the different coated masses on the two charts (method C), the density of the coating material according to ISO 2811 (all parts) and the coated area		17
8.4 Measurement of tristimulus value Y_{10} and calculation of the hiding power H_{10}		18
8.4.1 General		18
8.4.2 Method A (foil)		18
8.4.3 Method B (black and white charts)		18
8.4.4 Method C (black and white charts)		18
8.5 Graphical method for determination of the hiding power at a given spreading rate (method C)		19
8.5.1 General		19
8.5.2 Determination by graphical method		19
8.5.3 Determination by calculation with a known slope		21
9 Designation of the test result		22
10 Precision		23
11 Test report		23
Annex A (informative) Details on interlaboratory comparison		24
Bibliography		26