

### Contents

	Foreword
	Introduction
1	Scope
2	Normative references
3	Terms and definitions
4	Determination of wet-film thickness
4.1	General
4.2	Mechanical methods
4.2.1	Principle
4.2.2	Field of application
4.2.3	General
4.2.4	Method 1A — Comb gauge
4.2.4.1	Description of instrument
4.2.4.2	Procedure
4.2.5	Method 1B — Wheel gauge
4.2.5.1	Description of instrument
4.2.5.2	Procedure
4.2.6	Method 1C — Dial gauge
4.2.6.1	Instrument and reference materials (reference standard)
4.2.6.1.1	Dial gauge [see Figure 3 a) and b)]
4.2.6.1.2	Reference material for zeroing the gauge
4.2.6.2	Procedure
4.3	Gravimetric method
4.3.1	Principle
4.3.2	Field of application
4.3.3	General
4.3.4	Method 2 — By difference in mass
4.3.4.1	Apparatus
4.3.4.2	Procedure
4.4	Photothermal method
4.4.1	Principle
4.4.2	Field of application
4.4.3	General
4.4.4	Method 3 — Determination using thermal properties
4.4.4.1	Instrument and reference materials (reference specimens)
4.4.4.1.1	Measurement system
4.4.4.1.2	Reference material
4.4.4.2	Calibration
4.4.4.3	Procedure
5	Determination of dry-film thickness
5.1	General
5.2	Mechanical methods
5.2.1	Principle
5.2.2	Field of application
5.2.3	General
5.2.4	Method 4A — By difference in thickness
5.2.4.1	Description of instrument
5.2.4.1.1	Micrometre
5.2.4.1.1.1	General

- 5.2.4.1.1.2 Version 1 — Fixed to a stand
- 5.2.4.1.1.3 Version 2 — Hand-held (see Figure 5)
- 5.2.4.1.2 Dial gauge
  - 5.2.4.1.2.1 General
  - 5.2.4.1.2.2 Version 1 — Fixed to a stand
  - 5.2.4.1.2.3 Version 2 — Hand-held
- 5.2.4.2 Procedure
- 5.2.5 Method 4B — Depth gauging
  - 5.2.5.1 Instruments and reference materials (reference specimens)
    - 5.2.5.1.1 Version 1 — Micrometer depth gauge (see Figure 8)
    - 5.2.5.1.2 Version 2 — Dial depth gauge (see Figure 9)
    - 5.2.5.1.3 Reference materials for zeroing the gauge
  - 5.2.5.2 Procedure
- 5.2.6 Method 4C — Surface profile scanning
  - 5.2.6.1 Description of instrument
  - 5.2.6.2 Procedure
- 5.3 Gravimetric method
  - 5.3.1 Principle
  - 5.3.2 Field of application
  - 5.3.3 General
  - 5.3.4 Method 5 — By difference in mass
    - 5.3.4.1 Apparatus
    - 5.3.4.2 Procedure
- 5.4 Optical methods
  - 5.4.1 Principle
  - 5.4.2 Field of application
  - 5.4.3 General
  - 5.4.4 Method 6A — Cross-sectioning
    - 5.4.4.1 Version 1 — By grinding
      - 5.4.4.1.1 Apparatus and materials
        - 5.4.4.1.1.1 Grinding and polishing machine
        - 5.4.4.1.1.2 Embedding medium
        - 5.4.4.1.1.3 Grinding and polishing media
        - 5.4.4.1.1.4 Measuring microscope
      - 5.4.4.1.2 Procedure
    - 5.4.4.2 Version 2 — By cutting
      - 5.4.4.2.1 Apparatus
        - 5.4.4.2.1.1 Cutter
        - 5.4.4.2.1.2 Measuring microscope
        - 5.4.4.2.2 Procedure
  - 5.4.5 Method 6B — Wedge cut
    - 5.4.5.1 Apparatus
      - 5.4.5.1.1 General
      - 5.4.5.1.2 Cutter
      - 5.4.5.1.3 Measuring microscope or digital measurement equipment
    - 5.4.5.2 Procedure
  - 5.4.6 Method 6C — White-light interferometry
    - 5.4.6.1 Instrument and reference material
      - 5.4.6.1.1 White-light interferometer
      - 5.4.6.1.2 Reference material
    - 5.4.6.2 Procedure
- 5.5 Magnetic methods
  - 5.5.1 Principle
  - 5.5.2 Field of application
  - 5.5.3 General
  - 5.5.4 Method 7A — Magnetic pull-off gauge
    - 5.5.4.1 Description of instrument
    - 5.5.4.2 Procedure
  - 5.5.5 Method 7B.1 — Magnetic-flux gauge
    - 5.5.5.1 Description of instrument
    - 5.5.5.2 Procedure
  - 5.5.6 Method 7B.2 — Magnetic field change, magnetic-induction principle
    - 5.5.6.1 Description of instrument
    - 5.5.6.2 Procedure

- 5.5.7 Method 7C — Eddy-current gauge
  - 5.5.7.1 Description of instrument
  - 5.5.7.2 Procedure
- 5.6 Radiological method
  - 5.6.1 Principle
  - 5.6.2 Field of application
  - 5.6.3 General
  - 5.6.4 Method 8 — Beta backscatter method
    - 5.6.4.1 Description of instrument
    - 5.6.4.2 Verification
    - 5.6.4.3 Procedure
- 5.7 Photothermal method
  - 5.7.1 Principle
  - 5.7.2 Field of application
  - 5.7.3 General
  - 5.7.4 Method 9 — Determination using thermal properties
    - 5.7.4.1 Instruments and reference materials (reference specimens)
      - 5.7.4.1.1 Measurement system
      - 5.7.4.1.2 Reference materials
    - 5.7.4.2 Verification
    - 5.7.4.3 Procedure
- 5.8 Acoustic method
  - 5.8.1 Principle
  - 5.8.2 Field of application
  - 5.8.3 General
  - 5.8.4 Method 10 — Ultrasonic reflection
    - 5.8.4.1 Description of instrument
    - 5.8.4.2 Procedure
- 5.9 Electromagnetic method
  - 5.9.1 Method 11 — Terahertz method
    - 5.9.1.1 Description of instrument
    - 5.9.1.2 Field of application
    - 5.9.1.3 General

**6 Determination of thickness of uncured powder layers**

- 6.1 General
- 6.2 Gravimetric method
  - 6.2.1 Principle
  - 6.2.2 Field of application
  - 6.2.3 General
  - 6.2.4 Method 12 — By difference in mass
    - 6.2.4.1 Apparatus
    - 6.2.4.2 Procedure
- 6.3 Magnetic methods
  - 6.3.1 Principle
  - 6.3.2 Field of application
  - 6.3.3 General
  - 6.3.4 Method 13A — Magnetic-induction method
    - 6.3.4.1 Description of instrument
    - 6.3.4.2 Procedure
  - 6.3.5 Method 13B — Eddy-current
    - 6.3.5.1 Description of instrument
    - 6.3.5.2 Procedure
- 6.4 Photothermal method
  - 6.4.1 Principle
  - 6.4.2 Field of application
  - 6.4.3 General
  - 6.4.4 Method 14 — Determination using thermal properties
    - 6.4.4.1 Instruments and reference materials (reference specimens)
      - 6.4.4.1.1 Measurement system
      - 6.4.4.1.2 Reference materials
    - 6.4.4.2 Verification
    - 6.4.4.3 Procedure

**7 Test report**

**Annex A (informative) Overview of methods**

**Annex B (informative) Measurement of film thickness on rough surfaces**

- B.1 General**
- B.2 Apparatus and materials**
- B.3 Procedure**
  - B.3.1 Verification**
  - B.3.2 Measurement**
  - B.3.3 Number of readings**

**Annex C (informative) Factors affecting the precision of readings obtained when measuring on wooden substrates**

- C.1 General**
- C.2 Random sampling**
- C.3 Penetrating coating material**
- C.4 Orientation of measurements**

**Page count: 49**