

ISO 22987:2020 (E)

Ships and marine technology — Laboratory test method for skin friction of antifouling paints by rotating drum

Contents

| | |
|---------|--|
| | Foreword |
| | Introduction |
| 1 | Scope |
| 2 | Normative references |
| 3 | Terms and definitions |
| 4 | Test instrumentation |
| 4.1 | General |
| 4.2 | Dynamic ageing system |
| 4.3 | Friction test system |
| 4.4 | Motors |
| 4.5 | Testing solution |
| 4.6 | Torque sensor |
| 5 | Drum specification |
| 5.1 | Materials |
| 5.2 | Dimension |
| 6 | Preparation of the test specimen |
| 6.1 | Paint sampling |
| 6.2 | Paint application |
| 6.3 | Drying and conditioning of test specimen |
| 6.4 | Dry film thickness |
| 6.5 | Sample quantity |
| 7 | Test procedure |
| 7.1 | Test principle |
| 7.2 | Test procedure |
| 8 | Calculation and expression of results |
| 8.1 | Calculation of torque |
| 8.2 | Determination of roughness |
| 8.3 | Calculation of friction reduction rate |
| 9 | Precision |
| 10 | Test report |
| Annex A | (normative) Determination of paint surface roughness by stylus instrument |
| A.1 | Principle |
| A.2 | Apparatus |
| A.3 | Procedure for measurement of the grand mean maximum peak-to-valley height and expression of result |