ISO 17895:2024-08 (E)

Paints and varnishes - Determination of volatile organic compound (VOC) - Gas-chromatographic method with headspace injection for VOC determination

Contents

Page

Foreword iv

1 Scope 1

2 Normative references 1

3 Termsanddefinitions 1

4 Principle 3

5 Required information 3

6 Apparatus 3

7 Reagents 5

8 Procedure 6
8.1 Number of determinations 6
8.2 Sample preparation 6
8.2.1 General 6
8.2.2 Dilution of original sample 6
8.2.3 Preparation of test samples for analysis without multiple standard additions 6
8.2.4 Preparation of test samples for analysis with multiple standard additions 6
8.3 Analysis 7
8.3.1 General 7
8.3.2 Headspace injector 7
8.3.3 Gas chromatograph 7
8.3.4 Determination of integration end point 8

9 Evaluation 8

10 Calculation 9
10.1 General 9
10.2 Method 1: VOC content, as a percentage by mass, of the product "ready for use" 9
10.3 Method 2: VOC content, in grams per litre, of the product "ready for use" 10

11 Precision 11
11.1 General 11
11.2 Repeatability limit, r 11
11.3 Reproducibility limit, R 12

12 Test report 12

Annex A (informative) Gas chromatogram of the reference compound mixture and tetradecane 13

Bibliography 14