

DIN EN 12602:2008-08 (E)

Prefabricated reinforced components of autoclaved aerated concrete

Contents		Page
Foreword		9
1	Scope	11
2	Normative references	11
3	Terms, definitions, symbols and abbreviations	13
3.1	Terms and definitions	13
3.2	Symbols	14
3.2.1	General symbols	14
3.2.2	Subscripts	14
3.2.3	Symbols used in this European Standard (including normative annexes, except Annex C)	15
3.3	Abbreviations	20
4	Properties and requirements of materials	21
4.1	Constituent materials of autoclaved aerated concrete	21
4.1.1	General	21
4.1.2	Release of dangerous substances	21
4.2	Autoclaved aerated concrete parameters	22
4.2.1	General	22
4.2.2	Dry density	22
4.2.3	Characteristic strength values	23
4.2.4	Compressive strength	23
4.2.5	Tensile strength and flexural strength	24
4.2.6	Stress-strain diagram	24
4.2.7	Modulus of elasticity	24
4.2.8	Poisson's ratio	25
4.2.9	Coefficient of thermal expansion	25
4.2.10	Drying shrinkage	25
4.2.11	Creep	25
4.2.12	Specific heat	26
4.2.13	Thermal conductivity	26
4.2.14	Water vapour permeability	28
4.2.15	Water tightness	28
4.3	Reinforcement	28
4.3.1	Steel	28
4.3.2	Structural reinforcement	28
4.3.3	Effective diameter of coated bars	29
4.3.4	Non-structural reinforcement	29
4.4	Bond	30
4.5	Thermal prestress	30
4.5.1	General	30
4.5.2	Declared mean initial prestrain $0m,g$	31
5	Properties and requirements of components	31
5.1	General	31
5.1.1	Mechanical resistance	31
5.1.2	Acoustic properties	31
5.1.3	Reaction to fire and resistance to fire	32
5.1.4	Design thermal resistance and design thermal conductivity	32
5.2	Technical requirements and declared properties	32

5.2.1	Dimensions and tolerances	32
5.2.2	Mass of the components	33
5.2.3	Dimensional stability	33
5.2.4	Load-bearing capacity	34
5.2.5	Deflections	34
5.2.6	Joint strength	35
5.2.7	Minimum requirements	35
5.3	Durability	37
5.3.1	General	37
5.3.2	Environmental conditions	37
5.3.3	Corrosion protection of reinforcement	38
5.3.4	Freeze and thaw resistance	39
6	Evaluation of conformity	39
6.1	Introduction	39
6.2	Initial type-testing of the component	39
6.3	Factory production control	40
6.3.1	General	40
6.3.2	Process control	40
6.3.3	Finished products	41
6.4	Initial inspection of the factory and the factory production control	41
6.4.1	Information to be supplied	41
6.4.2	Inspection	41
6.4.3	Reports	41
6.5	Surveillance, assessment and acceptance of the factory production control	42
6.5.1	Inspection tasks	42
6.5.2	Frequency of inspections	42
6.5.3	Reports	42
6.6	Actions to be taken in the event of non-conformity	42
7	Basis for design	48
7.1	Design methods	48
7.2	Limit states	48
7.3	Actions	48
8	Marking, labelling and designation	49
8.1	Standard designation	49
8.2	Production detail information	49
8.3	Additional information on accompanying documents	49
A.1	General	51
A.2	Ultimate limit states (ULS) General design assumptions	51
A.3	Ultimate limit states (ULS): design for bending and combined bending and axial compression	53
A.3.1	Design assumptions	53
A.3.2	Stress-strain diagram for AAC	53
A.3.3	Stress-strain diagram for reinforcing steel	54
A.3.4	Minimum reinforcement	56
A.4	Shear	57
A.4.1	Shear design for components predominantly under transverse load	57
A.5	Ultimate limit states induced by structural deformation (buckling)	62
A.5.1	General	62
A.5.2	Method based on Euler formula	62
A.5.3	Modified model column method	63
A.6	Punching	69
A.6.1	General	69
A.6.2	Scope and definitions	69
A.6.3	Design method for punching shear	71
A.7	Primary torsion/combined primary torsion and shear	72
A.8	Concentrated forces	74
A.9	Serviceability limit states (SLS)	75
A.9.1	General	75

A.9.2	Limitation of stresses under serviceability conditions	75
A.9.3	Serviceability limit states of cracking	76
A.9.4	Serviceability limit states of deformation	76
A.10	Detailing of reinforcement	79
A.10.1	General	79
A.10.2	Bond	79
Annex A (normative) Design by calculation		51
A.10.3	Anchorage	80
A.11	Support length	82
B.1	General	84
B.2	Safety evaluation	85
B.2.1	General	85
B.2.2	Brittle and ductile failure	85
B.3	Ultimate limit state	85
B.3.1	General	85
B.3.2	Transversely loaded components	85
B.3.3	Longitudinally loaded components	87
B.3.4	Simultaneously transversely and longitudinally loaded wall components	90
B.3.5	Anchorage	91
B.4	Serviceability limit states	93
B.4.1	Crack width control	93
B.4.2	Deformations	93
C.1	General	94
C.1.1	Scope	94
C.1.2	Distinction between principles and application rules	94
C.1.3	Terms and definitions	94
C.1.4	Symbols	96
C.1.5	Units	97
C.2	Basic principles	97
C.2.1	Performance requirements	97
C.2.2	Design values of material properties	98
C.2.3	Assessment methods	98
C.3	Material properties	99
C.3.1	General	99
C.3.2	AAC	99
C.3.3	Steel	101
C.4	Structural fire design methods	102
C.4.1	General	102
C.4.2	Tabulated data	102
C.4.3	Simplified design methods	106
C.4.4	Anchorage	110
C.5	Protective layers	110
elevated temperature		111
CB.1	Floor and roof components with dry joints	114
CB.2	Floor and roof components with mortar joints	114
CB.3	Vertical and horizontal wall components with dry joints	115
CB.4	Vertical and horizontal wall components with mortar joints	115
CC.1	Basis of temperature profiles	117
CC.2	Temperature profiles for AAC wall, floor and roof components	117
CC.3	Temperature profiles for AAC beams	119

CC.4 Calculation assumptions	127
Annex B (normative) Design by testing	84
Annex C (normative) Resistance to fire design of AAC components and structures	94
Annex CA (normative) Modulus of elasticity and maximum strain of AAC and reinforcing steel at Annex CB (informative) Joints between AAC components satisfying resistance to fire E	114
Annex CC (normative) Temperature profiles of AAC wall, floor and roof components and AAC beams	117
Annex CD (normative) Resistance to fire tabulated data for walls with mechanical impact	128
Annex D (informative) Recommended values for partial safety factors	130
D.1 General	130
D.2 Ultimate Limit States (ULS)	130
D.3 Serviceability Limit States (SLS)	131
prefabricated reinforced AAC components	132
E.1 Calculation of prestrain from test results	132
E.1.1 General	132
E.1.2 Symbols	133
E.1.3 Cross-section values of AAC components	133
E.1.4 Calculation of prestrain 0 from steel measurement	133
E.2 Cross-sectional analysis of a AAC component in SLS if prestress is taken into account	134
E.3 Splitting forces due to prestress	134
E.4 Methods to prevent end cracks due to prestress	135
F.1 Quality control	136
autoclaved aerated concrete under the EC Construction Product Directive	138
ZA.1 Clauses of this European Standard addressing the provisions of EC Construction Products Directive	138
ZA.2 Procedures for the attestation of conformity of products	146
ZA.2.1 Systems of attestation of conformity	146
ZA.2.2 EC Certificate and Declaration of conformity	148
ZA.3 CE marking and labelling	149
ZA.3.1 General	149
ZA.3.2 Declaration of geometrical data and material properties	150
ZA.3.3 Declaration of product properties	153
ZA.3.4 Declaration of compliance with given design specification	155
ZA.3.5 Declaration of compliance with a given design specification	156
ZA.3.6 Simplified CE-marking label with reference to a manufacturer's catalogue	159
ZA.3.7 Additional information	160
Bibliography	161

Figures Figure 1 -- Determination of dry thermal conductivity 10_{dry}	27
Figure A.1 -- Determination of effective span l_{eff}	52
Figure A.2 -- Bi-linear stress-strain diagram for AAC in compression for cross-sectional design	54
Figure A.3 -- Design stress-strain diagram for reinforcing steel	55
Figure A.4 -- Strain diagrams in the ultimate limit state	56
Figure A.5 -- Notation for components subjected to shear	59
Figure A.6 -- Structural model and possible load cases for the modified model column method	64
Figure A.7 -- Relation between curvature and strain Two curvatures (great curvature and small curvature) are presented	67
Figure A.8 -- Application of punching provisions in non-standard cases	70
Figure A.9 -- Critical perimeter around loaded areas located away from an unsupported edge	70
Figure A.10 -- Critical perimeter near an opening	71
Figure A.11 -- Critical sections near unsupported edges	71
Figure A.12 -- Idealised box section	73
Figure A.13 -- Definition of the areas to be introduced in Equation (A.39)	74
Annex E (informative) Recommendations for the consideration of prestress in the design of Annex F (informative) Statistical methods for quality control	136
Annex ZA (informative) Provisions for the CE marking of prefabricated reinforced components of Figure A.14 -- Moment curvature relationship	79
Figure A.15 -- Effective length of transverse anchorage bars	82
Figure A.16 -- Envelope line for determining the tensile force in the longitudinal reinforcement	82
Figure A.17 -- Support length a_o	83
Figure B.1 -- Definition of shear span l_s	86
Figure B.2 -- Typical reinforcement layouts in AAC-components	86
Figure B.3 -- Diagram for determination of the column factor k	89
Figure B.4 -- N/M - interaction diagram of the cross-section representing the results of three test series	91
Figure B.5 -- Envelope line for determining the section of the actual bending moment, M_{da}	93
Figure C.1 - Coefficient $k_c()$ allowing for decrease of compressive strength, f_{ck} , of AAC at elevated temperature	100
Figure C.2 - Coefficient $k_s()$ allowing for decrease of characteristic strength f_{yk} of tension and compression reinforcement	101
Figure C.3 - Sections of AAC components showing nominal axis distance a and nominal concrete cover c of reinforcement	103
Figure C.4- Reduction of strength and cross-section for sections exposed to fire	108

Figure C.5 - Division of a wall, with both sides exposed to fire, into zones for use in calculation of strength reduction and az values	108
Figure CA.1 -- Stress-strain relationship of AAC under compression at elevated temperature	111
Figure CA.2 -- Stress-strain relationship of reinforcing steel at elevated temperature	113
Figure CB.1 -- Example of a dry joint in structures made of floor or roof components with cover (e.g. topping) preventing movement of air through the joint	114
Figure CB.2 -- Examples of mortar joints in structures made of floor or roof components	114
Figure CB.3 -- Example of dry joints with two sealing strips in structures made of horizontal wall components	115
Figure CB.4 -- Examples of thin layer mortar joints in structures made of vertical or horizontal wall components	116
Figure CC.1 - Temperature profiles for AAC wall, floor and roof components with a dry density of 300 kg/m	117
Figure CC.2 - Temperature profiles for AAC wall, floor and roof components with a dry density of 400 kg/m	118
Figure CC.3 - Temperature profiles for AAC wall, floor and roof components with a dry density of 500 kg/m	118
Figure CC.4 - Temperature profiles for AAC wall, floor and roof components with a dry density of 600 kg/m	119
Figure CC.5 -- Temperature profiles of the non exposed face of component for the determination of the criteria of the classification to fire, for a dry density of 300 and 600 kg/m	120
Figure CC.6 - Temperature profiles in °C for AAC-beams (b x h = 150 mm x 200 mm) with a dry density of 300 kg/m , exposed on three sides to standard fire	120
Figure CC.7 - Temperature profiles in °C for AAC-beams (b x h = 150 mm x 200 mm) with a dry density of 400 kg/m , exposed on three sides to standard fire	121
Figure CC.8 - Temperature profiles in °C for AAC-beams (b x h = 150 mm x 200 mm) with a dry density of 500 kg/m , exposed on three sides to standard fire	122
Figure CC.9 - Temperature profiles in °C for AAC-beams (b x h = 150 mm x 200 mm) with a dry density of 600 kg/m , exposed on three sides to standard fire	122
Figure CC.10 - Temperature profiles in °C for AAC-beams (b x h = 300 mm x 400 mm) with a dry density of 300 kg/m , exposed on three sides to standard fire	123
Figure CC.11 - Temperature profiles in °C for AAC-beams (b x h = 300 mm x 400 mm) with a dry density of 400 kg/m , exposed on three sides to standard fire	124
Figure CC.12 - Temperature profiles in °C for AAC-beams (b x h = 300 mm x 400 mm) with a dry density of 500 kg/m , exposed on three sides to standard fire	125
Figure CC.13 - Temperature profiles in °C for AAC-beams (b x h = 300 mm x 400 mm) with a dry density of 600 kg/m , exposed on three sides to standard fire	126
Figure E.1 -- Analysis of prestress by means of an assumed external force	132
Figure ZA.1 - Example of CE marking with Method 1	152

Figure ZA.2 - Example of CE marking with Method 2	154
Figure ZA.3a - Example of CE marking with Method 3a	156
Figure ZA.3b - Example of CE marking with Method 3b	158
Figure ZA.4 -- Example of simplified label	159
Tables Table 1 -- Density classes	22
Table 2 -- Compressive strength classes for AAC	24
Table 3 -- Creep classes	26
Table 4 -- Dry thermal conductivity 10_{dry} of AAC for 50 % and 90 % of production with a confidence level of = 90 %	28
Table 5 -- Welding strength classes and welding strength factors k_W	29
Table 6 -- Bond classes	30
Table 7 -- Prestress classes	30
Table 8 -- Dimensional tolerances of components	33
Table 9 -- Final shrinkage strains ϵ_0 for AAC components	34
Table 10 -- Thickness classes of structural components	35
Table 11 -- Exposure classes and protective measures related to environmental conditions	38
Table 12 -- Initial type-testing of the AAC components	43
Table 13 -- Testing of the finished product; AAC components for structural uses	45
Table 14 -- Testing of the finished product; AAC components for non-structural uses	47
Table A.1 -- Bond Classes	81
Table B.1 -- Design loadbearing capacity R_{cd} of components	92
Table C.1 -- Thermal conductivity of AAC (λ) at elevated temperature	100
Table C.2 -- Minimum wall thickness of non loadbearing AAC walls with a dry density between 350 kg/m ³ and 700 kg/m ³	103
Table C.3a -- Minimum wall thickness and axis distance a_{min} for separating loadbearing AAC walls. AAC dry density 350 kg/m ³ to 700 kg/m ³ and structural or non-structural reinforcement for resistance to fire REI	104
Table C.3b -- Minimum wall thickness and minimum axis distance a_{min} for non separating loadbearing AAC walls supported on at least two opposite ends of the components. AAC dry density 350 kg/m ³ to 700 kg/m ³ and structural or non-structural reinforcement for resistance to fire R	104
Table C.4 -- Minimum dimensions (height h_{min} and width b_{min}) in mm and minimum axis distance a_{min} in mm to the bottom side and to the vertical sides of AAC beams in relation to the maximum span length	104
Table C.5 -- Minimum thickness h_{min} in mm and minimum axis distance a_{min} in mm of AAC floor and roof components in relation to maximum span length	105

Table C.6 -- Reduction of the dimensions of AAC cross-section from fire exposed surfaces	110
Table CA.1 --Values for the parameters of stress-strain relationship of AAC in compression at elevated temperature	111
Table CA.2 - Values for the parameters of stress-strain relationship of reinforcing steel at elevated temperature	112
Table CC.1	127
Table CC.2	127
Table CD.1 - Minimum wall thickness and minimum axis distance a_{min} of AAC walls with mechanical impact supported on at least two opposite ends; AAC dry density 450 kg/m to 700 kg/m with structural or non structural reinforcement for resistance to fire REI-M and EI-M	128
Table CD.2 -- Minimum amount of reinforcement for AAC components used in walls with mechanical impact	129
Table D.1 -- Safety parameter for failure type	130
Table D.2 -- Safety parameter for accuracy when determining the material parameter	130
Table D.3 -- Safety parameters depending on variation	131
Table D.4 -- Partial safety factors	131
Table F.1 -- Control factor k_n as a function of samples n with a fractile value of 5 % ($p = 0,95$) and a confidence level of 0,75 (using bayesian procedures with "vague" prior distribution) and under the assumption that the safety level (Annex D) is based on a summarised variation of $VR = 0,10$	137
Table F.2-- Coefficient k_s as a function of samples n with a fractile value of 5 % ($p = 0,95$) and a confidence level 0,75 (using bayesian procedures with "vague" prior distribution)	137
Table ZA.1a -- Harmonised clauses for loadbearing wall components	139
Table ZA.1b -- Harmonised clauses for retaining wall components	140
Table ZA.1c -- Harmonised clauses for roof components	141
Table ZA.1d -- Harmonised clauses for floor components	142
Table ZA.1e -- Harmonised clauses for linear components	143
Table ZA.1f -- Harmonised clauses for non-loadbearing wall and noise barriers components	144
Table ZA.1g -- Harmonised clauses for cladding components	145
Table ZA.1h -- Harmonised clauses for small box culvert components	146
Table ZA.2a -- Systems of attestation of conformity	147
Table ZA.2b -- Assignment of evaluation of conformity tasks (for structural components) under system 2+ 1)	147
Table ZA.2c -- Assignment of evaluation of conformity tasks (for non structural or light structural components) under system 4 1)	148