

DIN EN 14637:2008-01 (E)

Building hardware - Electrically controlled hold-open systems for fire/smoke door assemblies - Requirements, test methods, application and maintenance

Contents	Page
Foreword	5
Introduction	6
1 Scope	9
2 Normative references	9
3 Terms, definitions and abbreviated terms	11
4 Classification	13
4.1 Coding system	13
4.2 Category of use (first digit)	13
4.3 Durability (second digit)	13
4.4 Door type (third digit)	13
4.5 Suitability for use on fire/smoke door assemblies (fourth digit)	14
4.6 Safety (fifth digit)	14
4.7 Corrosion resistance (sixth digit)	14
4.8 Example of classification	14
5 Requirements and test methods for components of a hold-open system	15
5.1 General	15
5.2 Fire detectors	15
5.2.1 Smoke detectors	15
5.2.2 Heat detectors	15
5.2.3 Resetting the detectors	15
5.3 Power supply units	16
5.3.1 All power supply units	16
5.3.2 For power supply units with stand-by parallel operation	16
5.4 Control units	17
5.4.1 General	17
5.4.2 Control units in stand-alone hold-open systems (single-line systems)	17
5.4.3 Control units in fire detection and fire alarm systems (multi-line systems)	17
5.5 Hold-open devices	18
5.5.1 General	18
5.5.2 Hold-open devices for swing doors	18
5.5.3 Hold-open devices for sliding doors, lifting doors, industrial doors and roller shutters	18
5.5.4 Automatic door operators	19
5.5.5 Low energy/power assisted swing door operators	19
5.5.6 Free-swing door closers	20
5.6 Auxiliary equipment	20
5.6.1 Manual control push-buttons and switches	20
5.6.2 Presence sensors (electro-sensitive protective equipment)	20
5.6.3 Door position sensors	21
5.6.4 Remote indicating devices	21
5.6.5 Manual reset	21
6 Requirements for the hold-open system	21
6.1 Design and performance	21
6.2 Product information	22
6.2.1 General	22

6.2.2	For installation and maintenance	22
6.2.3	For initial hold-open system test	23
6.3	Requirements not covered under Clause 5	23
6.4	Electromagnetic compatibility (EMC)	23
6.5	Additional design requirements for connection of components to fire alarm systems	24
6.6	Electrical safety	24
6.7	Durability	24
6.8	Environmental behaviour	25
6.8.1	Dry heat	25
6.8.2	Cold	25
6.8.3	Damp heat, steady state (operational)	25
6.8.4	Corrosion	25
6.8.5	Vibration	25
6.9	Supply voltage variations	25
7	System tests	25
7.1	General	25
7.2	Test apparatus	26
7.3	Theoretical analysis	27
7.4	Test methods	27
7.4.1	General	27
7.4.2	Design verification	28
7.4.3	Performance tests	28
7.4.4	Check of switching device capabilities of the control unit	30
7.4.5	Short-circuit test	30
7.4.6	Electrical safety tests	30
7.4.7	Electromagnetic compatibility (EMC) tests	30
7.4.8	Environmental tests	31
7.4.9	Corrosion test	32
7.4.10	Vibration test, sinusoidal (operational)	33
7.4.11	Vibration test, sinusoidal (endurance)	33
8	Marking	35
8.1	Components	35
8.2	Hold-open system	35
A.1	General	36
A.2	Restrictions	36
A.3	Detectors	36
A.3.1	Selection of detector type	36
A.3.2	Positioning and number of detectors	37
A.4	Selection of hold-open device	43
A.4.1	General	43
A.4.2	Swing doors	43
A.4.3	Sliding doors	44
A.4.4	Roller shutter and lifting doors	44
A.4.5	Automatic doors	44
A.5	Manual release and manual control	44
A.5.1	General	44
A.5.2	Location of switch/push-button	45
A.6	Interconnecting cables	45
A.7	Guidance on competence and responsibilities for individual installations in individual buildings	45
A.7.1	Planning	45
A.7.2	Installation	45
E.1	Usage of installations	50
E.1.1	General	50
E.1.2	Periodic inspection	50

Annex C (informative) Recommendations for acceptance inspection of the hold-open system 47

Annex B (informative) Recommendations for installation and fixing of the hold-open system	46
Annex D (informative) Acceptance inspection report form	48
Annex E (informative) Recommendations for usage and maintenance of the hold-open system	50
Annex A (informative) Recommendations for planning and design of the hold-open system	36
E.2 F.1 General	52
F.1.1 Introduction	52
F.1.2 Initial type test	52
F.1.3 Characteristics	52
F.1.4 Use of historical data	53
F.1.5 Treatment of calculated values and design	53
F.1.6 Sampling, testing and conformity criteria	53
F.2 Factory production control (FPC)	53
F.2.1 General	53
F.2.2 FPC requirements for all manufacturers	54
F.3 Further testing of sample systems	54
F.3.1 Periodic testing	54
F.3.2 Yearly testing	54
F.3.3 Manufacturer-specific FPC system requirements	54
G.1 Test report	57
G.2 List of approved components	57
H.1 Introduction	58
H.2 Points for analysis	58
H.2.1 General	58
H.2.2 List of characteristics	58
Bibliography	62
Figure 1 -- Basic system components with essential functions	6
Figure 2 -- Typical system with additional functions and components	7
Figure 3 -- Logic diagram for modes of operation of an electrically controlled hold-open system	8
Figure A.1 -- Ceiling types and critical dimensions	38
Figure A.2 -- Installation area in accordance with A.3.2.1	39
Figure A.3 -- Flow chart to determine the requisite number of detectors	40
Figure A.4 -- Typical electrically controlled hold-open system with release of connected hold-open devices triggered directly by the FDAS (see A.3.2.2 a))	41
Figure A.5 -- Typical electrically controlled hold-open system with release of connected hold-open devices by the control unit of the hold-open system driven by the information coming from the FDAS (see A.3.2.2 b))	42
Table G.1 -- List of approved components	57
Routine site inspection report form	50
Annex G (informative) Type test report and list of approved components	57
Annex F (informative) Evaluation of conformity	52
Annex H (informative) Example methodology for theoretical analysis	58