

# ISO 24473:2008-04 (E)

## Fire tests - Open calorimetry - Measurement of the rate of production of heat and combustion products for fires of up to 40 MW

---

<b>Contents</b>		<b>Page</b>
1	Scope .....	1
2	Normative references .....	1
3	Terms and definitions .....	2
4	Principle .....	2
5	Hood and exhaust duct .....	3
5.1	Requirements of the hood/duct and extraction system .....	3
5.2	Laboratory requirements .....	3
6	Instrumentation of the exhaust duct .....	3
6.1	General .....	3
6.2	Volume flow rate .....	3
6.3	Gas temperature .....	4
6.4	Gas analysis .....	4
6.5	Optical density .....	5
7	Additional equipment and procedures .....	5
7.1	Weigh platform .....	5
7.2	Heat flux measurements .....	5
7.3	Data recorder .....	6
7.4	Timing device .....	6
8	Heat and smoke release measurement .....	6
9	Experimental arrangements .....	6
10	Ignition sources .....	6
10.1	General .....	6
10.2	Calibration of gas burners .....	7
11	System performance .....	7
11.1	HRR measurement confirmation .....	7
11.2	System response .....	8
11.3	Precision .....	8
12	Reliability of data .....	8
13	Preparation of test specimens .....	8
14	Testing .....	9
14.1	Initial conditions .....	9
14.2	Procedure .....	9
15	Test report .....	10
Annex A (informative) Design of the hood and exhaust system .....		11
Annex B (informative) Instrumentation of the exhaust duct .....		16
Annex C (informative) Procedure for checking the stability of the oxygen analyser .....		18
Annex D (informative) Light measuring systems .....		19

<b>Annex E (informative) Calculations .....</b>	<b>21</b>
<b>Annex F (informative) Ignition sources .....</b>	<b>25</b>
<b>Annex G (normative) Specific procedure for testing upholstered furniture .....</b>	<b>27</b>
<b>Annex H (informative) Repeatability and reproducibility .....</b>	<b>29</b>
<b>Bibliography .....</b>	<b>30</b>