

# DIN EN 15715:2010-04 (E)

## Thermal insulation products - Instructions for mounting and fixing for reaction to fire testing - Factory made products

---

<b>Contents</b>		<b>Page</b>
Foreword .....		5
<b>1</b>	<b>Scope .....</b>	<b>9</b>
<b>2</b>	<b>Normative references .....</b>	<b>9</b>
<b>3</b>	<b>Terms, definitions and abbreviated terms .....</b>	<b>9</b>
<b>3.1</b>	<b>Terms and definitions .....</b>	<b>9</b>
<b>3.2</b>	<b>Abbreviated terms used in this European Standard .....</b>	<b>10</b>
<b>4</b>	<b>Principle .....</b>	<b>10</b>
<b>5</b>	<b>Instructions for mounting and fixing of test specimens .....</b>	<b>11</b>
<b>5.1</b>	<b>General .....</b>	<b>11</b>
<b>5.2</b>	<b>Product and installation parameters .....</b>	<b>11</b>
<b>5.3</b>	<b>Mounting and fixing .....</b>	<b>12</b>
<b>5.3.1</b>	<b>Ignitability, EN ISO 11925-2 Exposure to thermal attack .....</b>	<b>12</b>
<b>5.3.2</b>	<b>Single Burning Item (SBI), EN 13823 .....</b>	<b>12</b>
<b>5.4</b>	<b>Validity of test results for product groups (Field of application) .....</b>	<b>18</b>
<b>6</b>	<b>Instructions for mounting and fixing of products in standardised assemblies simulating end-use application(s) .....</b>	<b>18</b>
<b>6.1</b>	<b>General .....</b>	<b>18</b>
<b>6.2</b>	<b>Product and installation parameters .....</b>	<b>19</b>
<b>6.3</b>	<b>Mounting and fixing .....</b>	<b>20</b>
<b>6.3.1</b>	<b>Ignitability, EN ISO 11925-2 .....</b>	<b>20</b>
<b>6.3.2</b>	<b>Single Burning Item (SBI) (EN 13823) .....</b>	<b>20</b>
<b>6.4</b>	<b>Validity of test result for a product group (Field of application) .....</b>	<b>25</b>
<b>Annex A (normative)</b>	<b>Product specific details .....</b>	<b>26</b>
<b>A.1</b>	<b>General .....</b>	<b>26</b>
<b>A.2</b>	<b>Mineral wool (MW) .....</b>	<b>26</b>
<b>A.3</b>	<b>Expanded polystyrene (EPS) .....</b>	<b>34</b>
<b>A.4</b>	<b>Extruded polystyrene foam (XPS) .....</b>	<b>39</b>
<b>A.5</b>	<b>Polyurethane and polyisocyanurate (PUR/PIR) .....</b>	<b>44</b>
<b>A.6</b>	<b>Phenolic Foam (PF) .....</b>	<b>50</b>
<b>A.7</b>	<b>Cellular Glass (CG) .....</b>	<b>56</b>
<b>A.8</b>	<b>Wood Wool (WW) .....</b>	<b>63</b>
<b>A.9</b>	<b>Expanded perlite (EPB) .....</b>	<b>67</b>
<b>A.10</b>	<b>Expanded cork (ICB) .....</b>	<b>70</b>
<b>A.11</b>	<b>Wood fibre (WF) .....</b>	<b>73</b>
<b>A.12</b>	<b>Flexible elastomeric foam (FEF) .....</b>	<b>76</b>
<b>A.13</b>	<b>Calcium silicate (CS) .....</b>	<b>82</b>
<b>A.14</b>	<b>Polyethylene foam (PEF) .....</b>	<b>88</b>
<b>Bibliography .....</b>		<b>94</b>
<b>Tables</b>	<b>Table 1 -- Product parameters .....</b>	<b>11</b>
	<b>Table 2 -- Installation parameters .....</b>	<b>12</b>

<b>Table 3 -- Thermal insulation product parameters in standardised assemblies .....</b>	<b>19</b>
<b>Table 4 -- Installation parameters of standardised assemblies .....</b>	<b>19</b>
<b>Table 5 -- Standard test configurations of standardised assemblies .....</b>	<b>21</b>
<b>Table A.1 -- Product parameters for MW - flat products, when tested as placed on the market or in standard test configuration of assemblies .....</b>	<b>26</b>
<b>Table A.2 -- Installation parameters for MW - flat products, as placed on the market .....</b>	<b>29</b>
<b>Table A.3 -- Product parameters for MW - pipe insulation products, as placed on the market .....</b>	<b>30</b>
<b>Table A.4 -- Installation parameters for MW - pipe insulation products, as placed on the market .....</b>	<b>31</b>
<b>Table A.5 -- Installation parameters for MW - flat products in standard test configuration of assemblies, simulating end-use applications .....</b>	<b>32</b>
<b>Table A.6 -- Product parameters for EPS - flat products, when tested as placed on the market or in standard test configuration of assemblies .....</b>	<b>34</b>
<b>Table A.7 -- Installation parameters for EPS - flat products as placed on the market .....</b>	<b>35</b>
<b>Table A.8 -- Product parameters for EPS - pipe insulation products, as placed on the market .....</b>	<b>36</b>
<b>Table A.9 -- Installation parameters for EPS - pipe insulation products, as placed on the market .....</b>	<b>37</b>
<b>Table A.10 -- Installation parameters for EPS - flat products in standard test configuration of assemblies, simulating end-use applications .....</b>	<b>38</b>
<b>Table A.11 -- Product parameters for XPS - flat products when tested as placed on the market or in standard test configuration of assemblies .....</b>	<b>39</b>
<b>Table A.12-- Installation parameters for XPS - flat products as placed on the market .....</b>	<b>40</b>
<b>Table A.13 -- Product parameters for XPS - pipe insulation products, as placed on the market .....</b>	<b>41</b>
<b>Table A.14 -- Installation parameters for XPS - pipe insulation products, as placed on the market ...</b>	<b>42</b>
<b>Table A.15 -- Installation parameters for XPS - flat products in standard test configuration of assemblies, simulating end-use applications .....</b>	<b>43</b>
<b>Table A.16 -- Product parameters for PUR/PIR - flat products when tested as placed on the market or in standard test configuration of assemblies .....</b>	<b>44</b>
<b>Table A.17 -- Installation parameters for PUR/PIR - flat products, as placed on the market .....</b>	<b>45</b>
<b>Table A.18 -- Product parameters for PUR/PIR - pipe insulation products, as placed on the market .</b>	<b>46</b>
<b>Table A.19 -- Installation parameters for PUR/PIR - pipe insulation products, as placed on the market .....</b>	<b>47</b>
<b>Table A.20 -- Installation parameters for PUR/ PIR - flat products in standard test configuration of assemblies, simulating end-use applications .....</b>	<b>48</b>
<b>Table A.21 -- Product parameters for PF - flat products, when tested as placed on the market or in standard test configuration of assemblies .....</b>	<b>50</b>
<b>Table A.22 -- Installation parameters for PF - flat products, as placed on the market .....</b>	<b>51</b>
<b>Table A.23 -- Product parameters for PF - pipe insulation products, as placed on the market .....</b>	<b>52</b>

Table A.24 -- Installation parameters for PF - pipe insulation products, as placed on the market .....	53
Table A.25 -- Installation parameters for PF - flat products in standard test configuration of assemblies, simulating end-use applications .....	54
Table A.26 -- Product parameters for CG - flat products when tested as placed on the market or in standard test configuration of assemblies .....	56
Table A.27 -- Installation parameters for CG - flat products, as placed on the market .....	58
Table A.28 -- Product parameters for CG - pipe insulation products a , as placed on the market .....	59
Table A.29 -- Installation parameters for CG- linear pipe thermal insulation .....	60
Table A.30-- Installation parameters for CG -- flat products, in standard test configuration of assemblies simulating end-use applications .....	61
Table A.31 -- Product parameters for WW -- flat products, when tested as placed on the market or in standard test configuration of assemblies .....	63
Table A.31 (continued) .....	64
Table A.32 -- Installation parameters WW -- flat products, as placed on the market .....	65
Table A.33 -- Installation parameters for WW - flat products in standard test configuration of assemblies simulating end-use applications .....	66
Table A.34 -- Product parameters for EPB - flat products, when tested as placed on the market or in standard test configuration of assemblies .....	67
Table A.35-- Installation parameters for EPB - flat products, as placed on the market .....	68
Table A.36-- Installation parameters for EPB - flat products in standard test configuration of assemblies simulating end-use applications .....	69
Table A.37 -- Product parameters for ICB flat products, when tested as placed on the market or in standard test configuration of assemblies .....	70
Table A. 38-- Installation parameters for ICB - flat products, as placed on the market .....	71
Table A.39 -- Installation parameters for ICB - flat products in standard test configuration of assemblies simulating end-use applications .....	72
Table A.40 -- Product parameters for WF - flat products, when tested as placed on the market or in standard test configuration of assemblies .....	73
Table A.41-- Installation parameters for WF - flat products, as placed on the market .....	74
Table A.42-- Installation parameters for WF - flat products, in standard test configuration of assemblies simulating end-use applications .....	75
Table A.43 -- Product parameters for FEF - flat products, when tested as placed on the market or in standard test configuration of assemblies .....	76
Table A.44 -- Installation parameters for FEF - flat products, as placed on the market .....	77
Table A.45 -- Product parameters for FEF - pipe insulation products, as placed on the market .....	78
Table A.46 -- Installation parameters for FEF - pipe insulation products, as placed on the market ....	79

<b>Table A.47 -- Installation parameters for FEF - for flat products in standard test configuration of assemblies simulating end-use applications .....</b>	<b>80</b>
<b>Table A.48 -- Product parameters for CS - flat products when tested as placed on the market or in standard test configuration of assemblies .....</b>	<b>82</b>
<b>Table A.49 -- Installation Parameters for CS - flat products as placed on the market .....</b>	<b>83</b>
<b>Table A.50 - Product parameters for CS - pipe insulation products, as placed on the market .....</b>	<b>84</b>
<b>Table A.51 - Installation parameters for CS - pipe insulation products, as placed on the market .....</b>	<b>85</b>
<b>Table A.52 -- Installation parameters for CS - flat products in standard test configuration of assemblies simulating end-use applications .....</b>	<b>86</b>
<b>Table A.53 -- Product parameters for PEF, flat products when tested as placed on the market or in standard test configuration of assemblies .....</b>	<b>88</b>
<b>Table A.54 -- Installation parameters for PEF flat products, as placed on the market .....</b>	<b>89</b>
<b>Table A.55 -- Product parameters for PEF - pipe insulation products as placed on the market .....</b>	<b>90</b>
<b>Table A.56 -- Installation parameters for PEF - pipe insulation products as placed on the market ....</b>	<b>91</b>
<b>Table A.57 -- Installation parameters for PEF - for flat products in standard test configuration of assemblies simulating end-use applications .....</b>	<b>92</b>
<b>Figures Figure 1 -- Installation of specimen according to EN 13823 .....</b>	<b>15</b>
<b>Figure 2 -- Principle of positioning of minimum mechanical fixings .....</b>	<b>16</b>
<b>Figure 3 -- Joint arrangement for a product tested uncovered (front view) .....</b>	<b>16</b>
<b>Figure 4 -- Schematic drawings of the mounting of the test specimens in the SBI in the case of 25 mm insulation thickness .....</b>	<b>17</b>
<b>Figure 5 -- Fixing corrugated steel sheet (New figure is being drawn) .....</b>	<b>24</b>