DIN EN 15715:2010-04 (E)

Thermal insulation products - Instructions for mounting and fixing for reaction to fire testing - Factory made products

Contents

Page

Foreword 5

1 Scope 9

2 Normative references 9

3 Terms, definitions and abbreviated terms 9
3.1 Terms and definitions 9
3.2 Abbreviated terms used in this European Standard 10

4 Principle 10

5 Instructions for mounting and fixing of test specimens 11
5.1 General 11
5.2 Product and installation parameters 11
5.3 Mounting and fixing 12
5.3.1 Ignitability, EN ISO 11925-2 Exposure to thermal attack 12
5.3.2 Single Burning Item (SBI), EN 13823 12
5.4 Validity of test results for product groups (Field of application) 18

6 Instructions for mounting and fixing of products in standardised assemblies simulating end-use application(s) 18
6.1 General 18
6.2 Product and installation parameters 19
6.3 Mounting and fixing 20
6.3.1 Ignitability, EN ISO 11925-2 20
6.3.2 Single Burning Item (SBI) (EN 13823) 20
6.4 Validity of test result for a product group (Field of application) 25

Annex A (normative) Product specific details 26

A.1 General 26
A.2 Mineral wool (MW) 26
A.3 Expanded polystyrene (EPS) 34
A.4 Extruded polystyrene foam (XPS) 39
A.5 Polyurethane and polyisocyanurate (PUR/PIR) 44
A.6 Phenolic Foam (PF) 50
A.7 Cellular Glass (CG) 56
A.8 Wood Wool (WW) 63
A.9 Expanded perlite (EPB) 67
A.10 Expanded cork (ICB) 70
A.11 Wood fibre (WF) 73
A.12 Flexible elastomeric foam (FEF) 76
A.13 Calcium silicate (CS) 82
A.14 Polyethylene foam (PEF) 88

Bibliography 94

Tables Table 1 -- Product parameters 11

Table 2 -- Installation parameters 12

Table 3 -- Thermal insulation product parameters in standardised assemblies 19

Table 4 -- Installation parameters of standardised assemblies 19

Table 5 -- Standard test configurations of standardised assemblies 21

Table A.1 -- Product parameters for MW - flat products, when tested as placed on the market or in standard test configuration of assemblies 26

Table A.2 -- Installation parameters for MW - flat products, as placed on the market 29

Table A.3 -- Product parameters for MW - pipe insulation products, as placed on the market 30

Table A.4 -- Installation parameters for MW - pipe insulation products, as placed on the market 31

Table A.5 -- Installation parameters for MW - flat products in standard test configuration of assemblies, simulating end-use applications 32

Table A.6 -- Product parameters for EPS - flat products, when tested as placed on the market or in standard test configuration of assemblies 34

Table A.7 -- Installation parameters for EPS - flat products as placed on the market 35

Table A.8 -- Product parameters for EPS - pipe insulation products, as placed on the market 36

Table A.9 -- Installation parameters for EPS - pipe insulation products, as placed on the market 37

Table A.10 -- Installation parameters for EPS - flat products in standard test configuration of assemblies, simulating end-use applications 38

Table A.11 -- Product parameters for XPS - flat products when tested as placed on the market or in standard test configuration of assemblies 39

Table A.12-- Installation parameters for XPS - flat products as placed on the market 40

Table A.13 -- Product parameters for XPS - pipe insulation products, as placed on the market 41

Table A.14 -- Installation parameters for XPS - pipe insulation products, as placed on the market ... 42

Table A.15 -- Installation parameters for XPS - flat products in standard test configuration of assemblies, simulating end-use applications 43

Table A.16 -- Product parameters for PUR/PIR - flat products when tested as placed on the market or in standard test configuration of assemblies 44

Table A.17 -- Installation parameters for PUR/PIR - flat products, as placed on the market 45

Table A.18 -- Product parameters for PUR/PIR - pipe insulation products, as placed on the market . 46

Table A.19 -- Installation parameters for PUR/PIR - pipe insulation products, as placed on the market 47

Table A.20 -- Installation parameters for PUR/ PIR - flat products in standard test configuration of assemblies, simulating end-use applications 48

Table A.21 -- Product parameters for PF - flat products, when tested as placed on the market or in standard test configuration of assemblies 50

Table A.22 -- Installation parameters for PF - flat products, as placed on the market 51

Table A.23 -- Product parameters for PF - pipe insulation products, as placed on the market 52

Table A.24 -- Installation parameters for PF - pipe insulation products, as placed on the market 53

Table A.25 -- Installation parameters for PF - flat products in standard test configuration of assemblies, simulating end-use applications 54

Table A.26 -- Product parameters for CG - flat products when tested as placed on the market or in standard test configuration of assemblies 56

Table A.27 -- Installation parameters for CG - flat products, as placed on the market 58

Table A.28 -- Product parameters for CG - pipe insulation products a , as placed on the market 59

Table A.29 -- Installation parameters for CG- linear pipe thermal insulation 60

Table A.30-- Installation parameters for CG -- flat products, in standard test configuration of assemblies simulating end-use applications 61

Table A.31 -- Product parameters for WW -- flat products, when tested as placed on the market or in standard test configuration of assemblies 63

Table A.31 (continued) 64

Table A.32 -- Installation parameters WW -- flat products, as placed on the market 65

Table A.33 -- Installation parameters for WW - flat products in standard test configuration of assemblies simulating end-use applications 66

Table A.34 -- Product parameters for EPB - flat products, when tested as placed on the market or in standard test configuration of assemblies 67

Table A.35-- Installation parameters for EPB - flat products, as placed on the market 68

Table A.36-- Installation parameters for EPB - flat products in standard test configuration of assemblies simulating end-use applications 69

Table A.37 -- Product parameters for ICB flat products, when tested as placed on the market or in standard test configuration of assemblies 70

Table A. 38-- Installation parameters for ICB - flat products, as placed on the market 71

Table A.39 -- Installation parameters for ICB - flat products in standard test configuration of assemblies simulating end-use applications 72

Table A.40 -- Product parameters for WF - flat products, when tested as placed on the market or in standard test configuration of assemblies 73

Table A.41-- Installation parameters for WF - flat products, as placed on the market 74

Table A.42-- Installation parameters for WF - flat products, in standard test configuration of assemblies simulating end-use applications 75

Table A.43 -- Product parameters for FEF - flat products, when tested as placed on the market or in standard test configuration of assemblies 76

Table A.44 -- Installation parameters for FEF - flat products, as placed on the market 77

Table A.45 -- Product parameters for FEF - pipe insulation products, as placed on the market 78

Table A.46 -- Installation parameters for FEF - pipe insulation products, as placed on the market 79

Table A.47 -- Installation parameters for FEF - for flat products in standard test configuration of assemblies simulating end-use applications 80

Table A.48 -- Product parameters for CS - flat products when tested as placed on the market or in standard test configuration of assemblies 82

Table A.49 -- Installation Parameters for CS - flat products as placed on the market 83

Table A.50 - Product parameters for CS - pipe insulation products, as placed on the market 84

Table A.51 - Installation parameters for CS - pipe insulation products, as placed on the market 85

Table A.52 -- Installation parameters for CS - flat products in standard test configuration of assemblies simulating end-use applications 86

Table A.53 -- Product parameters for PEF, flat products when tested as placed on the market or in standard test configuration of assemblies 88

Table A.54 -- Installation parameters for PEF flat products, as placed on the market 89

Table A.55 -- Product parameters for PEF - pipe insulation products as placed on the market 90

Table A.56 -- Installation parameters for PEF - pipe insulation products as placed on the market 91

Table A.57 -- Installation parameters for PEF - for flat products in standard test configuration of assemblies simulating end-use applications 92

Figures Figure 1 -- Installation of specimen according to EN 13823 15

Figure 2 -- Principle of positioning of minimum mechanical fixings 16

Figure 3 -- Joint arrangement for a product tested uncovered (front view) 16

Figure 4 -- Schematic drawings of the mounting of the test specimens in the SBI in the case of 25 mm insulation thickness 17

Figure 5 -- Fixing corrugated steel sheet (New figure is being drawn) 24