

# DIN 18218:2010-01 (E)

## Pressure of fresh concrete on vertical formwork

---

| <b>Contents</b>   |   | <b>Page</b> |
|---|---|-------------|
| Foreword .....  |   | 3           |
| <b>1</b>  | <b>Scope .....</b>  | <b>4</b>    |
| <b>2</b>  | <b>Normative references .....</b>   | <b>4</b>    |
| <b>3</b>  | <b>Terms, definitions and symbols .....</b>   | <b>4</b>    |
| <b>3.1</b>  | <b>Terms and definitions .....</b>  | <b>4</b>    |
| <b>3.2</b>  | <b>Symbols .....</b>  | <b>6</b>    |
| <b>3.3</b>  | <b>Subscripts .....</b>   | <b>6</b>    |
| <b>4</b>  | <b>Fresh concrete pressure .....</b>  | <b>6</b>    |
| <b>4.1</b>  | <b>General .....</b>  | <b>6</b>    |
| <b>4.2</b>  | <b>Design value of fresh concrete pressure .....</b>  | <b>6</b>    |
| <b>4.3</b>  | <b>Distribution of fresh concrete pressure over the height of the formwork .....</b>          | <b>7</b>    |
| <b>4.4</b>  | <b>Determination of the characteristic value of the maximum fresh concrete pressure .....</b> | <b>8</b>    |
| <b>5</b>  | <b>Parameters affecting the magnitude of fresh concrete pressure .....</b>                    | <b>9</b>    |
| <b>5.1</b>  | <b>General .....</b>  | <b>9</b>    |
| <b>5.2</b>  | <b>End of setting .....</b>   | <b>10</b>   |
| <b>5.3</b>  | <b>Temperature .....</b>  | <b>10</b>   |
| <b>5.4</b>  | <b>Fresh concrete density .....</b>   | <b>11</b>   |
| <b>5.5</b>  | <b>Compaction .....</b>   | <b>11</b>   |
| <b>5.6</b>  | <b>Admixtures and additives .....</b>   | <b>11</b>   |
| <b>5.7</b>  | <b>Vibrations .....</b>   | <b>12</b>   |
| <b>5.8</b>  | <b>Reinforcement .....</b>  | <b>12</b>   |
| <b>Annex A (normative) Determination of setting times by the "knead bag" method .....</b>             |   | <b>13</b>   |
| <b>A.1</b>  | <b>General .....</b>  | <b>13</b>   |
| <b>A.2</b>  | <b>Apparatus .....</b>  | <b>13</b>   |
| <b>A.3</b>  | <b>Sampling and test procedure .....</b>  | <b>13</b>   |
| <b>A.4</b>  | <b>Test report .....</b>  | <b>14</b>   |
| <b>Annex B (normative) Diagrams to determine the maximum value of lateral fresh concrete pressure</b> |   | <b>15</b>   |