ISO/TR 16738:2009-08 (E)

Fire-safety engineering - Technical information on methods for evaluating behaviour and movement of people

Contents

Page

Foreword iv

Introduction v

1 Scope 1

2 Normative references 1

3 Terms and definitions 1

4 Symbols 3

5 Integration of behaviour and movement into performance-based design 4
5.1 General 4
5.2 Basis of performance-based design for life safety 4
5.3 ASET calculations 4
5.4 RSET calculations 5
5.5 Evacuation strategies 6
5.6 Margin of safety 6
5.7 Elements used in the quantification of RSET 6

6 Design behavioural scenarios for quantification of RSET 8

7 Estimation of pre-travel activity times 9

8 Estimation of travel times 9

9 Interactions between pre-travel activity time, walking time and exit flow time 10

10 Calculation of escape and evacuation times for single enclosures and for multi-storey or multi-enclosure buildings 11
11 Effects of fire effluent and heat on ASET and RSET 12
11.1 General 12
11.2 Simple criteria based upon zero exposure 13
11.3 Willingness to enter smoke 14
11.4 Ability to move through smoke 14
11.5 Effects of smoke on walking speed 14
11.6 Effects of visibility or exposure to fire and heat 14
11.7 Effects of exposure to toxic gases 15

Annex A (informative) Guidance on the evaluation of detection and warning times 16

Annex B (informative) Pre-travel activity behaviours and determinants 18

Annex C (informative) Detailed information needed for RSET calculations 20

Annex D (informative) Design behavioural scenarios for derivation of default RSET variables 23

Annex E (informative) Pre-travel activity time distribution data and derivations 30

Annex F (informative) Evacuation start time of the verification methods for safe evacuation in Japan 38

Annex G (informative) Guidance on travel speeds and flow rates 40

Annex H (informative) Examples of interactions between pre-travel activity and travel times 52

Annex I (informative) Effects of smoke on walking speed 55

Bibliography 57