

# DIN EN 15651-1:2010-06 (E)

## Sealants for non-structural use in joints in buildings and pedestrian walkways - Part 1: Sealants for facade elements

---

<b>Contents</b>		<b>Page</b>
Foreword .....		3
<b>1</b>	<b>Scope .....</b>	<b>4</b>
<b>2</b>	<b>Normative references .....</b>	<b>4</b>
<b>3</b>	<b>Terms and definitions .....</b>	<b>5</b>
<b>4</b>	<b>Requirements .....</b>	<b>5</b>
<b>4.1</b>	<b>Identification requirements and test methods .....</b>	<b>5</b>
<b>4.1.1</b>	<b>Short description of the sealant .....</b>	<b>5</b>
<b>4.1.2</b>	<b>Thermogravimetric test .....</b>	<b>6</b>
<b>4.1.3</b>	<b>Specific gravity .....</b>	<b>6</b>
<b>4.1.4</b>	<b>Indentation hardness (Shore hardness) .....</b>	<b>6</b>
<b>4.2</b>	<b>Conditioning, test procedure and substrates .....</b>	<b>6</b>
<b>4.3</b>	<b>Performance requirements and test methods for non-structural sealants for facade elements .....</b>	<b>7</b>
<b>4.3.1</b>	<b>General .....</b>	<b>7</b>
<b>4.3.2</b>	<b>Sealants for facade elements used in cold climates .....</b>	<b>8</b>
<b>4.3.3</b>	<b>Resistance to flow .....</b>	<b>9</b>
<b>4.4</b>	<b>Performance requirements for non-structural sealants for facade elements for interior application only .....</b>	<b>9</b>
<b>4.5</b>	<b>Reaction to fire .....</b>	<b>9</b>
<b>4.5.1</b>	<b>General .....</b>	<b>9</b>
<b>4.5.2</b>	<b>Mounting and fixing conditions for test samples .....</b>	<b>9</b>
<b>5</b>	<b>Durability .....</b>	<b>10</b>
<b>6</b>	<b>Sampling .....</b>	<b>10</b>
<b>7</b>	<b>Evaluation of conformity .....</b>	<b>10</b>
<b>7.1</b>	<b>General .....</b>	<b>10</b>
<b>7.2</b>	<b>Initial type testing .....</b>	<b>10</b>
<b>7.3</b>	<b>Factory production control .....</b>	<b>11</b>
<b>8</b>	<b>Marking and labelling .....</b>	<b>11</b>
<b>Annex A (informative) Example on the frequency of tests for factory production control .....</b>		<b>12</b>