

DIN EN 459-2:2010-12 (E)

Building lime - Part 2: Test methods

Contents		Page
Foreword		3
Introduction		4
1	Scope	5
2	Normative references	5
3	Sampling	5
3.1	General	5
3.2	Sampling of powdered material	5
3.3	Sampling of granular material	5
3.4	Sampling of lime putty and milk of lime	5
3.5	Preparation of the test portion	6
4	General requirements for testing	6
4.1	Number of tests	6
4.2	Repeatability and reproducibility	7
4.3	Expression of masses, volumes, factors and results	7
4.4	Blank determinations	7
4.5	Reagents	7
4.6	Evaluation of test results	8
5	Chemical analysis	8
5.1	Extraction with hydrochloric acid	8
5.2	Calcium oxide (CaO) and magnesium oxide (MgO)	9
5.3	Sulfate (expressed as SO ₃)	12
5.4	Free water	14
5.5	Gravimetric determination of carbon dioxide (CO ₂) (reference method)	15
5.6	Volumetric determination of carbon dioxide (CO ₂) (alternative method)	18
5.7	Loss on ignition	21
5.8	Available lime	22
6	Physical tests	24
6.1	Particle size by dry sieving	24
6.2	Particle size by air-jet sieving	25
6.3	Bulk density	27
6.4	Soundness	30
6.5	Setting times	37
6.6	Reactivity	41
6.7	Yield	47
6.8	Standard mortar by mass and water demand for values of flow and penetration	48
6.9	Water retention	53
6.10	Determination of air content	55
6.11	Compressive strength	57
	Annex A (informative) Example for the calculation of the results on sieving	61
	Annex B (informative) Precision data for the test methods	62
	Bibliography	64