

DIN EN 1991-1-4:2010-12 (E)

Eurocode 1: Actions on structures – Part 1-4: General actions – Wind actions
(includes Amendment A1:2010 + Corrigendum AC:2010) English translation of DIN EN 1991-1-4:2010-12

| Contents | Page |
|-------------------------------------------------------------|-----------|
| Foreword to EN 1991-1-4:2005 | 5 |
| A1) Foreword to EN 1991-1-4:2005/A1:2010 | 5 |
| Section 1 General | 10 |
| 1.1 Scope | 10 |
| 1.2 Normative references | 11 |
| 1.3 Assumptions | 11 |
| 1.4 Distinction between Principles and Application Rules | 11 |
| 1.5 Design assisted by testing and measurements | 11 |
| 1.6 Definitions | 11 |
| 1.7 Symbols | 12 |
| Section 2 Design situations | 17 |
| Section 3 Modelling of wind actions | 18 |
| 3.1 Nature | 18 |
| 3.2 Representations of wind actions | 18 |
| 3.3 Classification of wind actions | 18 |
| 3.4 Characteristic values | 18 |
| 3.5 Models | 18 |
| Section 4 Wind velocity and velocity pressure | 19 |
| 4.1 Basis for calculation | 19 |
| 4.2 Basic values | 19 |
| 4.3 Mean wind | 20 |
| 4.3.1 Variation with height | 20 |
| 4.3.2 Terrain roughness | 20 |
| 4.3.3 Terrain orography | 22 |
| 4.3.4 Large and considerably higher neighbouring structures | 22 |
| 4.3.5 Closely spaced buildings and obstacles | 23 |
| 4.4 Wind turbulence | 23 |
| 4.5 Peak velocity pressure | 23 |
| Section 5 Wind actions | 25 |
| 5.1 General | 25 |
| 5.2 Wind pressure on surfaces | 25 |
| 5.3 Wind forces | 26 |
| Section 6 Structural factor $c_s c_d$ | 29 |
| 6.1 General | 29 |
| 6.2 Determination of $c_s c_d$ | 29 |
| 6.3 Detailed procedure | 29 |
| 6.3.1 Structural factor $c_s c_d$ | 29 |
| 6.3.2 Serviceability assessments | 31 |
| 6.3.3 Wake buffeting | 31 |
| Section 7 Pressure and force coefficients | 32 |
| 7.1 General | 32 |
| 7.1.1 Choice of aerodynamic coefficient | 32 |
| 7.1.2 Asymmetric and counteracting pressures and forces | 33 |
| 7.1.3 Effects of ice and snow | 33 |
| 7.2 Pressure coefficients for buildings | 34 |
| 7.2.1 General | 34 |
| 7.2.2 Vertical walls of rectangular plan buildings | 35 |
| 7.2.3 Flat roofs | 38 |
| 7.2.4 Monopitch roofs | 41 |
| 7.2.5 Duopitch roofs | 44 |
| 7.2.6 Hipped roofs | 48 |
| 7.2.7 Multispan roofs | 49 |
| 7.2.8 Vaulted roofs and domes | 51 |

| | | |
|------------------------------|-----------------------------------------------------------------------------------------------|------------|
| 7.2.9 | Internal pressure | 52 |
| 7.2.10 | Pressure on walls or roofs with more than one skin | 54 |
| 7.3 | Canopy roofs | 55 |
| 7.4 | Free-standing walls, parapets, fences and signboards | 62 |
| 7.4.1 | Free-standing walls and parapets | 62 |
| 7.4.2 | Shelter factors for walls and fences | 64 |
| 7.4.3 | Signboards | 64 |
| 7.5 | Friction coefficients | 65 |
| 7.6 | Structural elements with rectangular sections | 66 |
| 7.7 | Structural elements with sharp edged section | 68 |
| 7.8 | Structural elements with regular polygonal section | 68 |
| 7.9 | Circular cylinders | 70 |
| 7.9.1 | External pressure coefficients | 70 |
| 7.9.2 | Force coefficients | 72 |
| 7.9.3 | Force coefficients for vertical cylinders in a row arrangement | 75 |
| 7.10 | Spheres | 75 |
| 7.11 | Lattice structures and scaffoldings | 77 |
| 7.12 | Flags | 79 |
| 7.13 | Effective slenderness λ and end-effect factor ψ_λ | 81 |
| Section 8 | Wind actions on bridges | 83 |
| 8.1 | General | 83 |
| 8.2 | Choice of the response calculation procedure | 86 |
| 8.3 | Force coefficients | 86 |
| 8.3.1 | Force coefficients in x-direction (general method) | 86 |
| 8.3.2 | Force in x-direction – Simplified Method | 89 |
| 8.3.3 | Wind forces on bridge decks in z-direction | 90 |
| 8.3.4 | Wind forces on bridge decks in y-direction | 91 |
| 8.4 | Bridge piers | 92 |
| 8.4.1 | Wind directions and design situations | 92 |
| 8.4.2 | Wind effects on piers | 92 |
| Annex A (informative) | Terrain effects | 93 |
| A.1 | Illustrations of the upper roughness of each terrain category | 93 |
| A.2 | Transition between roughness categories 0, I, II, III and IV | 94 |
| A.3 | Numerical calculation of orography coefficients | 96 |
| A.4 | Neighbouring structures | 101 |
| A.5 | Displacement height | 102 |
| Annex B (informative) | Procedure 1 for determining the structural factor $c_s c_d$ | 103 |
| B.1 | Wind turbulence | 103 |
| B.2 | Structural factor | 104 |
| B.3 | Number of loads for dynamic response | 106 |
| B.4 | Service displacement and accelerations for serviceability assessments of a vertical structure | 106 |
| Annex C (informative) | Procedure 2 for determining the structural factor $c_s c_d$ | 109 |
| C.1 | Wind turbulence | 109 |
| C.2 | Structural factor | 109 |
| C.3 | Number of loads for dynamic response | 110 |
| C.4 | Service displacement and accelerations for serviceability assessments | 110 |
| Annex D (informative) | $c_s c_d$ values for different types of structures | 112 |
| Annex E (informative) | Vortex shedding and aeroelastic instabilities | 115 |
| E.1 | Vortex shedding | 115 |
| E.1.1 | General | 115 |
| E.1.2 | Criteria for vortex shedding | 115 |
| E.1.3 | Basic parameters for vortex shedding | 116 |
| E.1.4 | Vortex shedding action | 119 |
| E.1.5 | Calculation of the cross wind amplitude | 119 |
| E.1.6 | Measures against vortex induced vibrations | 129 |
| E.2 | Galloping | 130 |
| E.2.1 | General | 130 |

| | |
|--------------------------------------------------------------------|------------|
| E.2.2 Onset wind velocity | 130 |
| E.2.3 Classical galloping of coupled cylinders | 132 |
| E.3 Interference galloping of two or more free standing cylinders | 134 |
| E.4 Divergence and Flutter | 135 |
| E.4.1 General | 135 |
| E.4.2 Criteria for plate-like structures | 135 |
| E.4.3 Divergency velocity | 135 |
| Annex F (informative) Dynamic characteristics of structures | 137 |
| F.1 General | 137 |
| F.2 Fundamental frequency | 137 |
| F.3 Fundamental mode shape | 142 |
| F.4 Equivalent mass | 144 |
| F.5 Logarithmic decrement of damping | 144 |
| Bibliography | 147 |