

DIN EN 1995-1-2: 2010-12(E)

Eurocode_5: Design of timber structures_ - Part_1-2: General_ - Structural fire design (includes Corrigendum AC:2009)

Contents

| | |
|---|----|
| Foreword to EN 1995-1-2:2004 + AC:2009 | 4 |
| Background of the Eurocode programme | 4 |
| Status and field of application of Eurocodes | 5 |
| National Standards implementing Eurocodes | 5 |
| Links between Eurocodes and harmonised technical specifications (ENs and ETAs) for products | 6 |
| Additional information specific to EN 1995-1-2 | 6 |
| National annex for EN 1995-1-2 | 7 |
| Section 1 General | 9 |
| 1.1 Scope | 9 |
| 1.1.1 Scope of Eurocode 5 | 9 |
| 1.1.2 Scope of EN 1995-1-2 | 9 |
| 1.2 Normative references | 10 |
| 1.3 Assumptions | 10 |
| 1.4 Distinction between principles and application rules | 10 |
| 1.5 Terms and definitions | 11 |
| 1.6 Symbols | 11 |
| Section 2 Basis of design | 14 |
| 2.1 Requirements | 14 |
| 2.1.1 Basic requirements | 14 |
| 2.1.2 Nominal fire exposure | 14 |
| 2.1.3 Parametric fire exposure | 14 |
| 2.2 Actions | 15 |
| 2.3 Design values of material properties and resistances | 15 |
| 2.4 Verification methods | 16 |
| 2.4.1 General | 16 |
| 2.4.2 Member analysis | 17 |
| 2.4.3 Analysis of parts of the structure | 18 |
| 2.4.4 Global structural analysis | 19 |
| Section 3 Material properties | 20 |
| 3.1 General | 20 |
| 3.2 Mechanical properties | 20 |
| 3.3 Thermal properties | 20 |
| 3.4 Charring depth | 20 |
| 3.4.1 General | 20 |
| 3.4.2 Surfaces unprotected throughout the time of fire exposure | 21 |
| 3.4.3 Surfaces of beams and columns initially protected from fire exposure | 23 |
| 3.4.3.1 General | 23 |
| 3.4.3.2 Charring rates | 26 |
| 3.4.3.3 Start of charring | 27 |
| 3.4.3.4 Failure times of fire protective claddings | 28 |
| 3.5 Adhesives | 29 |
| Section 4 Design procedures for mechanical resistance | 30 |
| 4.1 General | 30 |
| 4.2 Simplified rules for determining cross-sectional properties | 30 |
| 4.2.1 General | 30 |
| 4.2.2 Reduced cross-section method | 30 |
| 4.2.3 Reduced properties method | 31 |
| 4.3 Simplified rules for analysis of structural members and components | 32 |
| 4.3.1 General | 32 |
| 4.3.2 Beams | 32 |
| 4.3.3 Columns | 33 |
| 4.3.4 Mechanically jointed members | 33 |
| 4.3.5 Bracings | 34 |
| 4.4 Advanced calculation methods | 34 |
| Section 5 Design procedures for wall and floor assemblies | 35 |

| | | |
|-----------------------|---|----|
| 5.1 | General | 35 |
| 5.2 | Analysis of load-bearing function | 35 |
| 5.3 | Analysis of separating function | 35 |
| Section 6 | Connections | 36 |
| 6.1 | General | 36 |
| 6.2 | Connections with side members of wood | 36 |
| 6.2.1 | Simplified rules | 36 |
| 6.2.1.1 | Unprotected connections | 36 |
| 6.2.1.2 | Protected connections | 37 |
| 6.2.1.3 | Additional rules for connections with internal steel plates | 38 |
| 6.2.2 | Reduced load method | 39 |
| 6.2.2.1 | Unprotected connections | 39 |
| 6.2.2.2 | Protected connections | 41 |
| 6.3 | Connections with external steel plates | 41 |
| 6.3.1 | Unprotected connections | 41 |
| 6.3.2 | Protected connections | 41 |
| 6.4 | Simplified rules for axially loaded screws | 41 |
| Section 7 | Detailing | 43 |
| 7.1 | Walls and floors | 43 |
| 7.1.1 | Dimensions and spacings | 43 |
| 7.1.2 | Detailing of panel connections | 43 |
| 7.1.3 | Insulation | 43 |
| 7.2 | Other elements | 43 |
| Annex A (informative) | Parametric fire exposure | 45 |
| A1 | General | 45 |
| A2 | Charring rates and charring depths | 45 |
| A3 | Mechanical resistance of members in edgewise bending | 47 |
| Annex B (informative) | Advanced calculation methods | 48 |
| B1 | General | 48 |
| B2 | Thermal properties | 48 |
| B3 | Mechanical properties | 50 |
| Annex C (informative) | Load-bearing floor joists and wall studs in assemblies whose cavities are completely filled with insulation | 52 |
| C1 | General | 52 |
| C2 | Residual cross-section | 52 |
| C2.1 | Charring rates | 52 |
| C2.2 | Start of charring | 54 |
| C2.3 | Failure times of panels | 54 |
| C3 | Reduction of strength and stiffness parameters | 56 |
| Annex D (informative) | Charring of members in wall and floor assemblies with void cavities | 58 |
| D1 | General | 58 |
| D2 | Charring rates | 58 |
| D3 | Start of charring | 58 |
| D4 | Failure times of panels | 58 |
| Annex E (informative) | Analysis of the separating function of wall and floor assemblies | 60 |
| E1 | General | 60 |
| E2 | Simplified method for the analysis of insulation | 60 |
| E2.1 | General | 60 |
| E2.2 | Basic insulation values | 61 |
| E2.3 | Position coefficients | 62 |
| E2.4 | Effect of joints | 62 |
| Annex F (informative) | Guidance for users of this Eurocode Part | 68 |