

DIN EN 1996-1-1:2010-12 (E)

Eurocode 6: Design of masonry structures - Part 1-1: General rules for reinforced and unreinforced masonry structures (includes Corrigendum AC:2009)

| Contents | | Page |
|---|--|-------------|
| Background to the Eurocode programme | | 7 |
| Status and field of application of Eurocodes | | 8 |
| National Standards implementing Eurocodes | | 9 |
| Links between Eurocodes and harmonised technical specifications (ENs and ETAs) for products | | 9 |
| 1 | General | 11 |
| 1.1 | Scope | 11 |
| 1.1.1 | Scope of Eurocode 6 | 11 |
| 1.1.2 | Scope of Part 1-1 of Eurocode 6 | 11 |
| 1.2 | Normative references | 13 |
| 1.2.1 | General | 13 |
| 1.2.2 | Reference standards | 13 |
| 1.3 | Assumptions | 14 |
| 1.4 | Distinction between principles and application rules | 14 |
| 1.5 | Terms and Definitions | 15 |
| 1.5.1 | General | 15 |
| 1.5.2 | Terms relating to masonry | 15 |
| 1.5.3 | Terms relating to strength of masonry | 15 |
| 1.5.4 | Terms relating to masonry units | 16 |
| 1.5.5 | Terms relating to mortar | 17 |
| 1.5.6 | Terms relating to concrete infill | 18 |
| 1.5.7 | Terms relating to reinforcement | 18 |
| 1.5.8 | Terms relating to ancillary components | 18 |
| 1.5.9 | Terms relating to mortar joints | 19 |
| 1.5.10 | Terms relating to wall types | 19 |
| 1.5.11 | Miscellaneous terms | 20 |
| 1.6 | Symbols | 21 |
| 2 | Basis of design | 27 |
| 2.1 | Basic requirements | 27 |
| 2.1.1 | General | 27 |
| 2.1.2 | Reliability | 27 |
| 2.1.3 | Design working life and durability | 27 |
| 2.2 | Principles of limit state design | 27 |
| 2.3 | Basic variables | 28 |
| 2.3.1 | Actions | 28 |
| 2.3.2 | Design values of actions | 28 |
| 2.3.3 | Material and product properties | 28 |
| 2.4 | Verification by the partial factor method | 28 |
| 2.4.1 | Design values of material properties | 28 |
| 2.4.2 | Combination of actions | 28 |
| 2.4.3 | Ultimate limit states | 28 |
| 2.4.4 | Serviceability limit states | 29 |
| 2.5 | Design assisted by testing | 29 |
| 3 | Materials | 30 |
| 3.1 | Masonry Units | 30 |
| 3.1.1 | Types and grouping of masonry units | 30 |

| | | |
|-------|---|----|
| 3.1.2 | Properties of masonry units -compressive strength | 32 |
| 3.2 | Mortar | 32 |
| 3.2.1 | Types of masonry mortar | 32 |
| 3.2.2 | Specification of masonry mortar | 32 |
| 3.2.3 | Properties of mortar | 33 |
| 3.3 | Concrete infill | 33 |
| 3.3.1 | General | 33 |
| 3.3.2 | Specification for concrete infill | 33 |
| 3.3.3 | Properties of concrete infill | 33 |
| 3.4 | Reinforcing steel | 34 |
| 3.4.1 | General | 34 |
| 3.4.2 | Properties of reinforcing steel bars | 34 |
| 3.4.3 | ~Properties of bed joint reinforcement TM | 34 |
| 3.5 | Prestressing steel | 35 |
| 3.6 | Mechanical properties of masonry | 35 |
| 3.6.1 | Characteristic compressive strength of masonry | 35 |
| 3.6.2 | Characteristic shear strength of masonry | 38 |
| 3.6.3 | Characteristic flexural strength of masonry | 40 |
| 3.6.4 | Characteristic anchorage strength of reinforcement | 42 |
| 3.7 | Deformation properties of masonry | 43 |
| 3.7.1 | Stress-strain relationship | 43 |
| 3.7.2 | Modulus of elasticity | 44 |
| 3.7.3 | Shear modulus | 44 |
| 3.7.4 | Creep, moisture expansion or shrinkage and thermal expansion | 45 |
| 3.8 | Ancillary components | 45 |
| 3.8.1 | Damp proof courses | 45 |
| 3.8.2 | Wall ties | 45 |
| 3.8.3 | Straps, hangers and brackets | 46 |
| 3.8.4 | Prefabricated lintels | 46 |
| 3.8.5 | Prestressing devices | 46 |
| 4 | Durability | 46 |
| 4.1 | General | 46 |
| 4.2 | Classification of environmental conditions | 46 |
| 4.3 | Durability of masonry | 46 |
| 4.3.1 | Masonry units | 46 |
| 4.3.2 | Mortar | 46 |
| 4.3.3 | Reinforcing steel | 46 |
| 4.3.4 | Prestressing steel | 48 |
| 4.3.5 | Prestressing devices | 49 |
| 4.3.6 | Ancillary components and support angles | 49 |
| 4.4 | Masonry below ground | 49 |
| 5 | Structural analysis | 49 |
| 5.1 | General | 49 |
| 5.2 | Structural behaviour in accidental situations (other than earthquakes and fire) | 50 |
| 5.3 | Imperfections | 50 |
| 5.4 | Second order effects | 51 |
| 5.5 | Analysis of structural members | 51 |
| 5.5.1 | Masonry walls subjected to vertical loading | 51 |
| 5.5.2 | Reinforced masonry members subjected to vertical loading | 57 |
| 5.5.3 | Masonry shear walls subjected to shear loading | 60 |
| 5.5.4 | Reinforced masonry members subjected to shear loading | 62 |
| 5.5.5 | Masonry walls subjected to lateral loading | 62 |
| 6 | Ultimate Limit State | 64 |
| 6.1 | Unreinforced masonry walls subjected to mainly vertical loading | 64 |
| 6.1.1 | General | 64 |
| 6.1.2 | Verification of unreinforced masonry walls subjected to mainly vertical loading | 64 |
| 6.1.3 | Walls subjected to concentrated loads | 67 |
| 6.2 | Unreinforced masonry walls subjected to shear loading | 70 |
| 6.3 | Unreinforced masonry walls subjected to lateral loading | 70 |

| | | |
|-------|---|-----|
| 6.3.1 | General | 70 |
| 6.3.2 | Walls arching between supports | 72 |
| 6.3.3 | Walls subjected to wind loading | 73 |
| 6.3.4 | Walls subjected to lateral loading from earth and water | 73 |
| 6.3.5 | Walls subjected to lateral loading from accidental situations | 73 |
| 6.4 | Unreinforced masonry walls subjected to combined vertical and lateral loading | 74 |
| 6.4.1 | General | 74 |
| 6.4.2 | Method using factor | 74 |
| 6.4.3 | Method using apparent flexural strength | 74 |
| 6.4.4 | Method using equivalent bending moment coefficients | 74 |
| 6.5 | Ties | 74 |
| 6.6 | Reinforced masonry members subjected to bending, bending and axial loading, or axial loading | 75 |
| 6.6.1 | General | 75 |
| 6.6.2 | Verification of reinforced masonry members subjected to bending and/or axial loading ... | 76 |
| 6.6.3 | Flanged Reinforced Members | 78 |
| 6.6.4 | Deep beams | 80 |
| 6.6.5 | Composite lintels | 82 |
| 6.7 | Reinforced masonry members subjected to shear loading | 82 |
| 6.7.1 | General | 82 |
| 6.7.2 | Verification of reinforced masonry walls subjected to horizontal loads in the plane of the wall | 83 |
| 6.7.3 | Verification of reinforced masonry beams subjected to shear loading | 84 |
| 6.7.4 | Verification of deep beams subjected to shear loading | 85 |
| 6.8 | Prestressed masonry | 85 |
| 6.8.1 | General | 85 |
| 6.8.2 | Verification of Members | 86 |
| 6.9 | Confined masonry | 87 |
| 6.9.1 | General | 87 |
| 6.9.2 | Verification of members | 87 |
| 7 | Serviceability Limit State | 87 |
| 7.1 | General | 87 |
| 7.2 | Unreinforced masonry walls | 88 |
| 7.3 | Reinforced masonry members | 88 |
| 7.4 | Prestressed masonry members | 88 |
| 7.5 | Confined masonry members | 89 |
| 7.6 | Walls subjected to concentrated loads | 89 |
| 8 | Detailing | 89 |
| 8.1 | Masonry details | 89 |
| 8.1.1 | Masonry materials | 89 |
| 8.1.2 | Minimum thickness of wall | 89 |
| 8.1.3 | Minimum area of wall | 90 |
| 8.1.4 | Bonding of masonry | 90 |
| 8.1.5 | Mortar joints | 91 |
| 8.1.6 | Bearings under concentrated loads | 91 |
| 8.2 | Reinforcement details | 91 |
| 8.2.1 | General | 91 |
| 8.2.2 | Cover to reinforcing steel | 92 |
| 8.2.3 | Minimum area of reinforcement | 92 |
| 8.2.4 | Size of reinforcing steel | 93 |
| 8.2.5 | Anchorage and laps | 93 |
| 8.2.6 | Restraint of compression reinforcing steel | 97 |
| 8.2.7 | Spacing of reinforcing steel | 97 |
| 8.3 | Prestressing details | 98 |
| 8.4 | Confined masonry details | 98 |
| 8.5 | Connection of walls | 98 |
| 8.5.1 | Connection of walls to floors and roofs | 98 |
| 8.5.2 | Connection between walls | 99 |
| 8.6 | Chases and recesses on walls | 100 |
| 8.6.1 | General | 100 |

| | | |
|--|--------------------------------------|-----|
| 8.6.2 | Vertical chases and recesses | 101 |
| 8.6.3 | Horizontal and inclined chases | 101 |
| 8.7 | Damp proof courses | 102 |
| 8.8 | Thermal and long term movement | 102 |
| 9 | Execution | 102 |
| 9.1 | General | 102 |
| 9.2 | Design of structural members | 103 |
| 9.3 | Loading of masonry | 103 |
| Annex A (informative) Consideration of partial factors relating to Execution | | 104 |
| Annex B (informative) Method for calculating the eccentricity of a stability core | | 105 |
| Annex C (informative) A simplified method for calculating the out-of-plane eccentricity of loading on walls | | 107 |
| Annex D (informative) Determination of 3 and 4 | | 111 |
| Annex E (informative) Bending moment coefficients, $\sim 2TM$, in single leaf laterally loaded wall panels of thickness less than or equal to 250 mm | | 112 |
| Annex F (informative) Limiting height and length to thickness ratios for walls under the serviceability limit state | | 117 |
| Annex G (informative) Reduction factor for slenderness and eccentricity | | 119 |
| Annex H (informative) Enhancement factor as given in 6.1.3 | | 121 |
| Annex I (informative) Adjustment of lateral load for walls supported on three or four edges subjected to out-of-plane horizontal loading and vertical loading | | 122 |
| Annex J (informative) Reinforced masonry members subjected to shear loading: enhancement of fvd | | 123 |