

# DIN EN 410:2011-04 (E)

## Glass in building - Determination of luminous and solar characteristics of glazing

---

<b>Contents</b>		<b>Page</b>
Foreword .....		3
Introduction .....		4
<b>1</b>	<b>Scope .....</b>	<b>5</b>
<b>2</b>	<b>Normative references .....</b>	<b>5</b>
<b>3</b>	<b>Terms and definitions .....</b>	<b>5</b>
<b>4</b>	<b>Symbols .....</b>	<b>6</b>
<b>5</b>	<b>Determination of characteristics .....</b>	<b>8</b>
<b>5.1</b>	<b>General .....</b>	<b>8</b>
<b>5.2</b>	<b>Light transmittance .....</b>	<b>8</b>
<b>5.3</b>	<b>Light reflectance .....</b>	<b>11</b>
<b>5.4</b>	<b>Total solar energy transmittance (solar factor) .....</b>	<b>12</b>
<b>5.4.1</b>	<b>Calculation .....</b>	<b>12</b>
<b>5.4.2</b>	<b>Division of incident solar radiant flux .....</b>	<b>12</b>
<b>5.4.3</b>	<b>Solar direct transmittance .....</b>	<b>14</b>
<b>5.4.4</b>	<b>Solar direct reflectance .....</b>	<b>14</b>
<b>5.4.5</b>	<b>Solar direct absorptance .....</b>	<b>14</b>
<b>5.4.6</b>	<b>Secondary heat transfer factor towards the inside .....</b>	<b>14</b>
<b>5.5</b>	<b>UV-transmittance .....</b>	<b>19</b>
<b>5.6</b>	<b>Colour rendering .....</b>	<b>19</b>
<b>5.7</b>	<b>Shading coefficient .....</b>	<b>22</b>
<b>6</b>	<b>Expression of results .....</b>	<b>23</b>
<b>7</b>	<b>Test report .....</b>	<b>23</b>
<b>Annex A (normative)</b>	<b>Procedures for calculation of the spectral characteristics of glass plates with a different thickness and/or colour .....</b>	<b>33</b>
<b>Annex B (normative)</b>	<b>Procedure for calculation of the spectral characteristics of laminated glass ....</b>	<b>38</b>
<b>Annex C (informative)</b>	<b>Procedure for calculation of the spectral characteristics of screen printed glass .....</b>	<b>59</b>
<b>Annex D (informative)</b>	<b>Example of calculation of colour rendering index .....</b>	<b>60</b>
<b>Bibliography .....</b>		<b>64</b>