

DIN EN 15882-1:2012-03 (E)

Extended application of results from fire resistance tests for service installations - Part 1: Ducts

Contents		Page
Foreword		3
Introduction		4
1	Scope	5
2	Normative references	5
3	Terms and definitions	5
4	Critical parameters and factors	6
4.1	General	6
4.2	Common thermal and mechanical parameters and factors	6
4.3	Common constructional parameters and factors	7
4.4	Specific constructional parameters and factors	7
5	Methodology	8
6	Requirements, performance criteria and influences	13
6.1	Requirements and performance criteria	13
6.2	Influences	13
6.2.1	Insulation	13
6.2.2	Integrity and leakage	13
7	Assessment scheme	14
7.1	General	14
7.2	Requirement for additional tests	14
8	Test arrangements and criteria for additional tests	14
8.1	Maximum dimensions of ducts which can be classified	14
8.2	Closed ducts with pressure differential	14
8.3	Open horizontal duct B	15
8.4	Open vertical duct B	15
9	Evaluation of fire resistance	15
9.1	Application of the basic and additional test results	15
9.2	Suspension devices	16
9.2.1	General	16
9.2.2	Dimensioning of suspension devices	16
9.2.3	Fixing of suspension devices	16
9.2.4	Longitudinal limit of suspension devices	17
9.3	Inspection openings/access panels	17
9.4	Components within ducts	17
9.5	Surface finishes	17
9.6	Change in wall or floor thickness	17
10	Extended application report	18
Bibliography		23