

DIN EN 14081-3:2012-04 (E)

Timber structures - Strength graded structural timber with rectangular cross section - Part 3: Machine grading; additional requirements for factory production control

| Contents | | Page |
|--|---|-------------|
| Foreword | | 3 |
| Introduction | | 4 |
| 1 | Scope | 5 |
| 2 | Normative references | 5 |
| 3 | Terms and definitions | 5 |
| 4 | Symbols | 5 |
| 5 | Requirements for the operation, calibration and maintenance of a grading machine | 6 |
| 6 | Additional requirements for factory production control for machine controlled systems | 6 |
| 6.1 | General | 6 |
| 6.2 | Requirements for strength grades with a characteristic strength level above C30 | 6 |
| 7 | Additional factory production control requirements for output controlled systems | 7 |
| Annex A (normative) Requirements for using control planks | | 8 |
| A.1 | General | 8 |
| A.2 | Requirements for selecting the control planks | 8 |
| A.3 | Requirements for the use of control planks for internal factory production control | 8 |
| A.4 | Requirements for the use of control planks for third party factory production control | 9 |
| Annex B (informative) Additional factory production control requirements for output controlled systems | | 10 |
| B.1 | General | 10 |
| B.2 | Production control | 10 |
| Annex C (informative) Example of cusum control charts | | 13 |
| Bibliography | | 17 |