

# DIN EN 1745:2012-07 (E)

## Masonry and masonry products - Methods for determining thermal properties

---

<b>Contents</b>		<b>Page</b>
Foreword .....		4
Introduction .....		5
<b>1</b>	<b>Scope .....</b>	<b>7</b>
<b>2</b>	<b>Normative references .....</b>	<b>7</b>
<b>3</b>	<b>Terms, definitions and symbols .....</b>	<b>7</b>
<b>3.1</b>	<b>Terms and definitions .....</b>	<b>7</b>
<b>3.2</b>	<b>Symbols .....</b>	<b>9</b>
<b>3.3</b>	<b>Subscripts .....</b>	<b>10</b>
<b>4</b>	<b>Procedures to determine <math>\lambda_{10,dry}</math>, unit-values for solid masonry units and <math>\lambda_{10,dry,mor}</math>- values for mortars .....</b>	<b>11</b>
<b>4.1</b>	<b>General .....</b>	<b>11</b>
<b>4.2</b>	<b><math>\lambda_{10,dry}</math>, mat-values for solid masonry units and mortars .....</b>	<b>11</b>
<b>4.2.1</b>	<b>Model S1. Determination of <math>\lambda_{10,dry}</math>,unit-values from tabulated <math>\lambda_{10,dry,mat}</math> /net dry density relation .....</b>	<b>11</b>
<b>4.2.2</b>	<b>Model S2. Determination of <math>\lambda_{10,dry}</math>,unit-values based on <math>\lambda_{10,dry,mat}</math> /net dry density curve .....</b>	<b>11</b>
<b>4.2.3</b>	<b>Model S3. Procedures to determine <math>\lambda_{10,dry}</math>,unit-values from determining the thermal transmittance (<math>U_{mas}</math>) of masonry built from solid masonry units and mortar .....</b>	<b>13</b>
<b>4.3</b>	<b>Test methods and numbers of samples to be taken for the different models .....</b>	<b>14</b>
<b>5</b>	<b>Procedures to determine equivalent <math>\lambda_{10,dry}</math>,unit-values for masonry units with formed voids and composite masonry units .....</b>	<b>14</b>
<b>5.1</b>	<b>General .....</b>	<b>14</b>
<b>5.2</b>	<b>Calculation methods .....</b>	<b>15</b>
<b>5.3</b>	<b><math>\lambda_{10,dry}</math>,unit-values of masonry units .....</b>	<b>15</b>
<b>5.3.1</b>	<b>Determination of <math>\lambda_{10,dry}</math>,unit-values from tabulated unit /mat relation .....</b>	<b>15</b>
<b>5.3.2</b>	<b>Determination of <math>\lambda_{10,dry}</math>,unit-values based on calculation .....</b>	<b>16</b>
<b>5.3.3</b>	<b>Model P5. Determination of <math>\lambda_{10,dry}</math>,unit-values from determining the thermal transmittance (<math>U_{mas}</math>) of masonry built from masonry units with formed voids or composite masonry units and mortar .....</b>	<b>16</b>
<b>5.4</b>	<b>Test methods and numbers of samples to be taken for the different models .....</b>	<b>19</b>
<b>6</b>	<b>Moisture conversion .....</b>	<b>19</b>
<b>7</b>	<b>Procedures to determine design thermal values (<math>R_{design,mas}</math> or design, mas) for masonry built from masonry units and mortar .....</b>	<b>20</b>
<b>7.1</b>	<b>General .....</b>	<b>20</b>
<b>7.2</b>	<b><math>R_{design,mas}</math>- or design,mas-values based on calculation .....</b>	<b>20</b>
<b>7.3</b>	<b><math>R_{design,mas}</math>- or design,mas-values of masonry built from masonry units with formed voids or composite masonry units and mortar based on tabulated values .....</b>	<b>21</b>
<b>7.3.1</b>	<b>Tabulated values .....</b>	<b>21</b>
<b>8.</b>	<b>Determination of the thermal transmittance of masonry .....</b>	<b>23</b>
<b>9.</b>	<b>Specific heat capacity .....</b>	<b>23</b>
<b>10.</b>	<b>Rounding rules for <math>\lambda</math>-values for masonry .....</b>	<b>23</b>

<b>Annex A (normative) Tabulated 10,dry,mat-values of materials used for masonry products .....</b>	<b>24</b>
<b>Annex B (informative) Rdry,mas- or 10,dry,mas-values of masonry built from a range of masonry units containing formed voids .....</b>	<b>35</b>
<b>Annex C (informative) Example of how to use the tables in Annex B .....</b>	<b>62</b>
<b>Annex D (normative) Requirements for appropriate calculation procedures .....</b>	<b>64</b>
<b>D.1 Capabilities of the program .....</b>	<b>64</b>
<b>D.2 Input data and results .....</b>	<b>64</b>
<b>D.3 Testing of the program accuracy .....</b>	<b>65</b>
<b>D.4 Reference cases .....</b>	<b>65</b>
<b>Annex E (informative) Evaluation of conformity .....</b>	<b>73</b>
<b>Annex F (informative) Alternative procedure for the moisture correction of units with formed voids</b>	<b>75</b>
<b>Bibliography .....</b>	<b>76</b>