

DIN EN 1996-1-1/NA:2012-05 (E)

National Annex - Nationally determined parameters - Eurocode 6: Design of masonry structures - Part 1-1: General rules for reinforced and unreinforced masonry structures

| Contents | Page |
|---|-------------|
| Foreword | 5 |
| NA 1 Scope | 6 |
| NA 2.1 General | 6 |
| NA 2.2 National provisions | 7 |
| Re 1 General | 7 |
| NCI re 1.2 Normative references | 7 |
| NCI re 1.5 Terms and definitions | 8 |
| NCI re 1.6 Symbols | 9 |
| Re 2 Basis of design | 10 |
| NCI re 2.4.2 Combination of actions | 10 |
| NDP re 2.4.3 (1)P Ultimate limit states | 10 |
| NDP re 2.4.4 (1) Serviceability limit states | 11 |
| Re 3 Materials | 11 |
| NCI re 3.1.1 Types and grouping of masonry units | 11 |
| NCI re 3.1.2 Properties of masonry units - Compressive strength | 12 |
| NCI re 3.2.1 Types of masonry mortar | 12 |
| NDP re 3.2.2 (1) Specification of masonry mortar | 12 |
| NCI re 3.2.2 Specification of masonry mortar | 12 |
| NCI re 3.2.3.1 Compressive strength of masonry mortar | 13 |
| NCI re 3.3.3 (1)P Properties of concrete infill | 13 |
| NCI re 3.4.1 General | 13 |
| NCI re 3.5 Prestressing steel | 13 |
| NDP re 3.6.1.2 (1) Characteristic compressive strength of masonry other than shell-bedded masonry | 13 |
| NCI re 3.6.1.2 Characteristic compressive strength of masonry other than shell-bedded masonry | 16 |

| | |
|---|----|
| NCI re 3.6.2 Characteristic shear strength of masonry | 17 |
| NDP re 3.6.2 (3) Characteristic shear strength of masonry | 17 |
| NDP re 3.6.2 (4) Characteristic shear strength of masonry | 18 |
| NDP re 3.6.2 (6) Characteristic shear strength of masonry | 18 |
| NCI re 3.6.3 Characteristic flexural strength of masonry | 18 |
| NDP re 3.6.3 (3) Characteristic flexural strength of masonry | 18 |
| NCI re 3.6.4 Characteristic anchorage strength of reinforcement | 19 |
| NDP re 3.7.2 (2) Modulus of elasticity | 19 |
| NDP re 3.7.4 (2) Creep, moisture expansion or shrinkage and thermal expansion | 19 |
| NCI re 3.8.1 Damp proof courses | 20 |
| NCI re 3.8.2 Wall ties | 20 |
| NCI re 3.8.3 Straps, hangers and brackets | 20 |
| NCI re 3.8.4 Prefabricated lintels | 20 |
| NCI re 3.8.5 Prestressing devices | 21 |
| Re 4 Durability | 21 |
| NDP re 4.3.3 (3) Reinforcing steel | 21 |
| NDP re 4.3.3 (4) Reinforcing steel | 21 |
| NCI re 4.3.4 Prestressing steel | 22 |
| NCI re 4.3.5 Prestressing devices | 22 |
| NCI re 4.3.6 Ancillary components and support angles | 22 |
| Re 5 Structural analysis | 22 |
| NCI re 5.5.1.1 General | 22 |
| NCI re 5.5.1.2 Effective height of masonry walls | 22 |
| NCI re 5.5.1.3 Effective thickness of masonry walls | 24 |
| NDP re 5.5.1.3 (3) Effective thickness of masonry walls | 24 |
| NCI re 5.5.3 Masonry shear walls subjected to shear loading | 25 |
| NCI re 5.5.5 Masonry walls subjected to lateral loading | 25 |
| Re 6 Ultimate limit state | 25 |
| NCI re 6.1.1 General | 25 |
| NCI re 6.1.2.1 General | 25 |
| NCI re 6.1.2.2 Reduction factor for slenderness and eccentricity | 25 |

| | |
|--|-----------|
| NDP re 6.1.2.2 (2) Reduction factor for slenderness and eccentricity | 27 |
| NCI re 6.1.3 Walls subjected to concentrated loads | 27 |
| NCI re 6.2 Unreinforced masonry walls subjected to shear loading | 28 |
| NCI re 6.3.4 Walls subjected to lateral loading from earth and water | 31 |
| NCI re 6.6.1 General | 32 |
| NCI re 6.6.2 Verification of reinforced masonry members subjected to bending and/or axial loading | 33 |
| NCI re 6.6.4 Deep beams | 33 |
| NCI re 6.6.5 Composite lintels | 33 |
| NCI re 6.8.1 General | 33 |
| NCI re 6.8.2 Verification of members | 33 |
| Re 7 Serviceability limit state | 33 |
| NCI re 7.2 Unreinforced masonry walls | 33 |
| Re 8 Detailing | 34 |
| NCI re 8.1.1 Masonry materials | 34 |
| NDP re 8.1.2 (2) Minimum thickness of wall | 34 |
| NCI re 8.1.2 Minimum thickness of wall | 34 |
| NCI re 8.1.4.1 Manufactured units | 35 |
| NCI re 8.1.5 Mortar joints | 35 |
| NCI re 8.4 Confined masonry details | 37 |
| NCI re 8.5.1.1 General | 37 |
| NCI re 8.5.1.4 Ring ties and ring beams | 37 |
| NCI re 8.5.2.2 Cavity and veneer walls | 37 |
| NDP re 8.5.2.2 (2) Cavity and veneer walls | 37 |
| NDP re 8.5.2.3 (2) Double-leaf walls | 39 |
| NCI re 8.5.2.3 Double-leaf walls | 39 |
| NCI re 8.6.2 Vertical chases and recesses | 39 |
| NDP re 8.6.2 (1) Vertical chases and recesses | 39 |
| NDP re 8.6.3 (1) Horizontal and inclined chases | 40 |
| NCI re 8.7 Damp proof courses | 40 |
| Re 9 Execution | 41 |
| NCI re 9.1 General | 41 |

| | |
|--|----|
| NCI re Annex A Consideration of partial factors relating to execution | 41 |
| NCI re Annex B Method of calculating the eccentricity of a stability core | 41 |
| NCI re Annex C A simplified method of calculating the out-of-plane eccentricity of loading on walls | 42 |
| NCI re Annex D Determination of 3 and 4 | 45 |
| NCI re Annex E Bending moment coefficients 2 in single leaf laterally loaded wall panels of thickness less than or equal to 250 mm | 45 |
| NCI re Annex F Limiting height and length to thickness ratios for walls under the serviceability limit state | 47 |
| NCI re Annex G Reduction factor for slenderness and eccentricity | 47 |
| NCI re Annex H Enhancement factor as given in 6.1.3 | 48 |
| NCI re Annex I Adjustment of lateral load for walls supported on three or four edges subjected to out-of-plane horizontal loading and vertical loading | 48 |
| NCI re Annex J Reinforced masonry members subjected to shear loading: enhancement of f_{vd} | 48 |
| NCI Annex NA.K (informative) Supplementary provisions for the analysis of shear walls | 49 |
| NA.K.1 General | 49 |
| NA.K.2 In-plane resistance to bending compression | 49 |
| NA.K.3 In-plane shear resistance | 50 |
| NCI Annex NA.L (normative) Design of natural stone masonry | 52 |
| NA.L.1 General | 52 |
| NA.L.2 General principles | 52 |
| NA.L.3 Execution of natural stone masonry | 52 |
| NA.L.4 Types of masonry | 53 |
| NA.L.4.1 Loadbearing masonry | 53 |
| NA.L.4.2 Gravity masonry walls | 53 |
| NA.L.4.3 Facing masonry | 53 |
| NA.L.4.4 Outer leaves of veneer walls | 53 |
| NA.L.4.5 Dry stone masonry | 54 |
| NA.L.5 Types of bond | 54 |
| NA.L.5.1 General | 54 |
| NA.L.5.2 Polygonal masonry bonds | 56 |
| NA.L.5.3 Orthogonal masonry bonds | 57 |
| NA.L.6 Design of natural stone masonry | 59 |

| | |
|--|-----------|
| NA.L.6.1 General | 59 |
| NA.L.6.2 Analysis for axial and eccentric compression | 60 |
| NA.L.6.3 Tension and bending | 60 |
| NA.L.6.4 Analysis for shear | 61 |
| NCI Annex NA.M (normative) Amendments to the rules for the use of clay masonry units NA.M.1 General | 62 |
| Re DIN V 20000-401:2005-06, clause 3 Terms and definitions | 62 |
| Re DIN V 20000-401:2005-06, 4.2 Declared values | 62 |
| Re DIN V 20000-401:2005-06, 4.3.1 Dimensions | 62 |
| Re DIN V 20000-401:2005-06, 4.3.2.1 Mean value | 62 |
| Re DIN V 20000-401:2005-06, 4.3.2.2 Range | 64 |
| Re DIN V 20000-401:2005-06, 4.4.2 Percentage of voids | 64 |
| Re DIN V 20000-401:2005-06, 4.4.3 Grip holes | 64 |
| Re DIN V 20000-401:2005-06, 4.4.4 Thickness of webs and shells | 65 |
| Re DIN V 20000-401:2005-06, 4.4.5 Shape and geometry of the perforations | 65 |
| Re DIN V 20000-401:2005-06, 4.5.1.1 Gross dry density - General | 66 |
| Re DIN V 20000-401:2005-06, 4.5.2 Net dry density | 66 |
| Re DIN V 20000-401:2005-06, 4.6 Compressive strength normal to the bed joint | 66 |
| Re DIN V 20000-401:2005-06, 5.3 Calculation of structural stability | 66 |
| Re DIN V 20000-401:2005-06, 5.5 Thermal insulation | 66 |
| Re DIN V 20000-401:2005-06, Annex A | 66 |