

DIN EN 16069:2013-03 (E)

Thermal insulation products for buildings - Factory made products of polyethylene foam (PEF) - Specification

| Contents | | Page |
|-----------------|--|-------------|
| Foreword | | 5 |
| 1 | Scope | 6 |
| 2 | Normative references | 6 |
| 3 | Terms, definitions, symbols, units and abbreviated terms | 7 |
| 3.1 | Terms and definitions | 7 |
| 3.2 | Symbols, units and abbreviated terms | 8 |
| 3.2.1 | Symbols and units used in this European Standard | 8 |
| 3.2.2 | Abbreviated terms used in this European Standard: | 10 |
| 4 | Requirements | 11 |
| 4.1 | General | 11 |
| 4.2 | For all applications | 11 |
| 4.2.1 | Thermal resistance and thermal conductivity | 11 |
| 4.2.2 | Length and width | 12 |
| 4.2.3 | Thickness | 12 |
| 4.2.4 | Squareness | 12 |
| 4.2.5 | Flatness | 13 |
| 4.2.6 | Reaction to fire of the product as placed on the market | 13 |
| 4.2.7 | Durability characteristics | 13 |
| 4.3 | For specific applications | 13 |
| 4.3.1 | General | 13 |
| 4.3.2 | Dimensional stability | 13 |
| 4.3.3 | Compressive stress or compressive strength | 14 |
| 4.3.4 | Tensile strength and elongation in length and width | 14 |
| 4.3.5 | Point load | 15 |
| 4.3.6 | Compressive creep | 15 |
| 4.3.7 | Water absorption | 15 |
| 4.3.8 | Water vapour transmission | 15 |
| 4.3.9 | Dynamic stiffness | 16 |
| 4.3.10 | Compressibility | 16 |
| 4.3.11 | Sound absorption | 17 |
| 4.3.12 | Width length and thickness of preformed products | 17 |
| 4.3.13 | Release of dangerous substances | 18 |
| 4.3.14 | Reaction to fire of the product in standardized assemblies simulating end-use applications | 18 |
| 4.3.15 | Continuous glowing combustion | 18 |
| 5 | Test methods | 19 |
| 5.1 | Sampling | 19 |
| 5.2 | Conditioning | 19 |
| 5.3 | Testing | 19 |
| 5.3.1 | General | 19 |
| 5.3.2 | Thermal resistance and thermal conductivity | 19 |
| 6 | Designation Code | 21 |
| 7 | Evaluation of conformity | 22 |
| 7.1 | General | 22 |

| | | |
|---|--|----|
| 7.2 | Initial type testing | 22 |
| 7.3 | Factory production control | 23 |
| 8 | Marking and labelling | 23 |
| Annex A (normative) Determination of the declared values of thermal resistance and thermal conductivity | | 24 |
| A.1 | General | 24 |
| A.2 | Input data | 24 |
| A.3 | Declared values | 24 |
| A.3.1 | General | 24 |
| A.3.2 | Case where thermal resistance and thermal conductivity are declared | 24 |
| Case where only thermal resistance is declared | | 25 |
| Annex B (normative) Initial type testing (ITT) and factory production control (FPC) | | 26 |
| Annex C (normative) PEF multilayered insulation products | | 30 |
| C.1 | General | 30 |
| C.2 | Requirements | 30 |
| C.2.1 | For all applications | 30 |
| C.2.2 | For specific applications | 31 |
| C.3 | Test methods | 31 |
| C.4 | Evaluation of conformity | 31 |
| Annex D (informative) Examples for the determination of the declared values of thermal resistance and thermal conductivity for a product or a product group | | 32 |
| D.1 | Case where both thermal resistance and thermal conductivity are declared | 32 |
| D.2 | Case where only thermal resistance is declared | 33 |
| Annex E (informative) Additional properties | | 35 |
| E.1 | General | 35 |
| E.2 | Deformation under specific compressive load and temperature conditions | 35 |
| E.3 | Compression modulus of elasticity | 35 |
| E.4 | Bending strength | 35 |
| E.5 | Apparent density | 35 |
| E.6 | Compressive stress at defined deformation | 36 |
| E.7 | Air flow resistivity | 36 |
| E.8 | Cyclic load behaviour | 36 |
| E.9 | Shear behaviour | 36 |
| E.10 | Peel strength | 36 |
| Annex ZA (informative) Clauses of this European Standard addressing the provisions of the EU Construction Products Directive | | 38 |
| ZA.1 Scope and relevant characteristics | | 38 |
| ZA.2 Procedures for attestation of conformity of factory made PolyEthylene Foam products | | 40 |
| ZA.2.1 Systems of attestation of conformity | | 40 |
| ZA.2.2 EC certificate and declaration of conformity | | 42 |
| ZA.3 CE Marking and labelling | | 44 |
| Bibliography | | 46 |
| Tables Table 1 -- Level and classes for dimensional tolerances | | 12 |

| | |
|---|-----------|
| Table 2 -- Dimensional stability under specified temperature and humidity conditions | 14 |
| Table 3 -- Classes for thickness tolerances | 16 |
| Table 4 -- Levels for compressibility | 17 |
| Table 5 -- Levels for dimensions of preformed products | 18 |
| Table 6 -- Test methods, test specimens and conditions | 20 |
| Table A.1 -- Values for k for one sided 90 % tolerance interval with a confidence level of 90 % | 25 |
| Table B.1 -- Minimum number of tests for ITT and minimum product testing frequencies | 26 |
| Table B.2 -- Minimum product testing frequencies for the reaction to fire characteristics | 29 |
| Table D.1 -- test results | 32 |
| Table D.2 -- R test results | 33 |
| Table E.1 -- Levels of bending strength | 35 |
| Table E.2 -- Levels for compressive stress at a defined deformation | 36 |
| Table E.3 -- Test methods, test specimens, conditions and minimum testing frequencies | 37 |
| Table ZA.1 -- Relevant clauses for PolyEthylene Foam and intended use | 39 |
| Table ZA.2 -- Systems of attestation of conformity | 40 |
| Table ZA.3.1 -- Assignment of evaluation of conformity tasks for products under system 1 for reaction to fire and system 3 for other characteristics | 41 |
| Table ZA.3.2 -- Assignment of evaluation of conformity tasks for products under system 3 or system 3 combined with system 4 for reaction to fire | 42 |
| Figures Figure ZA.1 -- Example CE marking information | 45 |