

DIN EN 408:2012-10 (E)

Timber structures - Structural timber and glued laminated timber - Determination of some physical and mechanical properties (includes Amendment A1:2012)

| Contents | | Page |
|--------------------|---|-------------|
| Foreword | | 4 |
| Introduction | | 5 |
| 1 | Scope | 6 |
| 2 | Normative references | 6 |
| 3 | Terms and definitions | 6 |
| 4 | Symbols and abbreviations | 6 |
| 5 | Determination of dimensions of test pieces | 8 |
| 6 | Determination of moisture content of test pieces | 8 |
| 7 | Determination of density of test pieces | 8 |
| 8 | Conditioning of test pieces | 8 |
| 9 | Determination of local modulus of elasticity in bending | 9 |
| 9.1 | Test piece | 9 |
| 9.2 | Procedure | 9 |
| 9.3 | Expression of results | 10 |
| 10 | Determination of global modulus of elasticity in bending | 11 |
| 10.1 | Test piece | 11 |
| 10.2 | Procedure | 11 |
| 10.3 | Expression of results | 12 |
| 11 | Determination of the shear modulus | 13 |
| 11.1 | Torsion method | 13 |
| 11.1.1 | Test piece | 13 |
| 11.1.2 | Procedure | 13 |
| 11.1.3 | Expression of results | 16 |
| 11.2 | Shear field test method | 17 |
| 11.2.1 | Test piece | 17 |
| 11.2.2 | Procedure | 17 |
| 11.2.3 | Expression of results | 19 |
| 12 | Determination of modulus of elasticity in tension parallel to the grain | 19 |
| 12.1 | Test piece | 19 |
| 12.2 | Procedure | 19 |
| 12.3 | Expression of results | 20 |
| 13 | Determination of tension strength parallel to the grain | 20 |
| 13.1 | Test piece | 20 |
| 13.2 | Procedure | 21 |
| 13.3 | Expression of results | 21 |
| 14 | Determination of modulus of elasticity in compression parallel to the grain | 21 |

| | | |
|---|---|----|
| 14.1 | Test piece | 21 |
| 14.2 | Procedure | 22 |
| 14.3 | Expression of results | 22 |
| 15 | Determination of compression strength parallel to grain | 22 |
| 15.1 | Test piece | 22 |
| 15.2 | Procedure | 22 |
| 15.3 | Expression of results | 23 |
| 16 | Determination of tension and compression strengths perpendicular to the grain | 23 |
| 16.1 | Requirements for test pieces | 23 |
| 16.1.1 | Fabrication | 23 |
| 16.1.2 | Surface preparation | 23 |
| 16.2 | Procedure | 24 |
| 16.3 | Expression of results | 27 |
| 16.3.1 | Compression perpendicular to the grain | 27 |
| 16.3.2 | Tension perpendicular to the grain | 27 |
| 17 | Determination of modulus of elasticity perpendicular to the grain | 27 |
| 17.1 | Requirements for test pieces | 27 |
| 17.2 | Procedure | 27 |
| 17.3 | Expression of results | 28 |
| 17.3.1 | Compression perpendicular to the grain | 28 |
| 17.3.2 | Tension perpendicular to the grain | 28 |
| 18 | Determination of shear strength parallel to the grain | 29 |
| 18.1 | Requirements for test pieces | 29 |
| 18.1.1 | Fabrication | 29 |
| 18.1.2 | Surface preparation | 29 |
| 18.2 | Procedure | 30 |
| 18.3 | Expression of results | 31 |
| 19 | Bending strength parallel to grain | 32 |
| 19.1 | Test piece | 32 |
| 19.2 | Procedure | 32 |
| 19.3 | Expression of results | 33 |
| 20 | Test report | 34 |
| 20.1 | General | 34 |
| 20.2 | Test piece | 34 |
| 20.3 | Test method | 34 |
| 20.4 | Test results | 34 |
| Annex A (informative) Example of compression perpendicular to grain test arrangement | | 35 |
| Annex B (informative) Example of tension perpendicular to grain test arrangement with rigid fixings | | 37 |
| Bibliography | | 38 |