

# DIN EN 572-6:2012-11 (E)

## Glass in building - Basic soda lime silicate glass products - Part 6: Wired patterned glass

---

<b>Contents</b>		<b>Page</b>
<b>Foreword</b> .....		<b>3</b>
<b>1</b> <b>Scope</b> .....		<b>4</b>
<b>2</b> <b>Normative references</b> .....		<b>4</b>
<b>3</b> <b>Terms and definitions</b> .....		<b>4</b>
<b>4</b> <b>Dimensional requirements</b> .....		<b>5</b>
<b>4.1</b> <b>Thickness</b> .....		<b>5</b>
<b>4.1.1</b> <b>General</b> .....		<b>5</b>
<b>4.1.2</b> <b>Tolerances</b> .....		<b>6</b>
<b>4.2</b> <b>Length, width and squareness</b> .....		<b>6</b>
<b>4.3</b> <b>Wire mesh</b> .....		<b>6</b>
<b>5</b> <b>Quality requirements</b> .....		<b>6</b>
<b>5.1</b> <b>General</b> .....		<b>6</b>
<b>5.2</b> <b>Methods of observation and measurement</b> .....		<b>7</b>
<b>5.2.1</b> <b>Spot and linear/extended faults</b> .....		<b>7</b>
<b>5.2.2</b> <b>Pattern faults</b> .....		<b>7</b>
<b>5.2.3</b> <b>Wire faults</b> .....		<b>7</b>
<b>5.3</b> <b>Acceptance levels</b> .....		<b>8</b>
<b>5.3.1</b> <b>Spot faults</b> .....		<b>8</b>
<b>5.3.2</b> <b>Linear/extended faults</b> .....		<b>8</b>
<b>5.3.3</b> <b>Pattern faults</b> .....		<b>9</b>
<b>5.3.4</b> <b>Wire faults</b> .....		<b>9</b>
<b>6</b> <b>Designation</b> .....		<b>9</b>
<b>Bibliography</b> .....		<b>10</b>