

# DIN EN 572-8:2012-11 (E)

## Glass in building - Basic soda lime silicate glass products - Part 8: Supplied and final cut sizes

---

| <b>Contents</b>     |  | <b>Page</b> |
|---------------------|--|-------------|
| Foreword .....      |  | 3           |
| 1                   | Scope .....  | 4           |
| 2                   | Normative references .....   | 4           |
| 3                   | Terms and definitions .....  | 4           |
| 4                   | Glass products .....   | 8           |
| 5                   | Dimensional requirements .....   | 8           |
| 5.1                 | Manufacturing dimensions .....   | 8           |
| 5.1.1               | Supplied sizes .....   | 8           |
| 5.1.2               | Final cut sizes .....  | 8           |
| 5.2                 | Thickness .....  | 9           |
| 5.2.1               | General .....  | 9           |
| 5.2.2               | Tolerances .....   | 9           |
| 5.3                 | Length, width, and squareness .....  | 10          |
| 6                   | Quality requirements .....   | 12          |
| 6.1                 | General .....  | 12          |
| 6.2                 | Methods of observation and measurement .....   | 13          |
| 6.2.1               | Optical faults .....   | 13          |
| 6.2.2               | Visual faults .....  | 13          |
| 6.2.3               | Edge defects for final cut sizes .....   | 14          |
| 6.3                 | Acceptance levels .....  | 15          |
| 6.3.1               | Optical faults .....   | 15          |
| 6.3.2               | Visual faults .....  | 15          |
| Annex A (normative) | Test methods of examination for visual faults - Spot faults and linear/extended faults .....                       | 22          |
| A.1                 | Float glass (EN 572-2:2012) .....  | 22          |
| A.1.1               | Method of observation .....  | 22          |
| A.1.2               | Linear/extended faults .....   | 22          |
| A.2                 | Polished wired glass (EN 572-3:2012) .....   | 22          |
| A.2.1               | Spot faults .....  | 22          |
| A.2.2               | Linear/extended faults .....   | 23          |
| A.3                 | Drawn sheet glass (EN 572-4:2012) .....  | 23          |
| A.3.1               | Spot faults .....  | 23          |
| A.3.2               | Linear/extended faults .....   | 23          |
| A.4                 | Patterned glass (EN 572-5:2012) and wired patterned glass (EN 572-6:2012) -- Spot and linear/extended faults ..... | 23          |
| Annex B (normative) | Method for measuring spot fault size (including halo) .....  | 24          |
| B.1                 | Conditions of observation .....  | 24          |
| B.2                 | Measurement of the size of the spot fault including the halo .....   | 25          |
| Bibliography .....  |  | 26          |