

DIN EN 572-8:2012-11 (E)

Glass in building - Basic soda lime silicate glass products - Part 8: Supplied and final cut sizes

Contents		Page
Foreword		3
1	Scope	4
2	Normative references	4
3	Terms and definitions	4
4	Glass products	8
5	Dimensional requirements	8
5.1	Manufacturing dimensions	8
5.1.1	Supplied sizes	8
5.1.2	Final cut sizes	8
5.2	Thickness	9
5.2.1	General	9
5.2.2	Tolerances	9
5.3	Length, width, and squareness	10
6	Quality requirements	12
6.1	General	12
6.2	Methods of observation and measurement	13
6.2.1	Optical faults	13
6.2.2	Visual faults	13
6.2.3	Edge defects for final cut sizes	14
6.3	Acceptance levels	15
6.3.1	Optical faults	15
6.3.2	Visual faults	15
Annex A (normative)	Test methods of examination for visual faults - Spot faults and linear/extended faults	22
A.1	Float glass (EN 572-2:2012)	22
A.1.1	Method of observation	22
A.1.2	Linear/extended faults	22
A.2	Polished wired glass (EN 572-3:2012)	22
A.2.1	Spot faults	22
A.2.2	Linear/extended faults	23
A.3	Drawn sheet glass (EN 572-4:2012)	23
A.3.1	Spot faults	23
A.3.2	Linear/extended faults	23
A.4	Patterned glass (EN 572-5:2012) and wired patterned glass (EN 572-6:2012) -- Spot and linear/extended faults	23
Annex B (normative)	Method for measuring spot fault size (including halo)	24
B.1	Conditions of observation	24
B.2	Measurement of the size of the spot fault including the halo	25
Bibliography		26