DIN EN 14320-2:2013-04 (E)

Thermal insulating products for building equipment and industrial installations - In-situ formed sprayed rigid polyurethane (PUR) and polyisocyanurate (PIR) foam products - Part 2: Specification for the installed insulation products

Contents

Page

Foreword 3

1 Scope 4

2 Normative references 4

3 Terms, definitions, abbreviations and symbols 4
3.1 Terms and definitions 4
3.2 Symbols and abbreviations 6

4 Requirements 6
4.1 General 6
4.2 Suitability of the building equipment or industrial installation for the installation of the product 6

5 In-situ measurements and calculations 6
5.1 Declared installed insulation thickness 6
5.2 Declared installed aged thermal resistance, RD 6
5.3 Declared installed insulation density 7
5.4 Foam quality checks carried out by the installer 7

6 Guidelines for installation 7

7 Installer's declaration 7

Annex A (normative) Method for the determination of the declared installed insulation thickness 8

Annex B (normative) Methods for the determination of the declared installed insulation density 9

B.1 Principle 9
B.2 Procedure 9
B.2.1 General 9
B.2.2 Destructive testing 9
B.2.3 Non-destructive testing 9
B.3 Test report 9

Annex C (normative) Immersion method for the determination of the declared installed insulation density 10

C.1 Scope 10
C.2 Principles 10
C.3 Necessary equipment 10
C.4 Products and reagents 10
C.5 Procedure 10
C.6 Results 11

Annex D (normative) Installation guidelines 12

D.1 General 12

D.2 Substrate preparation 12
D.3 Substrate conditions 12
D.4 Atmospheric conditions 12
D.5 Spraying machine preparation 12
D.5.1 General 12
D.5.2 Mixing ratio 12
D.6 Spraying procedure 13

Annex E (normative) Suitability of the building equipment or industrial installation to receive the insulation product 14

E.1 Building equipment or industrial installation 14
E.2 Site survey 14

Bibliography 15