

# DIN EN 15269-3:2012-10 (E)

**Extended application of test results for fire resistance and/or smoke control for door, shutter and openable window assemblies, including their elements of building hardware - Part 3: Fire resistance of hinged and pivoted timber doorsets and openable timber framed windows**

---

<b>Contents</b>		<b>Page</b>
	<b>Foreword</b> .....	<b>3</b>
<b>1</b>	<b>Scope</b> .....	<b>4</b>
<b>2</b>	<b>Normative references</b> .....	<b>4</b>
<b>3</b>	<b>Terms and definitions</b> .....	<b>5</b>
<b>4</b>	<b>Determination of the field of extended application</b> .....	<b>6</b>
<b>4.1</b>	<b>General</b> .....	<b>6</b>
<b>4.2</b>	<b>How to use the extended application rules in Annex A</b> .....	<b>6</b>
<b>4.3</b>	<b>Procedure for maximum field of extended application</b> .....	<b>6</b>
<b>4.4</b>	<b>Analysis of test results</b> .....	<b>7</b>
<b>5</b>	<b>Extended application report</b> .....	<b>7</b>
<b>6</b>	<b>Classification report</b> .....	<b>7</b>
	<b>Annex A (normative) Construction parameter variations</b> .....	<b>9</b>
	<b>Annex B (normative) Arrangements for doorsets incorporating side and/or overpanels</b> .....	<b>70</b>