

DIN EN 13126-9:2013-04 (E)

Building hardware - Requirements and test methods for windows and door height windows - Part 9: Hardware for horizontal and vertical pivot windows

Contents		Page
Foreword		4
1	Scope	6
2	Normative references	6
3	Terms and definitions	6
4	Classification	7
4.1	General	7
4.2	Category of use (1 - first digit)	7
4.3	Durability (2 - second digit)	7
4.4	Mass (3 - third digit)	7
4.5	Fire resistance (4 - fourth digit)	7
4.6	Safety in use (5 - fifth digit)	7
4.7	Corrosion resistance (6 - sixth digit)	7
4.8	Security (7 - seventh digit)	7
4.9	Application (8 - eighth digit)	8
4.10	Test sizes (9 - ninth digit)	8
4.10.1	Window size for horizontal pivot windows	8
4.10.2	Window size for vertical pivot windows	8
4.11	Example of classification for horizontal and vertical pivot windows	8
5	Requirements	9
5.1	General	9
5.2	Durability	9
5.3	Locking point variable tolerance	9
5.4	Handle operation tolerance	10
5.5	Balance test for pivot hinges with integrated braking function	10
5.6	Resistance to static load	10
5.7	Resistance to free fall test for horizontal pivot windows	10
5.8	Resistance to rebate hindrance test for vertical pivot windows	10
5.9	Minimum closing devices resistance	10
5.10	Corrosion test	10
6	Test equipment	11
7	Test methods	11
7.1	Samples	11
7.2	Test order	11
7.3	Durability test	12
7.3.1	Durability test of normal opening	12
7.3.2	Reversed position durability test	13
7.4	Balance tests	14
7.5	Static Tests	14
7.5.1	Ventilation position static test on horizontal pivot windows	14
7.5.2	Ventilation position static test on vertical pivot windows	15
7.5.3	Reversed position static test on horizontal pivot windows	16
7.5.4	Reversed position static test on vertical pivot windows	17
7.6	Free fall test for horizontal pivot windows	18
7.7	Rebate hindrance test for vertical pivot windows	18

7.8	Minimum closing device resistance test	19
7.9	Corrosion resistance	19
Annex A (informative) Test equipment		21
Annex B (normative) Flowchart of test procedures		22
Bibliography		24