

DIN EN ISO 13788:2013-05 (E)

Hygrothermal performance of building components and building elements - Internal surface temperature to avoid critical surface humidity and interstitial condensation - Calculation methods (ISO 13788:2012)

Contents	Page
Foreword	3
Introduction	4
1 Scope	5
2 Normative references	5
3 Terms and definitions, symbols and units	5
3.1 Terms and definitions	5
3.2 Symbols and units	7
3.3 Subscripts	8
4 Input data for the calculations	8
4.1 Material and product properties	8
4.2 External boundary conditions	8
4.3 Internal boundary conditions	10
4.4 Surface resistances	10
5 Calculation of surface temperature to avoid critical surface humidity	11
5.1 General	11
5.2 Determining parameters	11
5.3 Design for avoidance of mould growth, corrosion or other moisture damage	11
5.4 Design for the limitation of surface condensation on low thermal inertia elements	12
6 Calculation of interstitial condensation	13
6.1 General	13
6.2 Principle	13
6.3 Limitation of sources of error	14
6.4 Calculation	14
6.5 Criteria used to assess building components	20
7 Calculation of drying of building components	20
7.1 General	20
7.2 Principle	21
7.3 Specification of the method	21
7.4 Criteria used to assess drying potential of building components	21
Annex A (informative) Internal boundary conditions	22
Annex B (informative) Examples of calculation of the temperature factor at the internal surface to avoid critical surface humidity	24
Annex C (informative) Examples of calculation of interstitial condensation	28
Annex D (informative) Example of the calculation of the drying of a wetted layer	38
Annex E (informative) Relationships governing moisture transfer and water vapour pressure	41
Bibliography	44