DIN EN ISO 13788:2013-05 (E)

Hygrothermal performance of buildi ng components and building elements - Internal surface temperature to avoid critical surface humidity and interstitial condensation - Calculation methods (ISO 13788:2012)

Contents

Page

Foreword ... **3**

Introduction ... **4**

1 Scope ... **5**

2 Normative references ... **5**

3 Terms and definitions, symbols and units ... **5**
3.1 Terms and definitions ... 5
3.2 Symbols and units ... 7
3.3 Subscripts ... 8

4 Input data for the calculations ... **8**
4.1 Material and product properties ... 8
4.2 External boundary conditions ... 8
4.3 Internal boundary conditions ... 10
4.4 Surface resistances ... 10

5 Calculation of surface temperature to avoid critical surface humidity ... **11**
5.1 General ... 11
5.2 Determining parameters ... 11
5.3 Design for avoidance of mould growth, corrosion or other moisture damage ... 11
5.4 Design for the limitation of surface condensation on low thermal inertia elements ... 12

6 Calculation of interstitial condensation ... **13**
6.1 General ... 13
6.2 Principle ... 13
6.3 Limitation of sources of error ... 14
6.4 Calculation ... 14
6.5 Criteria used to assess building components ... 20

7 Calculation of drying of building components ... **20**
7.1 General ... 20
7.2 Principle ... 21
7.3 Specification of the method ... 21
7.4 Criteria used to assess drying potential of building components ... 21

Annex A (informative) **Internal boundary conditions** ... **22**

Annex B (informative) **Examples of calculation of the temperature factor at the internal surface to avoid critical surface humidity** ... **24**

Annex C (informative) **Examples of calculation of interstitial condensation** ... **28**

Annex D (informative) **Example of the calculation of the drying of a wetted layer** ... **38**

Annex E (informative) **Relationships governing moisture transfer and water vapour pressure** ... **41**

Bibliography ... **44**