

DIN EN ISO 13788:2013-05 (E)

Hygrothermal performance of building components and building elements - Internal surface temperature to avoid critical surface humidity and interstitial condensation - Calculation methods (ISO 13788:2012)

Contents		Page
Foreword		3
Introduction		4
1 Scope		5
2 Normative references		5
3 Terms and definitions, symbols and units		5
3.1 Terms and definitions		5
3.2 Symbols and units		7
3.3 Subscripts		8
4 Input data for the calculations		8
4.1 Material and product properties		8
4.2 External boundary conditions		8
4.3 Internal boundary conditions		10
4.4 Surface resistances		10
5 Calculation of surface temperature to avoid critical surface humidity		11
5.1 General		11
5.2 Determining parameters		11
5.3 Design for avoidance of mould growth, corrosion or other moisture damage		11
5.4 Design for the limitation of surface condensation on low thermal inertia elements		12
6 Calculation of interstitial condensation		13
6.1 General		13
6.2 Principle		13
6.3 Limitation of sources of error		14
6.4 Calculation		14
6.5 Criteria used to assess building components		20
7 Calculation of drying of building components		20
7.1 General		20
7.2 Principle		21
7.3 Specification of the method		21
7.4 Criteria used to assess drying potential of building components		21
Annex A (informative) Internal boundary conditions		22
Annex B (informative) Examples of calculation of the temperature factor at the internal surface to avoid critical surface humidity		24
Annex C (informative) Examples of calculation of interstitial condensation		28
Annex D (informative) Example of the calculation of the drying of a wetted layer		38
Annex E (informative) Relationships governing moisture transfer and water vapour pressure		41
Bibliography		44