

ISO 14824-2:2012-10 (E)

Grout for prestressing tendons - Part 2: Grouting procedures

| Contents | | Page |
|--------------------|---|-------------|
| Foreword | | iv |
| Introduction | | v |
| 1 | Scope | 1 |
| 2 | Normative references | 1 |
| 3 | Terms and definitions | 1 |
| 4 | Documentation | 1 |
| 4.1 | Execution specification | 1 |
| 4.2 | Quality plan | 2 |
| 4.3 | Execution documentation | 2 |
| 5 | Materials | 2 |
| 6 | Grout assessment | 3 |
| 6.1 | Suitability testing | 3 |
| 6.2 | Project specific grouting tests | 3 |
| 7 | Equipment | 4 |
| 7.1 | General | 4 |
| 7.2 | Mixer | 4 |
| 7.3 | Pump | 4 |
| 7.4 | Hoses | 4 |
| 7.5 | Inlet connections | 4 |
| 7.6 | Stand-by and emergency equipment | 4 |
| 8 | Grouting procedures | 5 |
| 8.1 | Inlets, outlets and tendon anchorages | 5 |
| 8.2 | Precautions before grouting | 5 |
| 8.3 | Temperature at grouting | 5 |
| 8.4 | Grouting operations | 6 |
| 8.5 | Precautions after grouting | 6 |
| 9 | Quality management | 6 |
| 9.1 | General | 6 |
| 9.2 | Personnel | 7 |
| 9.3 | Inspection | 7 |
| 9.4 | Conformity criteria | 10 |
| 9.5 | Action in the event of a non-conformity | 10 |
| Bibliography | | 12 |