

# DIN EN 1013:2013-03 (E)

## Light transmitting single skin profiled plastics sheets for internal and external roofs, walls and ceilings - Requirements and test methods

---

| <b>Contents</b>    |   | <b>Page</b> |
|--------------------|---|-------------|
| Foreword .....     |   | 4           |
| Introduction ..... |   | 5           |
| <b>1</b>           | <b>Scope .....</b>  | <b>6</b>    |
| <b>2</b>           | <b>Normative references .....</b>   | <b>6</b>    |
| <b>3</b>           | <b>Terms and definitions .....</b>  | <b>7</b>    |
| <b>4</b>           | <b>Symbols and abbreviations .....</b>  | <b>7</b>    |
| <b>4.1</b>         | <b>Symbols .....</b>  | <b>7</b>    |
| <b>4.2</b>         | <b>Abbreviations .....</b>  | <b>8</b>    |
| <b>5</b>           | <b>Requirements .....</b>   | <b>8</b>    |
| <b>5.1</b>         | <b>Visual appearance .....</b>  | <b>8</b>    |
| <b>5.2</b>         | <b>Dimensional tolerances and mass per square metre .....</b>                             | <b>8</b>    |
| <b>5.3</b>         | <b>Light transmission .....</b>   | <b>9</b>    |
| <b>5.4</b>         | <b>Flexural/tensile strength .....</b>  | <b>9</b>    |
| <b>5.5</b>         | <b>Durability .....</b>   | <b>10</b>   |
| <b>5.6</b>         | <b>Thermal ageing resistance (only for thermoplastic sheets) .....</b>                    | <b>12</b>   |
| <b>5.7</b>         | <b>Longitudinal reversion and profile retention (only for thermoplastic sheets) .....</b> | <b>12</b>   |
| <b>5.8</b>         | <b>Impact resistance .....</b>  | <b>12</b>   |
| <b>5.9</b>         | <b>Resistance to deflection (mechanical resistance) .....</b>                             | <b>13</b>   |
| <b>5.10</b>        | <b>Water vapour permeability .....</b>  | <b>13</b>   |
| <b>5.11</b>        | <b>Water/air permeability .....</b>   | <b>13</b>   |
| <b>5.12</b>        | <b>Linear thermal expansion .....</b>   | <b>14</b>   |
| <b>5.13</b>        | <b>Reaction to fire .....</b>   | <b>14</b>   |
| <b>5.14</b>        | <b>External fire performance .....</b>  | <b>14</b>   |
| <b>5.15</b>        | <b>Glass-fibre content (only for glass-fibre reinforced sheets) .....</b>                 | <b>15</b>   |
| <b>5.16</b>        | <b>Barcol hardness (only for glass-fibre reinforced sheets) .....</b>                     | <b>15</b>   |
| <b>5.17</b>        | <b>Presence of protective coating .....</b>   | <b>15</b>   |
| <b>5.18</b>        | <b>Adhesion of surface coating (only for glass-fibre reinforced sheets) .....</b>         | <b>16</b>   |
| <b>5.19</b>        | <b>Resistance to fixings .....</b>  | <b>16</b>   |
| <b>5.20</b>        | <b>Dangerous substances .....</b>   | <b>16</b>   |
| <b>6</b>           | <b>Test methods .....</b>   | <b>16</b>   |
| <b>6.1</b>         | <b>Dimensional tolerances .....</b>   | <b>16</b>   |
| <b>6.2</b>         | <b>Light transmission .....</b>   | <b>19</b>   |
| <b>6.3</b>         | <b>Yellowness index .....</b>   | <b>20</b>   |
| <b>6.4</b>         | <b>Flexural/tensile strength .....</b>  | <b>20</b>   |
| <b>6.5</b>         | <b>Thermal ageing resistance .....</b>  | <b>21</b>   |
| <b>6.6</b>         | <b>Longitudinal reversion and profile retention .....</b>                                 | <b>22</b>   |
| <b>6.7</b>         | <b>Small hard body impact resistance .....</b>  | <b>24</b>   |
| <b>6.8</b>         | <b>Resistance to deflection .....</b>   | <b>26</b>   |
| <b>6.9</b>         | <b>Reaction to fire .....</b>   | <b>29</b>   |
| <b>6.10</b>        | <b>External fire performance .....</b>  | <b>31</b>   |
| <b>6.11</b>        | <b>Glass-fibre content .....</b>  | <b>32</b>   |
| <b>6.12</b>        | <b>Barcol hardness .....</b>  | <b>32</b>   |
| <b>6.13</b>        | <b>Presence of protective coating .....</b>   | <b>32</b>   |
| <b>6.14</b>        | <b>Adhesion of surface coating .....</b>  | <b>35</b>   |

|   |  |           |
|---|--|-----------|
| <b>7</b>  | <b>Evaluation of conformity .....</b>                          | <b>36</b> |
| <b>7.1</b>  | <b>General .....</b>   | <b>36</b> |
| <b>7.2</b>  | <b>Initial type testing .....</b>                              | <b>36</b> |
| <b>7.3</b>  | <b>Factory production control (FPC) .....</b>                  | <b>38</b> |
| <b>8</b>  | <b>Marking and labelling .....</b>                             | <b>41</b> |
| <b>Annex A (normative) Profile terminology .....</b>  |  | <b>42</b> |
| <b>A.1</b>  | <b>Non-sinusoidal profiles .....</b>                           | <b>42</b> |
| <b>A.2</b>  | <b>Sinusoidal profile .....</b>                                | <b>43</b> |
| <b>A.3</b>  | <b>Minimum information to be declared .....</b>                | <b>43</b> |
| <b>Annex B (normative) Glass content by density of laminate .....</b>   |  | <b>44</b> |
| <b>B.1</b>  | <b>Determination of density of laminate constituents .....</b> | <b>44</b> |
| <b>B.2</b>  | <b>Test specimens .....</b>                                    | <b>44</b> |
| <b>B.3</b>  | <b>Procedure .....</b>   | <b>44</b> |
| <b>Annex ZA (informative) Clauses of this European Standard addressing the provisions of the EU<br/>Construction Products Directive .....</b> |  | <b>46</b> |
| <b>ZA.1 Scope and relevant characteristics .....</b>  |  | <b>46</b> |
| <b>ZA.2 Procedures for the attestation of conformity of light transmitting single skin profiled plastics<br/>sheets .....</b>                 |  | <b>48</b> |
| <b>ZA.3 CE marking and labelling .....</b>  |  | <b>53</b> |
| <b>Bibliography .....</b>   |  | <b>58</b> |