

DIN EN 14080:2013-09 (E)

Timber structures - Glued laminated timber and glued solid timber - Requirements

Contents		Page
Foreword		6
1	Scope	10
2	Normative references	10
3	Terms and definitions	11
4	Symbols	17
4.1	Main symbols	17
4.2	Subscripts	18
5	Requirements for glued laminated products	19
5.1	Mechanical resistance of glued laminated timber	19
5.1.1	General	19
5.1.2	Timber	19
5.1.3	Related material properties	19
5.1.4	Verification from classification of standardised beam lay-ups and lamination properties of glued laminated timber	20
5.1.5	Verification from cross sectional layup and properties of boards and finger joints	24
5.1.6	Verifications from full scale tests with glued laminated timber	26
5.1.7	Resawn glulam	26
5.2	Mechanical resistance of glued solid timber	28
5.2.1	General	28
5.2.2	Timber	28
5.2.3	Related material properties	28
5.2.4	Verification from classification of lamination properties of glued solid timber	28
5.2.5	Verifications from full scale tests with glued solid timber	29
5.3	Additional requirement for mechanical resistance of glulam with large finger joints	30
5.4	Additional requirement for mechanical resistance of block glued glulam	30
5.5	Bonding strength and durability of bonding strength of glued laminated products	30
5.5.1	General	30
5.5.2	Species	30
5.5.3	Adhesives for the production of glued laminated products	31
5.5.4	Finger joints in laminations	33
5.5.5	Bonding of laminations	33
5.5.6	Bonding of large finger joints	35
5.5.7	Bonding of block glued glulam	35
5.6	Durability of other characteristics against biological attack	35
5.6.1	Glued laminated products without preservative treatment	35
5.6.2	Glued laminated products with preservative treatment	35
5.7	Resistance to fire	35
5.8	Reaction to fire	36
5.9	Formaldehyde emission	37
5.10	Release/content of other dangerous substances	37
5.11	Deviation in sizes	37
5.11.1	Maximum deviations	37
5.11.2	Corrected sizes and moisture deformation factor	39
6	Evaluation of conformity	40
6.1	General	40
6.2	Initial Type Testing	40

6.2.1	General	40
6.2.2	Test samples, testing and compliance criteria	41
6.2.3	Test reports	46
6.3	Factory production control (FPC)	46
6.3.1	General	46
6.3.2	Requirements	47
6.3.3	Product specific requirements	52
6.4	Initial inspection of factory and of FPC	53
6.5	Continuous surveillance of FPC	54
6.6	Procedure for modifications	54
7	Marking and labelling	54
7.1	General	54
7.2	Glued laminated products	54
7.3	Additional for glulam with large finger joints	55
Annex A (normative) Release of Formaldehyde		56
A.1	General	56
A.2	Classification	56
A.2.1	Glued laminated timber or glued solid timber	56
A.2.2	Classification for glulam with large finger joints and block glued glulam	57
Annex B (normative) Additional test methods and requirements for adhesives		58
B.1	General	58
B.2	Long-term sustained load test at cyclic climate conditions with specimens loaded perpendicular to the glue line for moisture curing one-component polyurethane and emulsion polymer isocyanate adhesives	58
B.2.1	General description	58
B.2.2	Production of the specimens	58
B.2.3	Test procedure and climate conditions	59
B.2.4	Requirements	60
B.2.5	Report	60
B.3	Delamination test for finger joints in laminations	60
B.3.1	Production of the specimens	60
B.3.2	Testing	61
B.3.3	Results	61
B.3.4	Report	61
Annex C (normative) Delamination test of glue lines		63
C.1	Principle	63
C.2	Apparatus	63
C.2.1	Pressure vessel	63
C.2.2	Drying duct	63
C.2.3	Balance	63
C.2.4	Metal wedge and hammer	63
C.3	Sampling and preparation of test pieces	63
C.4	Procedures	64
C.4.1	General	64
C.4.2	Measurement and evaluation of delamination	64
C.4.3	Test cycle for method A	65
C.4.4	Test cycle for method B	65
C.4.5	Test cycle for method C	66
C.5	Results	66
C.5.1	General	66
C.5.2	Total delamination	66
C.5.3	Maximum delamination	66
C.6	Report	67
Annex D (normative) Shear test of glue lines		68

D.1	Principle	68
D.2	Apparatus	68
D.2.1	Testing machine	68
D.2.2	Shearing tool	68
D.3	Test pieces for glulam and glued solid timber	69
D.3.1	Preparation of test pieces	69
D.3.2	Sampling of test pieces (test bars)	70
D.3.3	Marking of test pieces (test bars)	71
D.4	Test pieces for glue lines between glulam components of block glued glulam	72
D.5	Procedure	72
D.6	Results	73
D.7	Report	73
Annex E (normative) Tests with laminations with or without finger joints (including compliance criteria)		74
E.1	Sampling of finger joints in laminations	74
E.1.1	General	74
E.1.2	For Initial type testing	74
E.1.3	For Factory production control	74
E.2	Testing of finger joints in laminations	74
E.2.1	General	74
E.2.2	Additionally for initial type testing	74
E.2.3	Additionally for factory production control	74
E.3	Compliance criteria of finger joints in laminations	75
E.3.1	For Initial type testing	75
E.3.2	For factory production control	75
E.4	Report of tests with finger joints in laminations	75
E.5	Tests with laminations without finger joints	76
Annex F (normative) Bending tests with glued laminated timber, glued solid timber and glulam with large finger joints (including compliance criteria)		77
F.1	Sampling	77
F.2	Testing	77
F.3	Evaluation	77
F.4	Compliance criteria	77
F.5	Report	78
Annex G (normative) Measurement of moisture content		79
G.1	General	79
G.2	Measurement of moisture content of boards during production	79
G.3	Mean moisture content of glued laminated timber and glulam components for the production of glulam with large finger joints and block glued glulam	79
G.4	Moisture content of glued solid timber	79
Annex H (normative) Equipment		80
H.1	General	80
H.2	Additionally for the production of glued laminated timber and glued solid timber	80
H.3	Additionally for the production of glulam with large finger joints	80
H.4	Additionally for the production of block glued glulam	80
Annex I (normative) Minimum production requirements		81
I.1	Personnel	81
I.2	Production and storage facilities	81
I.2.1	General	81
I.2.2	Facilities for drying and storage of timber	81
I.2.3	Facilities for processing and storage of adhesives	81

I.2.4	Facilities for production and curing	81
I.3	Equipment	81
I.4	Finger joints in laminations	82
I.4.1	Wane and edge damages	82
I.4.2	Finger joint geometry	82
I.4.3	Knots and local grain deviation	82
I.4.4	Moisture content at bonding	83
I.4.5	Bonding surface and application of the adhesive	83
I.4.6	Time between cutting and bonding	84
I.4.7	Pressure	84
I.4.8	Curing	84
I.5	Bonding of laminations	85
I.5.1	Permissible finished lamination sizes and radius of curvature	85
I.5.2	Laminations made of two boards side by side	85
I.5.3	Grooves in laminations	85
I.5.4	Orientation of laminations in the cross section	86
I.5.5	Moisture content at bonding	86
I.5.6	Planing of laminations	86
I.5.7	Bonding surface and adhesive application	87
I.5.8	Glue line thickness	87
I.5.9	Cramping	87
I.5.10	Curing	87
I.6	Glulam with large finger joints	88
I.6.1	Moisture content at bonding	88
I.6.2	Finger joint geometry	88
I.6.3	Machining of the fingers	88
I.6.4	Bonding surface and adhesive application	88
I.6.5	Cramping	88
I.6.6	Glue line thickness	89
I.6.7	Curing	89
I.7	Block glued glulam	89
I.7.1	Moisture content at bonding	89
I.7.2	Bonding surface and adhesive application	89
I.7.3	Cramping	89
I.7.4	Glue line thickness	89
I.7.5	Curing	89
Annex ZA (informative) Clauses of this European Standard addressing the provisions of the EU Construction Products Directive		90
ZA.1 Scope and relevant characteristics		90
ZA.2 Procedures for the attestation of conformity of glued laminated products		92
ZA.2.1 System of attestation of conformity		92
ZA.2.2 EC certificate of conformity		93
ZA.3 CE marking and labelling		94
ZA.3.1 General		94
ZA.3.2 CE marking on the product		94
ZA.3.3 CE marking in the accompanying documents		97
Bibliography		103