

# DIN EN 14308:2013-04 (E)

Thermal insulation products for building equipment and industrial installations -  
Factory made rigid polyurethane foam (PUR) and polyisocyanurate foam (PIR)  
products - Specification (includes Amendment A1:2013)

---

<b>Contents</b>	<b>Page</b>
Foreword .....	4
1 Scope .....	6
2 Normative references .....	6
3 Terms, definitions, symbols, units and abbreviated terms .....	7
4 Requirements .....	11
5 Test methods .....	17
6 Designation code .....	20
7 Evaluation of conformity .....	21
8 Marking and labelling .....	22
Annex A (normative) Factory production control .....	23
Annex B (normative) Determination of minimum service temperature .....	27
Annex C (normative) Determination of the aged value of thermal conductivity and thermal resistance .....	33
Annex D (informative) Additional properties .....	41
Annex ZA (informative) Clauses of this European Standard addressing the provisions of the EU Construction Products Directive .....	43
Bibliography .....	51
Figures Figure B.1 -- Dimensions of test specimens .....	32
Figure C.1 -- Flow chart of the alternative ageing procedures .....	34
Figure ZA.1 -- Example of CE marking information .....	50
Tables Table 1 -- Dimensional tolerances .....	12
Table 2 -- Levels for dimensional stability .....	13
Table 3 -- Levels for compressive stress or compressive strength .....	15
Table 4 -- Test methods, test specimens and conditions .....	18
Table A.1 -- Minimum product testing frequencies .....	23
Table A.2 -- Minimum product testing frequencies for the reaction to fire characteristics .....	25

<b>Table C.1 -- Increments for calculating the aged value of thermal conductivity .....</b>	<b>36</b>
<b>Table C.2 -- Increments for calculating the aged value of thermal conductivity <math>T_{mean} = - 120\text{ }^{\circ}\text{C}</math> .....</b>	<b>36</b>
<b>Table C.3 -- Increments for calculating the aged value of thermal conductivity <math>T_{mean} = + 10\text{ }^{\circ}\text{C}</math> .....</b>	<b>37</b>
<b>Table C.4 -- Increments for calculating the aged value of thermal conductivity <math>T_{mean} = + 120\text{ }^{\circ}\text{C}</math> ....</b>	<b>37</b>
<b>Table C.5 -- Safety increments to be added to the measured accelerated aged value of thermal conductivity .....</b>	<b>39</b>
<b>Table D.1 -- Test methods, test specimens, conditions and minimum testing frequencies .....</b>	<b>42</b>
<b>Table ZA.1 -- Relevant clauses .....</b>	<b>44</b>
<b>Table ZA.2 -- System(s) of attestation of conformity .....</b>	<b>45</b>
<b>Table ZA.3 -- Assignment of evaluation of conformity tasks for products under system 1 .....</b>	<b>46</b>
<b>Table ZA.4 -- Assignment of evaluation of conformity tasks for products under system 3 or system 3 combined with system 4 for reaction to fire .....</b>	<b>47</b>