

# DIN EN 14305:2013-04 (E nglisch)

Thermal insulation products for building equipment and industrial installations -  
Factory made cellular glass (CG) products - Specification (includes Amendment  
A1:2013)

---

<b>Contents</b>	<b>Page</b>
Foreword .....	4
1 Scope .....	6
2 Normative references .....	6
3 Terms, definitions, symbols, units and abbreviated terms .....	8
4 Requirements .....	11
5 Test methods .....	18
6 Designation code .....	22
7 Evaluation of conformity .....	23
8 Marking and labelling .....	23
Annex A (normative) Factory production control .....	25
Annex B (informative) Determination of minimum service temperature .....	29
Annex C (informative) Additional properties .....	33
Annex D (informative) Preparation of the flat test specimens to measure thermal conductivity .....	35
Annex ZA (informative) Clauses of this European Standard addressing the provisions of the EU Construction Products Directive .....	36
Bibliography .....	44
Figure Figure ZA.1 -- Example of CE marking information .....	43
Tables Table 1 -- Dimensional tolerances .....	12
Table 2 -- Dimensional stability under specified conditions .....	13
Table 3 -- Levels for compressive strength .....	15
Table 4 -- Levels for bending strength .....	16
Table 5 -- Levels for deformation under point load .....	16
Table 6 -- Test methods, test specimens and conditions .....	20
Table A.1 -- Minimum product testing frequencies .....	25
Table A.2 -- Minimum product testing frequencies for the reaction to fire of the product as placed on the market .....	27

<b>Table C.1 -- Test methods, test specimens, conditions and minimum testing frequencies .....</b>	<b>34</b>
<b>Table ZA. 1 -- Relevant clauses .....</b>	<b>37</b>
<b>Table ZA.2 -- System(s) of attestation of conformity .....</b>	<b>38</b>
<b>Table ZA.3 -- Assignment of evaluation of conformity tasks for products under system 1 .....</b>	<b>39</b>
<b>Table ZA.4 -- Assignment of evaluation of conformity tasks for products as placed on the market under system 3 or system 3 combined with system 4 for reaction to fire .....</b>	<b>40</b>