DIN EN 16361:2013-12 (E)

Power operated pedestrian doors - Product standard, performance characteristics - Pedestrian doorsets, other than swing type, initially designed for installation with power operation without resistance to fire and smoke leakage characteristics

Contents

Page

Foreword 4

1 Scope 5

2 Normative references 6

3 Terms and definitions 7

4 Requirements 7
4.1 General 7
4.2 Rate of release of dangerous substances (only for indoor impact) 7
4.3 Impact resistance (only for glazed doors with injury risks) 8
4.4 Height 8
4.5 Direct airborne sound insulation index (only for uses where acoustic performance is declared) 8
4.6 Impact forces (safety in use) 8
4.7 Water tightness (only for external doors) 8
4.8 Resistance to wind load (only for external doors) 9
4.9 Thermal transmittance (only for external doors and for internal doors where the thermal insulation is declared) 10
4.10 Air permeability (only for external doors and for internal doors where thermal insulation is declared) 10
4.11 Durability 11
4.11.1 General 11
4.11.2 Durability 12
4.12 Electromagnetic compatibility (EMC) 12
4.13 Other requirements 13
4.13.1 Glazing 13
4.13.2 Unframed glass doorsets 13
4.13.3 Doorsets in escape routes and emergency exits 13
4.13.4 Burglar resistance 13

5 Testing, assessment and sampling methods 13
5.1 General 13
5.2 Rate of release of dangerous substances (only for indoor impact) 13
5.3 Impact resistance (only for glazed doors with injury risks) 13
5.4 Height 13
5.5 Direct airborne sound insulation index (only for uses where acoustic performance is declared) 13
5.6 Impact forces (safety in use) 13
5.7 Water tightness (only for external doors) 14
5.8 Resistance to wind load (only for external doors) 14
5.9 Thermal transmittance (only for external doors and for internal doors where thermal insulation is declared) 14
5.10 Air permeability (only for external doors and for internal doors where thermal insulation is declared) 14
5.11 Durability 14
5.12 Electromagnetic compatibility (EMC) 14
5.12.1 Verification 14

5.12.2 Test for electromagnetic emissions 14
5.12.3 Tests for immunity to disturbances 15

6 Evaluation of conformity 15
6.1 General 15
6.2 Initial Type Testing - Type Testing 15
6.2.1 General 15
6.2.2 Test samples, testing and compliance criteria 16
6.2.3 Test reports 17
6.3 Factory production control (FPC) 17
6.3.1 General 17
6.3.2 Requirements 17
6.3.3 Product specific requirements 20
6.3.4 Initial inspection of factory and of FPC 21
6.3.5 Continuous surveillance of FPC for products covered by attestation of conformity system 1 22
6.3.6 Procedure for modifications 22
6.3.7 One-off products, pre-production products (e.g. prototypes) and products produced in very low quantity 22

Annex A (normative) Standards and draft standards on glass 24

Annex B (informative) Summary of the characteristics 25

B.1 Summary of the characteristics of power operated pedestrian doorsets, other than swing type, initially designed for installation with power operation without resistance to fire and smoke leakage characteristics 25

Annex C (informative) Handling, installation, maintenance and care 27

Annex D (informative) Summary of classification of characteristics 28

Annex ZA (informative) Clauses of this European Standard addressing the provisions of the EU Construction Products Directive 32

ZA.1 Scope and relevant characteristics 32

ZA.2 Procedure for the attestation of conformity of power operated doorsets, other than swing type, initially designed for installation with power operation without resistance to fire and smoke leakage characteristics 36

ZA.2.1 System(s) of attestation of conformity 36

ZA.2.2 EC Certificate and Declaration of conformity 38

ZA.3 CE marking and labelling 39

Annex ZB (informative) Relationship between this European Standard and the Essential Requirements of the EMC Directive 43

Bibliography 44