

DIN EN 1364-3:2014-05 (E)

Fire resistance tests for non-loadbearing elements - Part 3: Curtain walling - Full configuration (complete assembly)

Contents		Page
Foreword		5
Introduction		6
1	Scope	7
2	Normative references	7
3	Terms and definitions	8
4	Test equipment	9
5	Test conditions	9
6	Test specimen	9
6.1	Size	9
6.1.1	General	9
6.1.2	Internal fire exposure	9
6.1.3	External fire exposure	10
6.2	Number of specimens	10
6.3	Design	10
6.3.1	General	10
6.3.2	Standard configuration	10
6.3.3	Restraint	11
6.3.4	Surfaces	11
6.3.5	Perimeter seal	11
6.4	Construction	11
6.5	Verification	11
7	Installation of the test specimen	12
7.1	General	12
7.2	Supporting floors	12
7.2.1	Standard supporting floor	12
7.2.2	Non-standard supporting floor	12
7.3	Simulated wall construction	12
7.3.1	Standard construction	12
7.3.2	Non-standard construction	12
7.4	Furnace closure	12
8	Conditioning	13
9	Application of instrumentation	13
9.1	Thermocouples	13
9.1.1	Furnace thermocouples (plate thermometers)	13
9.1.2	Unexposed face thermocouples	13
9.2	Pressure	16
9.3	Deflection	17
9.4	Radiation	17
10	Test procedure	17

11	Performance criteria	17
12	Test report	18
13	Field of direct application of test results	18
13.1	General rules	18
13.1.1	General	18
13.1.2	Exposure conditions	19
13.1.3	Overrun time	19
13.2	Rules for the complete construction	19
13.2.1	Width of the curtain walling	19
13.2.2	Height of the curtain walling	19
13.2.3	Span length	20
13.2.4	Installation angle (vertical/sloped)	20
13.2.5	Facet angles of horizontally faceted curtain walling	20
13.3	Framing system	21
13.3.1	Distance between mullions and transoms	21
13.3.2	Geometry/dimension of mullions and transoms	21
13.3.3	Connection between mullions and transoms	22
13.3.4	Framing material	22
13.3.5	Decorative frame surface treatments/coverings/coatings	23
13.3.6	Fixing of the framing system (anchoring)	23
13.3.7	Pressure plate system	25
13.3.8	Other fixing systems than pressure plate	26
13.4	Infill panels	26
13.4.1	Opaque (non-translucent/non-transparent) infill panels	26
13.4.2	Sandwich panels	27
13.4.3	Translucent or transparent infill panels	28
13.4.4	Glazing materials	30
13.5	Perimeter seals / Vertical linear joint seals	30
13.5.1	General	30
13.5.2	Orientation	30
13.5.3	Material	30
13.5.4	Width/depth	31
13.5.5	Fixing of the perimeter seal	31
13.5.6	Covering	31
13.6	Supporting floor	31
13.7	Walls abutting the curtain walling	32
Annex A (normative) Field of direct application of test results for unitised construction		55
A.1	General	55
A.2	Rules for the complete construction	55
A.2.1	Width of the curtain walling	55
A.2.2	Height of the curtain wall	55
A.2.3	Span length	55
A.3	Infill panels	55
A.3.1	Opaque (non-translucent/non-transparent) infill panels	55
A.3.2	Sandwich panels	55
A.3.3	Translucent or transparent infill panels	55
Annex B (informative) Explanatory notes		56
B.1	Notes to Clause 1 "Scope"	56
B.1.1	Test principles and requirements	56
B.1.2	Fire from the outside of the building (e.g. E, EW and EI (o i))	56
B.2	Notes to Clause 3 "Terms and definitions"	56
B.3	Notes to Clause 5 "Test conditions"	57
B.4	Notes to Clause 6 "Test specimen"	57
B.5	Notes to 7.2.1 "Standard supporting floor"	57
B.6	Notes to Clause 9 "Application of instrumentation"	57
B.6.1	Thermocouples	57

B.6.2	Deflection measurement	57
B.7	Notes to Clause 13 "Field of direct application of test results"	58
B.7.1	Overrun time	58
B.7.2	Width of the curtain walling	58
B.7.3	Installation angle (vertical/sloped)	58
B.7.4	Horizontally faceted curtain walling	58
B.7.5	Height of the curtain walling / span length	58
B.7.6	Framing system	58
B.7.7	Infill panels / spandrel panels	59
B.7.8	Perimeter seal	59
Bibliography		63