

# DIN EN 12697-49:2014-05 (E)

## Bituminous mixtures - Test methods for hot mix asphalt - Part 49: Determination of friction after polishing

---

<b>Contents</b>		<b>Page</b>
Foreword .....		3
<b>1</b>	<b>Scope .....</b>	<b>6</b>
<b>2</b>	<b>Normative references .....</b>	<b>6</b>
<b>3</b>	<b>Terms, definitions and symbols .....</b>	<b>6</b>
<b>3.1</b>	<b>Terms and definitions .....</b>	<b>6</b>
<b>3.2</b>	<b>Symbols .....</b>	<b>6</b>
<b>4</b>	<b>Principle .....</b>	<b>7</b>
<b>5</b>	<b>Equipment .....</b>	<b>7</b>
<b>5.1</b>	<b>Test device .....</b>	<b>7</b>
<b>5.1.1</b>	<b>General .....</b>	<b>7</b>
<b>5.1.2</b>	<b>Polishing unit .....</b>	<b>7</b>
<b>5.1.3</b>	<b>Specimen clamping system .....</b>	<b>10</b>
<b>5.1.4</b>	<b>Friction measuring unit .....</b>	<b>10</b>
<b>5.2</b>	<b>Glass-control plate .....</b>	<b>12</b>
<b>5.3</b>	<b>Sand-blasting-equipment .....</b>	<b>12</b>
<b>6</b>	<b>Other materials .....</b>	<b>12</b>
<b>6.1</b>	<b>Quartz powder .....</b>	<b>12</b>
<b>6.2</b>	<b>Water quartz powder mixture .....</b>	<b>13</b>
<b>6.3</b>	<b>Corundum .....</b>	<b>13</b>
<b>7</b>	<b>Test method .....</b>	<b>13</b>
<b>7.1</b>	<b>Preparation of the specimens .....</b>	<b>13</b>
<b>7.1.1</b>	<b>Specimens prepared in the laboratory .....</b>	<b>13</b>
<b>7.1.2</b>	<b>Specimens taken from the site .....</b>	<b>13</b>
<b>7.2</b>	<b>Polishing procedure .....</b>	<b>14</b>
<b>7.3</b>	<b>Friction measurement .....</b>	<b>14</b>
<b>7.3.1</b>	<b>Pre-test check of the measurement device .....</b>	<b>14</b>
<b>7.3.2</b>	<b>Friction test .....</b>	<b>15</b>
<b>8</b>	<b>Calculation and expression of the results .....</b>	<b>15</b>
<b>8.1</b>	<b>Friction force and friction coefficient .....</b>	<b>15</b>
<b>8.2</b>	<b>Determination of FAP .....</b>	<b>15</b>
<b>9</b>	<b>Test report .....</b>	<b>16</b>
<b>10</b>	<b>Precision .....</b>	<b>16</b>
<b>Annex A (informative) Example of polishing head and friction unit .....</b>		<b>17</b>
<b>Bibliography .....</b>		<b>18</b>