

# DIN EN 12602:2013-10 (E)

## Prefabricated reinforced components of autoclaved aerated concrete (includes Amendment A1:2013)

---

<b>Contents</b>		<b>Page</b>
Foreword .....		10
<b>1</b>	<b>Scope .....</b>	<b>12</b>
<b>2</b>	<b>Normative references .....</b>	<b>12</b>
<b>3</b>	<b>Terms, definitions, symbols and abbreviations .....</b>	<b>14</b>
3.1	Terms and definitions .....	14
3.2	Symbols .....	15
3.2.1	General symbols .....	15
3.2.2	Subscripts .....	16
3.2.3	Symbols used in this European Standard (including normative annexes, except Annex C) .....	16
3.3	Abbreviations .....	22
<b>4</b>	<b>Properties and requirements of materials .....</b>	<b>22</b>
4.1	Constituent materials of autoclaved aerated concrete .....	22
4.1.1	General .....	22
4.1.2	Release of dangerous substances .....	23
4.2	Autoclaved aerated concrete parameters .....	23
4.2.1	General .....	23
4.2.2	Dry density .....	23
4.2.3	Characteristic strength values .....	25
4.2.4	Compressive strength .....	25
4.2.5	Tensile strength and flexural strength .....	25
4.2.6	Stress-strain diagram .....	26
4.2.7	Modulus of elasticity .....	26
4.2.8	Poisson's ratio .....	26
4.2.9	Coefficient of thermal expansion .....	27
4.2.10	Drying shrinkage .....	27
4.2.11	Creep .....	27
4.2.12	Specific heat .....	28
4.2.13	Thermal conductivity .....	28
4.2.14	Water vapour permeability .....	30
4.2.15	Water tightness .....	30
4.3	Reinforcement .....	30
4.3.1	Steel .....	30
4.3.2	Structural reinforcement .....	31
4.3.3	Effective diameter of coated bars .....	32
4.3.4	Non-structural reinforcement .....	33
4.4	Bond .....	33
4.5	Thermal prestress .....	34
4.5.1	General .....	34
4.5.2	Declared mean initial prestrain $0m,g$ .....	34
<b>5</b>	<b>Properties and requirements of components .....</b>	<b>35</b>
5.1	General .....	35
5.1.1	Mechanical resistance .....	35
5.1.2	Acoustic properties .....	35
5.1.3	Reaction to fire and resistance to fire .....	35
5.1.4	Design thermal resistance and design thermal conductivity .....	36

5.2	Technical requirements and declared properties .....	36
5.2.1	Dimensions and tolerances .....	36
5.2.2	Mass of the components .....	37
5.2.3	Dimensional stability .....	37
5.2.4	Load-bearing capacity .....	38
5.2.5	Deflections .....	38
5.2.6	Joint strength .....	38
5.2.7	Minimum requirements .....	39
5.3	Durability .....	41
5.3.1	General .....	41
5.3.2	Environmental conditions .....	41
5.3.3	Corrosion protection of reinforcement .....	42
5.3.4	Freeze and thaw resistance .....	43
6	Evaluation of conformity .....	43
6.1	Introduction .....	43
6.2	Initial type-testing of the component .....	43
6.3	Factory production control .....	44
6.3.1	General .....	44
6.3.2	Process control .....	44
6.3.3	Finished products .....	45
6.4	Initial inspection of the factory and the factory production control .....	45
6.4.1	Information to be supplied .....	45
6.4.2	Inspection .....	45
6.4.3	Reports .....	46
6.5	Surveillance, assessment and acceptance of the factory production control .....	46
6.5.1	Inspection tasks .....	46
6.5.2	Frequency of inspections .....	46
6.5.3	Reports .....	46
6.6	Actions to be taken in the event of non-conformity .....	46
7	Basis for design .....	54
7.1	Design methods .....	54
7.2	Limit states .....	54
7.3	Actions .....	55
8	Marking, labelling and designation .....	55
8.1	Standard designation .....	55
8.2	Production detail information .....	56
8.3	Additional information on accompanying documents .....	56
Annex A (normative) Design by calculation .....		57
A.1	General .....	57
A.2	Ultimate limit states (ULS) General design assumptions .....	57
A.3	Ultimate limit states (ULS): design for bending and combined bending and axial compression .....	59
A.3.1	Design assumptions .....	59
A.3.2	Stress-strain diagram for AAC .....	59
A.3.3	Stress-strain diagram for reinforcing steel .....	60
A.3.4	Minimum reinforcement .....	62
A.4	Shear .....	63
A.4.1	Shear design for components predominantly under transverse load .....	63
A.5	Ultimate limit states induced by structural deformation (buckling) .....	68
A.5.1	General .....	68
A.5.2	Method based on Euler formula .....	69
A.5.3	Modified model column method .....	70
A.6	Punching .....	76
A.6.1	General .....	76
A.6.2	Scope and definitions .....	76
A.6.3	Design method for punching shear .....	78
A.7	Primary torsion/combined primary torsion and shear .....	79

A.8	Concentrated forces .....	81
A.9	Serviceability limit states (SLS) .....	82
A.9.1	General .....	82
A.9.2	Limitation of stresses under serviceability conditions .....	82
A.9.3	Serviceability limit states of cracking .....	83
A.9.4	Serviceability limit states of deformation .....	83
A.10	Detailing of reinforcement .....	86
A.10.1	General .....	86
A.10.2	Bond .....	87
A.10.3	Anchorage .....	87
A.11	Support length .....	91
<b>Annex B (normative) Design by testing .....</b>		<b>93</b>
B.1	General .....	93
B.2	Safety evaluation .....	94
B.2.1	General .....	94
B.2.2	Brittle and ductile failure .....	94
B.3	Ultimate limit state .....	94
B.3.1	General .....	94
B.3.2	Transversely loaded components .....	95
B.3.3	Longitudinally loaded components .....	97
B.3.4	Simultaneously transversely and longitudinally loaded wall components .....	100
B.3.5	Anchorage .....	101
B.4	Serviceability limit states .....	103
B.4.1	Crack width control .....	103
B.4.2	Deformations .....	103
<b>Annex C (normative) Resistance to fire design of AAC components and structures .....</b>		<b>104</b>
C.1	General .....	104
C.1.1	Scope .....	104
C.1.2	Distinction between principles and application rules .....	104
C.1.3	Terms and definitions .....	104
C.1.4	Symbols .....	106
C.1.5	Units .....	107
C.2	Basic principles .....	108
C.2.1	Performance requirements .....	108
C.2.2	Design values of material properties .....	108
C.2.3	Assessment methods .....	108
C.3	Material properties .....	109
C.3.1	General .....	109
C.3.2	AAC .....	110
C.3.3	Steel .....	112
C.4	Structural fire design methods .....	113
C.4.1	General .....	113
C.4.2	Tabulated data .....	113
C.4.3	Simplified design methods .....	118
C.4.4	Anchorage .....	122
C.5	Protective layers .....	122
<b>Annex CA (normative) Modulus of elasticity and maximum strain of AAC and reinforcing steel at elevated temperature .....</b>		<b>123</b>
<b>Annex CB (informative) Joints between AAC components satisfying resistance to fire E .....</b>		<b>126</b>
CB.1	Floor and roof components with dry joints .....	126
CB.2	Floor and roof components with mortar joints .....	126
CB.3	Vertical and horizontal wall components with dry joints .....	127

CB.4 Vertical and horizontal wall components with mortar joints .....	127
Annex CC (normative) Temperature profiles of AAC wall, floor and roof components and AAC beams .....	129
CC.1 Basis of temperature profiles .....	129
CC.2 Temperature profiles for AAC wall, floor and roof components .....	129
CC.3 Temperature profiles for AAC beams .....	132
CC.4 Calculation assumptions .....	141
Annex CD (normative) Resistance to fire tabulated data for walls with mechanical impact .....	142
Annex D (informative) Recommended values for partial safety factors .....	144
D.1 General .....	144
D.2 Ultimate Limit States (ULS) .....	144
D.3 Serviceability Limit States (SLS) .....	146
Annex E (informative) Recommendations for the consideration of prestress in the design of prefabricated reinforced AAC components .....	147
E.1 Calculation of prestrain from test results .....	147
E.1.1 General .....	147
E.1.2 Symbols .....	148
E.1.3 Cross-section values of AAC components .....	149
E.1.4 Calculation of prestrain $\sigma$ from steel measurement .....	149
E.2 Cross-sectional analysis of a AAC component in SLS if prestress is taken into account .....	149
E.3 Splitting forces due to prestress .....	150
E.4 Methods to prevent end cracks due to prestress .....	151
Annex F (informative) Statistical methods for quality control .....	152
F.1 Quality control .....	152
Annex G (normative) "Factory production control of stainless reinforcing steel based on at least three samples - Minimum acceptance criteria for individual values and corresponding mean values" .....	154
Annex ZA (informative) Provisions for the CE marking of prefabricated reinforced components of autoclaved aerated concrete under the EC Construction Product Directive .....	155
ZA.1 Clauses of this European Standard addressing the provisions of EC Construction Products Directive .....	155
ZA.2 Procedures for the attestation of conformity of products .....	163
ZA.2.1 Systems of attestation of conformity .....	163
ZA.2.2 EC Certificate and Declaration of conformity .....	165
ZA.3 CE marking and labelling .....	166
ZA.3.1 General .....	166
ZA.3.2 Declaration of geometrical data and material properties .....	167
ZA.3.3 Declaration of product properties .....	170
ZA.3.4 Declaration of compliance with given design specification .....	172

ZA.3.5 !Declaration of compliance with the manufacturers' designed specification" .....	173
ZA.3.6 Simplified CE-marking label with reference to a manufacturer's catalogue .....	176
ZA.3.7 !Example on Technical information in the CE-marking" .....	177
Bibliography .....	179
Figures Figure 1 -- Determination of dry thermal conductivity 10dry .....	29
Figure A.1 -- Determination of effective span $l_{eff}$ .....	58
Figure A.2 -- Bi-linear stress-strain diagram for AAC in compression for cross-sectional design .....	60
Figure A.3 -- Design stress-strain diagram for reinforcing steel .....	61
Figure A.4 -- Strain diagrams in the ultimate limit state .....	62
Figure A.5 -- Notation for components subjected to shear .....	65
Figure A.6 --Structural model and possible load cases for the modified model column method .....	71
Figure A.7 -- Relation between curvature and strain Two curvatures (great curvature and small curvature) are presented .....	74
Figure A.8 -- Application of punching provisions in non-standard cases .....	77
Figure A.9 -- Critical perimeter around loaded areas located away from an unsupported edge .....	77
Figure A.10 -- Critical perimeter near an opening .....	78
Figure A.11 -- Critical sections near unsupported edges .....	78
Figure A.12 -- Idealised box section .....	81
Figure A.13 -- Definition of the areas to be introduced in Equation (A.39) .....	82
Figure A.14 -- Moment curvature relationship .....	86
Figure A.15 -- Effective length of transverse anchorage bars .....	89
Figure A.16 -- Envelope line for determining the tensile force in the longitudinal reinforcement .....	90
Figure A.17 -- Support length $a_o$ .....	92
Figure B.1 -- Definition of shear span $l_s$ .....	95
Figure B.2 -- Typical reinforcement layouts in AAC-components .....	96
Figure B.3 -- Diagram for determination of the column factor $k$ .....	99
Figure B.4 -- N/M - interaction diagram of the cross-section representing the results of three test series 100 Figure B.5 -- Envelope line for determining the section of the actual bending moment, $M_{da}$ .....	103
Figure C.1 Coefficient $k_c()$ allowing for decrease of compressive strength, $f_{ck}$ , of AAC at elevated temperature .....	110
!Figure C.2" .....	111

!Figure C.3" - Coefficient $k_s()$ allowing for decrease of characteristic strength $f_{yk}$ of tension and compression reinforcement .....	112
!Figure C.4" -- Sections of AAC components showing nominal axis distance $a$ and nominal concrete cover $c$ of reinforcement .....	114
!Figure C.5" -- Reduction of strength and cross-section for sections exposed to fire .....	120
!Figure C.6" -- Division of a wall, with both sides exposed to fire, into zones for use in calculation of strength reduction and $a_z$ values .....	120
Figure CA.1 -- Stress-strain relationship of AAC under compression at elevated temperature .....	123
Figure CA.2 -- Stress-strain relationship of reinforcing steel at elevated temperature .....	125
Figure CB.1 -- Example of a dry joint in structures made of floor or roof components with cover (e.g. topping) preventing movement of air through the joint .....	126
Figure CB.2 -- Examples of mortar joints in structures made of floor or roof components .....	126
Figure CB.3 -- Example of dry joints with two sealing strips in structures made of horizontal wall components .....	127
Figure CB.4 -- Examples of thin layer mortar joints in structures made of vertical or horizontal wall components .....	128
Figure CC.1 -- Temperature profiles for AAC wall, floor and roof components with a dry density of 300 kg/m <sup>3</sup> .....	129
Figure CC.2 -- Temperature profiles for AAC wall, floor and roof components with a dry density of 400 kg/m <sup>3</sup> .....	130
Figure CC.3 -- Temperature profiles for AAC wall, floor and roof components with a dry density of 500 kg/m <sup>3</sup> .....	131
Figure CC.4 -- Temperature profiles for AAC wall, floor and roof components with a dry density of 600 kg/m <sup>3</sup> .....	132
Figure CC.5 -- Temperature profiles of the non exposed face of component for the determination of the criteria of the classification to fire, for a dry density of 300 and 600 kg/m <sup>3</sup> .....	133
Figure CC.6 -- Temperature profiles in °C for AAC-beams ( $b \times h = 150 \text{ mm} \times 200 \text{ mm}$ ) with a dry density of 300 kg/m <sup>3</sup> , exposed on three sides to standard fire .....	133
Figure CC.7 -- Temperature profiles in °C for AAC-beams ( $b \times h = 150 \text{ mm} \times 200 \text{ mm}$ ) with a dry density of 400 kg/m <sup>3</sup> , exposed on three sides to standard fire .....	134
Figure CC.8 -- Temperature profiles in °C for AAC-beams ( $b \times h = 150 \text{ mm} \times 200 \text{ mm}$ ) with a dry density of 500 kg/m <sup>3</sup> , exposed on three sides to standard fire .....	135
Figure CC.9 -- Temperature profiles in °C for AAC-beams ( $b \times h = 150 \text{ mm} \times 200 \text{ mm}$ ) with a dry density of 600 kg/m <sup>3</sup> , exposed on three sides to standard fire .....	136
Figure CC.10 -- Temperature profiles in °C for AAC-beams ( $b \times h = 300 \text{ mm} \times 400 \text{ mm}$ ) with a dry density of 300 kg/m <sup>3</sup> , exposed on three sides to standard fire .....	137
Figure CC.11 -- Temperature profiles in °C for AAC-beams ( $b \times h = 300 \text{ mm} \times 400 \text{ mm}$ ) with a dry density of 400 kg/m <sup>3</sup> , exposed on three sides to standard fire .....	138
Figure CC.12 -- Temperature profiles in °C for AAC-beams ( $b \times h = 300 \text{ mm} \times 400 \text{ mm}$ ) with a dry density of 500 kg/m <sup>3</sup> , exposed on three sides to standard fire .....	139

Figure CC.13 -- Temperature profiles in °C for AAC-beams (b x h = 300 mm x 400 mm) with a dry density of 600 kg/m <sup>3</sup> , exposed on three sides to standard fire .....	140
Figure E.1 -- Analysis of prestress by means of an assumed external force .....	148
Figure ZA.1 Example of CE marking with Method 1 .....	170
Figure ZA.2 Example of CE marking with Method 2 .....	171
Figure ZA.3a Example of CE marking with Method 3a .....	173
Figure ZA.3b Example of CE marking with Method 3b .....	175
Figure ZA.4 -- Example of simplified label .....	177
Tables Table 1 -- Density classes .....	24
Table 2a" -- Compressive strength classes for AAC .....	25
Table 2b Drying shrinkage classes for AAC" .....	27
Table 3 -- Creep classes .....	28
Table 4 -- Dry thermal conductivity $\lambda_{dry}$ of AAC for 50 % and 90 % of production with a confidence level of = 90 % (compiled according to EN 1745) .....	30
Table 5a List of steel grades for stainless reinforcing steel .....	31
Table 5b Mandrel diameter for the bending test .....	32
Table 5c" -- Welding strength classes and welding strength factors $k_W$ .....	32
Table 6 Bond classes" .....	33
Table 7 -- Prestress classes .....	34
Table 8 -- Dimensional tolerances of components .....	37
Table 9 -- Final shrinkage strains $\epsilon_0$ for AAC components .....	37
Table 10 -- Thickness classes of structural components .....	39
Table 11 -- Exposure classes and protective measures related to environmental conditions .....	42
Table 12 -- Initial type-testing of the AAC components .....	47
Table 13 -- Testing of the finished product; AAC components for structural uses .....	50
Table 14 -- Testing of the finished product; AAC components for non-structural uses .....	53
Table A.1 -- Bond Classes .....	89
Table B.1 -- Design loadbearing capacity $R_{cd}$ of components .....	102
Table C.1 -- Thermal conductivity of AAC ( $\lambda$ ) at elevated temperature .....	111
Table C.2 -- Minimum wall thickness of non loadbearing AAC walls with a dry density between 350 kg/m <sup>3</sup> and 700 kg/m <sup>3</sup> .....	114
Table C.3a -- Minimum wall thickness and axis distance $a_{min}$ for separating loadbearing AAC walls. AAC dry density 350 kg/m <sup>3</sup> to 700 kg/m <sup>3</sup> and structural or non-structural reinforcement for resistance to fire REI .....	115

Table C.3b -- Minimum wall thickness and minimum axis distance $a_{min}$ for non separating loadbearing AAC walls supported on at least two opposite ends of the components. AAC dry density 350 kg/m <sup>3</sup> to 700 kg/m <sup>3</sup> and structural or non-structural reinforcement for resistance to fire R .....	115
Table C.4 -- Minimum dimensions (height $h_{min}$ and width $b_{min}$ ) in mm and minimum axis distance $a_{min}$ in mm to the bottom side and to the vertical sides of AAC beams in relation to the maximum span length 116 Table C.5 -- Minimum thickness $h_{min}$ in mm and minimum axis distance $a_{min}$ in mm of AAC floor and roof components in relation to maximum span length .....	117
Table C.6 -- Reduction of the dimensions of AAC cross-section from fire exposed surfaces .....	122
Table CA.1 --Values for the parameters of stress-strain relationship of AAC in compression at elevated temperature .....	123
Table CA.2 -- Values for the parameters of stress-strain relationship of reinforcing steel at elevated temperature .....	124
Table CC.1 .....	141
Table CC.2 .....	141
Table CD.1 -- Minimum wall thickness and minimum axis distance $a_{min}$ of AAC walls with mechanical impact supported on at least two opposite ends; AAC dry density 450 kg/m <sup>3</sup> to 700 kg/m <sup>3</sup> with structural or non structural reinforcement for resistance to fire REI-M and EI-M .....	142
Table CD.2 -- Minimum amount of reinforcement for AAC components used in walls with mechanical impact .....	143
Table D.1 -- Safety parameter for failure type .....	144
Table D.2 -- Safety parameter for accuracy when determining the material parameter .....	144
Table D.3 -- Safety parameters depending on variation .....	145
Table D.4 -- Partial safety factors .....	145
Table F.1 -- Control factor $k_n$ as a function of samples $n$ with a fractile value of 5 % ( $p = 0,95$ ) and a confidence level of 0,75 (using bayesian procedures with "vague" prior distribution) and under the assumption that the safety level (Annex D) is based on a summarised variation of $VR = 0,10$ .....	153
Table F.2-- Coefficient $k_s$ as a function of samples $n$ with a fractile value of 5 % ( $p = 0,95$ ) and a confidence level 0,75 (using bayesian procedures with "vague" prior distribution) .....	153
Table ZA.1a -- Harmonised clauses for loadbearing wall components .....	156
Table ZA.1b -- Harmonised clauses for retaining wall components .....	157
Table ZA.1c -- Harmonised clauses for roof components .....	158
Table ZA.1d -- Harmonised clauses for floor components .....	159
Table ZA.1e -- Harmonised clauses for linear components .....	160
Table ZA.1f -- Harmonised clauses for non-loadbearing wall and noise barriers components .....	161
Table ZA.1g -- Harmonised clauses for cladding components .....	162

<b>Table ZA.1h -- Harmonised clauses for small box culvert components .....</b>	<b>163</b>
<b>Table ZA.2a -- Systems of attestation of conformity .....</b>	<b>164</b>
<b>Table ZA.2b -- Assignment of evaluation of conformity tasks (for structural components) under system 2+1) .....</b>	<b>164</b>
<b>Table ZA.2c -- Assignment of evaluation of conformity tasks (for non structural or light structural components) under system 4 1) .....</b>	<b>165</b>