

# DIN EN 15683-1:2014-01 (E)

## Glass in building - Thermally toughened soda lime silicate channel shaped safety glass - Part 1: Definition and description

---

<b>Contents</b>		<b>Page</b>
Foreword .....		3
Introduction .....		4
1	Scope .....	5
2	Normative references .....	5
3	Terms and definitions .....	5
4	Glass products .....	6
5	Fracture characteristics .....	6
6	Dimensions and tolerances .....	6
6.1	General .....	6
6.2	Dimensions and dimensional tolerances .....	6
6.2.1	Nominal thickness (c) and thickness tolerances .....	6
6.2.2	Width, flange height and length (sizes) .....	6
6.3	Shape .....	7
6.3.1	Flange deviation .....	7
6.3.2	Squareness of cut, q .....	8
6.3.3	Tolerances on shape .....	8
6.4	Flatness .....	8
6.4.1	General .....	8
6.4.2	Measurement of overall bow .....	9
6.4.3	Limitation on overall bow .....	10
7	Edge working of channel shaped glass before toughening .....	10
8	Fragmentation test .....	11
8.1	General .....	11
8.2	Dimensions and number of test specimens .....	11
8.3	Test procedure .....	11
8.4	Assessment of fragmentation .....	12
8.5	Minimum values from the particle count .....	12
8.6	Selection of the longest particle .....	13
8.7	Maximum length of longest particle .....	13
9	Other physical characteristics .....	13
9.1	Optical distortion .....	13
9.2	Anisotropy (iridescence) .....	13
9.3	Thermal durability .....	13
9.4	Profile bending strength .....	13
9.5	Allowable stress .....	14
9.6	Allowable deflection .....	14
10	Marking .....	14
Annex A (informative)	Example of particle count .....	15
Bibliography .....		18