DIN EN 15497:2014-07 (E)

Structural finger jointed solid timber - Performance requirements and minimum production requirements

Contents

Page

Foreword 4

Introduction 5

1 Scope 6

2 Normative references 6

3 Terms and definitions 7

4 Symbols 9
4.1 Main symbols 9
4.2 Subscripts 9

5 Performance characteristics for structural finger jointed timber 10
5.1 Mechanical resistance 10
5.1.1 General 10
5.1.2 Timber 10
5.1.3 Bending strength of finger joints 10
5.1.4 Related material properties 10
5.2 Bonding strength and durability of bonding strength 10
5.2.1 General 10
5.2.2 Species 11
5.2.3 Adhesives for the production of structural finger jointed timber 11
5.3 Durability against biological attack 13
5.3.1 Structural finger jointed timber without preservative treatment 13
5.3.2 Structural finger jointed timber with preservative treatment 13
5.4 Resistance to fire 13
5.5 Reaction to fire 13
5.6 Formaldehyde emission 15
5.7 Release/content of other dangerous substances 15
5.8 Deviation in sizes 15

6 Assessment and Verification of Constancy of Performance (AVCP) 16
6.1 General 16
6.2 Type testing 16
6.2.1 General 16
6.2.2 Test samples, testing and compliance criteria 17
6.2.3 Test reports 19
6.2.4 Shared other party results 19
6.2.5 Cascading determination of the product type results 20
6.3 Factory production control (FPC) 21
6.3.1 General 21
6.3.2 Provisions 21
6.3.3 Product specific provisions 26
6.3.4 Initial inspection of factory and of FPC 26
6.3.5 Continuous surveillance of FPC 27
6.3.6 Procedure for modifications 27

7 Marking and labelling 27

Annex A (normative) Release of Formaldehyde 29

A.1 General 29
A.2 Classification 29
A.2.1 Provisions 29
A.2.2 Test procedure 29
A.2.3 Test report 30

Annex B (normative) Additional test methods and provisions for adhesives 31

B.1 General 31
B.2 Long-term sustained load test at cyclic climate conditions with specimens loaded perpendicular to the glue line for moisture curing one-component polyurethane and emulsion polymer isocyanate adhesives 31
B.2.1 General description 31
B.2.2 Production of the specimens 31
B.2.3 Test procedure and climate conditions 32
B.2.4 Provisions 33
B.2.5 Report 33

Annex C (normative) Bending tests with finger joints (including compliance criteria) 34

C.1 Sampling 34
C.1.1 General 34
C.1.2 For type testing 34
C.1.3 For factory production control 34
C.2 Testing 34
C.2.1 General 34
C.2.2 Additional provisions for type testing 34
C.2.3 Additional provisions for factory production control 34
C.3 Compliance criteria 35
C.3.1 For type testing 35
C.3.2 For factory production control 35
C.4 Report 35

Annex D (normative) Measurement of moisture content 37

D.1 General 37
D.2 Measurement of moisture content of timber during production 37
D.3 Mean moisture content of structural finger jointed timber 37

Annex E (normative) Equipment 38

Annex F (normative) Separation tests with finger joints produced with contact-free application of adhesive 39

Annex G (normative) Minimum production provisions 40

G.1 Personnel 40
G.2 Production and storage facilities 40
G.2.1 General 40
G.2.2 Facilities for drying and storage of timber 40
G.2.3 Facilities for processing and storage of adhesives 40
G.2.4 Facilities for production and curing 40
G.3 Equipment 40
G.4 Finger joints 41
G.4.1 Wane and edge damages 41
G.4.2 Finger joint geometry 42
G.4.3 Knots, local grain deviations and fissures 42
G.4.4 Moisture content at bonding 43
G.4.5 Bonding surface and application of the adhesive 43
G.4.6 Time between cutting and adhesive application 44

G.4.7 Pressure 44
G.4.8 Curing 45

Annex ZA (informative) Clauses of this European Standard addressing the provisions of EU Construction Products Regulation 46

Bibliography 57