

# DIN EN 1995-1-1/A2:2014-07 (E)

## Eurocode 5: Design of timber structures - Part 1-1: General - Common rules and rules for buildings

---

<b>Contents</b>		<b>Page</b>
	<b>Foreword</b> .....	<b>3</b>
<b>1</b>	<b>Modifications to 1.2, Normative references</b> .....	<b>4</b>
<b>2</b>	<b>Modification to 1.6, Symbols used in EN 1995-1-1</b> .....	<b>4</b>
<b>3</b>	<b>Modifications to 2.2.3, Serviceability limit states</b> .....	<b>4</b>
<b>4</b>	<b>Modification to 2.3.2.2, Load-duration and moisture influences on deformations</b> .....	<b>4</b>
<b>5</b>	<b>Modification to 4.2, Resistance to corrosion</b> .....	<b>5</b>
<b>6</b>	<b>Modification to 6.1.5, Compression perpendicular to the grain</b> .....	<b>5</b>
<b>7</b>	<b>Modification to 6.1.8, Torsion</b> .....	<b>5</b>
<b>8</b>	<b>Modification to 6.2.3, Combined bending and axial tension</b> .....	<b>5</b>
<b>9</b>	<b>Modification to 6.5.2, Beams with a notch at the support</b> .....	<b>6</b>
<b>10</b>	<b>Modification to 8.3.2, Axially loaded nails</b> .....	<b>6</b>
<b>11</b>	<b>Modifications to 8.4, Stapled connections</b> .....	<b>6</b>
<b>12</b>	<b>Modification to 8.6, Dowelled connections</b> .....	<b>6</b>
<b>13</b>	<b>Modifications to 8.7.1, Laterally loaded screws</b> .....	<b>7</b>
<b>14</b>	<b>Modification to 8.7.2, Axially loaded screws</b> .....	<b>7</b>
<b>15</b>	<b>Modifications to 8.8.5.1, Plate anchorage capacity</b> .....	<b>8</b>
<b>16</b>	<b>Modification to 8.8.5.2, Plate capacity</b> .....	<b>8</b>
<b>17</b>	<b>Modification to 8.9, Split ring and shear plate connectors</b> .....	<b>9</b>
<b>18</b>	<b>Modification to 8.10, Toothed -plate connectors</b> .....	<b>9</b>
<b>19</b>	<b>Modifications to Annex A</b> .....	<b>10</b>
<b>20</b>	<b>Modification to B.4, Maximum shear stress</b> .....	<b>10</b>