

DIN EN 13381-5:2015-02 (E)

Test methods for determining the contribution to the fire resistance of structural members - Part 5: Applied protection to concrete/profiled sheet steel composite member

| Contents | | Page |
|-----------------|--|-------------|
| Foreword | | 4 |
| 1 | Scope | 5 |
| 2 | Normative references | 5 |
| 3 | Terms and definitions, symbols and units | 6 |
| 3.1 | Terms and definitions | 6 |
| 3.2 | Symbols and units | 8 |
| 4 | Test equipment | 9 |
| 4.1 | General | 9 |
| 4.2 | Furnace | 9 |
| 4.3 | Loading equipment | 9 |
| 5 | Test conditions | 9 |
| 5.1 | General | 9 |
| 5.2 | Support and restraint conditions | 10 |
| 5.3 | Loading conditions | 10 |
| 6 | Test specimens | 10 |
| 6.1 | Number of test specimens | 10 |
| 6.2 | Size of test specimens | 11 |
| 6.3 | Construction of test specimens | 11 |
| 6.4 | Composition of test specimen component materials | 13 |
| 6.5 | Properties of test materials | 14 |
| 6.6 | Verification of the test specimen | 15 |
| 7 | Installation of the test construction | 15 |
| 8 | Conditioning of the test construction | 15 |
| 9 | Application of instrumentation | 16 |
| 9.1 | General | 16 |
| 9.2 | Instrumentation for measurement of furnace temperature | 16 |
| 9.3 | Instrumentation for measurement of test specimen temperature | 16 |
| 9.4 | Instrumentation for measurement of pressure | 17 |
| 9.5 | Instrumentation for measurement of deformation | 17 |
| 9.6 | Instrumentation for measurement of applied load | 17 |
| 10 | Test procedure | 17 |
| 10.1 | General | 17 |
| 10.2 | Furnace temperature and pressure | 17 |
| 10.3 | Application and control of load | 17 |
| 10.4 | Temperature of test specimen | 17 |
| 10.5 | Deformation | 18 |
| 10.6 | Observations | 18 |
| 10.7 | Termination of test | 18 |

| | | |
|---|---|----|
| 11 | Test results | 18 |
| 11.1 | Acceptability of test results | 18 |
| 11.2 | Presentation of test results | 19 |
| 12 | Test report | 19 |
| 13 | Assessment | 20 |
| 13.1 | General | 20 |
| 13.2 | Profiled steel sheet temperature | 21 |
| 13.3 | Equivalent thickness of concrete | 21 |
| 13.4 | Limiting exposure time | 22 |
| 13.5 | Insulation | 22 |
| 14 | Report of the assessment | 22 |
| 15 | Limits of applicability of the results of the assessment | 23 |
| 16 | Additional limits of applicability of the results of the assessment for suspended ceilings used as protection system | 25 |
| 16.1 | Height of the cavity | 25 |
| 16.2 | Exposed width of test specimen | 25 |
| 16.3 | Properties of the horizontal protective membrane | 25 |
| 16.4 | Size of panels within the horizontal protective membrane | 25 |
| 16.5 | Fixtures and fittings | 25 |
| 16.6 | Gaps between grid members and test frame or walls | 25 |
| Annex A (normative) Test method to the smouldering fire or slow heating curve | | 32 |
| A.1 | General | 32 |
| A.2 | Test conditions | 32 |
| A.3 | Termination of the test | 32 |
| A.4 | Evaluation of the results | 33 |
| Annex B (normative) Measurement of properties of fire protection materials | | 35 |
| B.1 | General | 35 |
| B.2 | Thickness of fire protection materials | 35 |
| B.3 | Density of applied fire protection materials | 36 |
| B.4 | Moisture content of applied fire protection materials | 36 |
| Bibliography | | 38 |