

# DIN EN 12966:2015-03 (E)

## Road vertical signs - Variable message traffic signs

---

	Contents	Page
Foreword .....	7	
Introduction .....	9	
1 Scope .....	10	
2 Normative references .....	10	
3 Terms and definitions .....	11	
4 Product characteristics .....	15	
4.1 Dimensions and tolerances requirements .....	15	
4.2 General design requirement .....	15	
4.3 Visual performance requirements of continuous VMS .....	15	
4.4 Visual performance requirements of discontinuous VMS .....	15	
4.5 Physical performance requirements .....	24	
4.6 Dangerous substances .....	28	
5 Testing, assessment and sampling methods .....	28	
5.1 Test sequence .....	28	
5.2 Durability .....	29	
5.3 Test modules .....	29	
5.4 Physical performance test methods .....	31	
5.5 Visual performance test methods .....	36	
6 Assessment and verification of constancy of performance (AVCP) .....	45	
6.1 General .....	45	
6.2 Type testing .....	45	
6.3 Factory production control (FPC) .....	51	
7 Classification and designation .....	57	
7.1 General .....	57	
7.2 Continuous retro-reflective VMS .....	57	
7.3 Continuous, externally illuminated retro-reflective VMS .....	58	
7.4 Discontinuous VMS .....	59	
8 Marking, labelling and packaging .....	60	
9 Product information .....	60	
Annex A (normative) Equivalent area .....	61	
A.1 General .....	61	
A.2 Calculation of the luminance .....	61	
A.3 Calculation of non-matrix equivalent areas .....	64	
A.3.1 Equivalent area for a line of elements .....	64	
A.3.2 Equivalent area for a symbol fully populated with elements .....	65	
A.3.3 Equivalent area for a symbol partially populated with elements .....	65	
Annex B (normative) VMS performance declaration codes for marking .....	67	
B.1 General .....	67	

B.2	Code for continuous retro-reflective VMS .....	67
B.3	Code for externally illuminated continuous retro-reflective VMS .....	67
B.4	Code for discontinuous VMS .....	68
<b>Annex L (informative) Terminology used in this European Standard .....</b>		<b>69</b>
<b>Annex M (informative) Guidance on graphics for discontinuous light emitting signs .....</b>		<b>71</b>
M.1	General .....	71
M.2	Apparent luminance of lines and letter strokes .....	71
M.2.1	General .....	71
M.2.2	Further technical explanation of Apparent luminance .....	72
M.3	VMS with colour inversion .....	73
M.4	VMS without colour inversion .....	78
<b>Annex N (informative) Guidance on dimensions , luminance, beam width, legibility and efficiency for discontinuous VMS .....</b>		<b>80</b>
N.1	General .....	80
N.2	Dimensions .....	80
N.2.1	General .....	80
N.2.2	Text .....	81
N.2.3	Circles .....	81
N.2.4	Triangles .....	82
N.3	Luminance and beam width classes .....	82
N.4	Beam width and distances of legibility .....	87
N.4.1	Group of VMS, centred above the road .....	87
N.4.2	Group of VMS, not centred above the road .....	88
N.4.3	Curved road sections .....	89
N.4.4	Limits of legibility due to vertical beam .....	90
N.4.5	Calculation of recognition time .....	92
N.4.5.1	General .....	92
N.4.5.2	Distances in metres per second at various speeds .....	92
N.4.5.3	Example of calculation of the recognition time .....	92
N.4.5.3.1	General .....	92
N.4.5.3.2	Using beam width class B2 .....	93
N.4.5.3.3	Using beam width class B4 .....	94
N.4.5.3.4	Using beam width class B6 .....	95
N.4.5.4	Conclusions after calculation of recognition time .....	95
N.4.6	Luminance and luminance ratio .....	96
N.4.7	Beam width .....	96
N.5	Energy efficiency .....	96
<b>Annex O (informative) Specific design issues .....</b>		<b>97</b>
O.1	Finish .....	97
O.2	Front panels .....	97
O.3	Front screens .....	97
O.4	Appearance .....	97
O.5	Electrolytic compatibility .....	97
O.6	Protection against thermal overload .....	97
O.7	Physical security against unauthorised access .....	97
O.8	Interfaces between VMS, control, and higher order equipment .....	97
O.9	Diagnostic .....	97
<b>Annex P (informative) Guidance for design of VMS messages .....</b>		<b>99</b>
P.1	Design of VMS messages .....	99
P.2	Specifying text dimensions .....	100
<b>Annex Q (informative) Technical documentation .....</b>		<b>102</b>

<b>Q.1</b>	<b>Sign enclosure .....</b>	<b>102</b>
<b>Q.2</b>	<b>Electrical equipment .....</b>	<b>102</b>
<b>Q.3</b>	<b>Mounting devices (if applicable) .....</b>	<b>102</b>
<b>Q.4</b>	<b>Retro-reflective and non retro-reflective components .....</b>	<b>102</b>
<b>Annex R (informative) Example of recommended summary of class combinations .....</b>		<b>104</b>
<b>Annex ZA (informative) Clauses of this European Standard addressing the provisions of the EU Construction Products Regulation .....</b>		<b>112</b>
<b>ZA.1</b>	<b>Scope and relevant characteristics .....</b>	<b>112</b>
<b>ZA.2</b>	<b>Procedure for AVCP of VMS .....</b>	<b>115</b>
<b>ZA.3</b>	<b>CE marking and labelling .....</b>	<b>119</b>
<b>Bibliography .....</b>		<b>128</b>
<b>Figures Page</b>		
<b>Figure 1 -- Chromaticity areas for the colour classes C1 and C2 plotted in the CIE 1931 chromaticity diagram .....</b>	<b>18</b>	
<b>Figure 2 -- Examples of passed and failed luminance distributions .....</b>	<b>23</b>	
<b>Figure 3 -- Examples of variable message traffic sign test modules in front view - a) and c) - and side view b) .....</b>	<b>30</b>	
<b>Figure 4 -- Side elevation of the set-up for the measurement of luminance and luminance ratio .....</b>	<b>37</b>	
<b>Figure 5 -- Layout examples for a test module and the positioning of the measuring area (circle) of the luminance meter .....</b>	<b>42</b>	
<b>Figure A.1 -- Merging of elements .....</b>	<b>61</b>	
<b>Figure A.2 -- Character with a regular orthogonal matrix of (5 × 8) elements .....</b>	<b>62</b>	
<b>Figure A.3 -- Open line .....</b>	<b>64</b>	
<b>Figure A.4 -- Closed line .....</b>	<b>64</b>	
<b>Figure A.5 -- Example of symbol with an area fully populated with elements .....</b>	<b>65</b>	
<b>Figure A.6 -- Example of symbol with an area partially populated with elements .....</b>	<b>66</b>	
<b>Figure B.1 -- Code of performance classes of continuous retro-reflective VMS .....</b>	<b>67</b>	
<b>Figure B.2 -- Code of performance classes of externally illuminated continuous retro-reflective VMS .....</b>	<b>68</b>	
<b>Figure B.3 -- Code of performance classes of discontinuous VMS .....</b>	<b>68</b>	
<b>Figure L.1 -- Parts of a VMS .....</b>	<b>69</b>	
<b>Figure L.2 -- Test configuration .....</b>	<b>70</b>	
<b>Figure M.1 -- A legend seen at short (left), longer (centre), and very long distance (right) .....</b>	<b>72</b>	
<b>Figure M.2 -- Example for calculation of dimensions of circular mandatory VMS .....</b>	<b>76</b>	
<b>Figure M.3 -- Example for calculation of dimensions of circular mandatory VMS .....</b>	<b>76</b>	
<b>Figure M.4 -- Example for calculation of dimensions of a triangular warning VMS .....</b>	<b>77</b>	

Figure M.5 -- Example of VMS using (64 × 64) elements with colour inversion .....	78
Figure M.6 -- Example of VMS using (48 × 48) elements with colour inversion .....	78
Figure M.7 -- Example of VMS using (32 × 32) elements with colour inversion .....	78
Figure M.8 -- Example of VMS using (64 × 64) elements, no colour inversion .....	79
Figure M.9 -- Example of VMS using (48 × 48) elements, no colour inversion .....	79
Figure M.10 -- Example of VMS using (32 × 32) elements, no colour inversion .....	79
Figure N.1 -- Relation between classes .....	83
Figure N.2 -- Example of coverage by beam width class B1 .....	84
Figure N.3 -- Example of coverage by beam width class B3 .....	85
Figure N.4 -- Example of coverage by beam width class B6 .....	86
Figure N.5 -- Legibility of group of VMS, centred on gantry above the road .....	87
Figure N.6 -- Legibility of group of VMS, mounted on cantilever aside the road .....	88
Figure N.7 -- Legibility of group of VMS, mounted on cantilever aside the road .....	90
Figure N.8 -- Legibility of group of VMS, mounted on cantilever aside the road .....	91
Figure P.1 -- Example of the design of the letter E in a regular orthogonal matrix .....	99
Figure P.2 -- Equivalent text dimensions using uppercase characters .....	100
Figure P.3 -- Equivalent text dimensions using upper- and lower-case characters .....	100
Figure P.4 -- Equivalent text dimensions of full matrix display using proportional character spacing .....	101
Figure R.1 -- Example of summary of the characteristics of products .....	105
Figure R.2 -- Example 1 for visual performance class combination .....	107
Figure R.3 -- Example 2 for visual performance class combination .....	108
Figure R.4 -- Example 3 for visual performance class combination .....	110
Figure R.5 -- Example 4 for visual performance class combination .....	111
Figure ZA.1 -- Example of CE marking affixed to a continuous retro-reflective VMS .....	123
Figure ZA.2 -- Example of CE marking affixed to a continuous, externally illuminated retro-reflective VMS .....	124
Figure ZA.3 -- Example of CE marking affixed to a discontinuous VMS .....	125
Figure ZA.4 -- Example of CE marking affixed to a continuous retro-reflective VMS .....	126
Figure ZA.5 -- Example of CE marking affixed to a continuous, externally illuminated retro-reflective VMS .....	126
Figure ZA.6 -- Example of CE marking affixed to a discontinuous VMS .....	127
Tables Page Table 1 -- Class designation of the visual performance parameters of VMS .....	16

<b>Table 2 -- Corner points (CIE 1931 chromaticity co-ordinates x, y) of the chromaticity areas for the colours of class C1 .....</b>	<b>17</b>
<b>Table 3 -- Corner points (CIE 1931 chromaticity co-ordinates x, y) of the chromaticity areas for the colours of class C2 .....</b>	<b>17</b>
<b>Table 4 -- Le and La luminance limits for white on reference axis .....</b>	<b>19</b>
<b>Table 5 -- Le and La luminance limits for yellow on reference axis .....</b>	<b>20</b>
<b>Table 6 -- Le and La luminance limits for orange on reference axis .....</b>	<b>20</b>
<b>Table 7 -- Le and La luminance limits for green on reference axis .....</b>	<b>20</b>
<b>Table 8 -- Le and La luminance limits for red on reference axis .....</b>	<b>21</b>
<b>Table 9 -- Le and La luminance limits for blue on reference axis .....</b>	<b>21</b>
<b>Table 10 -- Minimum luminance ratio values (LR) for various colours and classes R1, R2 and R3, at test angles on the reference axis and off the reference axis .....</b>	<b>22</b>
<b>Table 11 -- Beam width classes .....</b>	<b>23</b>
<b>Table 12 -- Class designation .....</b>	<b>24</b>
<b>Table 13 -- Temperature range classes .....</b>	<b>25</b>
<b>Table 14 -- Ingress protection level classes .....</b>	<b>26</b>
<b>Table 15 -- Effect of voltage interruption .....</b>	<b>27</b>
<b>Table 16 -- Operating voltage range, power-up activation and temporary overvoltage tests .....</b>	<b>31</b>
<b>Table 17 -- Frequency and voltage tests .....</b>	<b>31</b>
<b>Table 18 -- Impact test .....</b>	<b>32</b>
<b>Table 19 -- Vibration test .....</b>	<b>32</b>
<b>Table 20 -- Corrosion test .....</b>	<b>33</b>
<b>Table 21 -- Water ingress test - Severity .....</b>	<b>33</b>
<b>Table 22 -- Dust ingress test - Severity .....</b>	<b>33</b>
<b>Table 23 -- Temperature test .....</b>	<b>34</b>
<b>Table 24 -- Test angles (in degrees, with respect to the reference axis), used for the measurement of luminance under external illumination and luminance ratio .....</b>	<b>38</b>
<b>Table 25 -- Test angles (in degrees, with respect to the reference axis), used for the measurement of luminance without external illumination .....</b>	<b>38</b>
<b>Table 26 -- Test angles (in degrees, with respect to the reference axis), used for the measurement of beam width, and for uniformity of luminous intensity and colour of monochromatic elements .....</b>	<b>39</b>
<b>Table 27 -- Test angles (in degrees, with respect to the reference axis), used for the measurement of uniformity of luminous intensity and colour of elements formed by mixing colours .....</b>	<b>40</b>
<b>Table 28 -- Characteristics of continuous VMS .....</b>	<b>46</b>

<b>Table 29 -- Characteristics of discontinuous VMS .....</b>	<b>48</b>
<b>Table 30 -- Identification label .....</b>	<b>51</b>
<b>Table 31 -- Minimum frequency of testing continuous VMS for product testing and evaluation as part of FPC .....</b>	<b>53</b>
<b>Table 32 -- Minimum frequency of testing discontinuous VMS for product testing and evaluation as part of FPC .....</b>	<b>54</b>
<b>Table M.1 -- Parameters for mandatory signs using a red circle .....</b>	<b>74</b>
<b>Table M.2 -- Parameters for mandatory signs using a red triangle .....</b>	<b>75</b>
<b>Table N.1 -- Minimum dimensions of text (mm) .....</b>	<b>81</b>
<b>Table N.2 -- Minimum dimensions of circles (mm) .....</b>	<b>82</b>
<b>Table N.3 -- Minimum dimensions of triangles (mm) .....</b>	<b>82</b>
<b>Table N.4 -- Examples for applications of beam width classes .....</b>	<b>83</b>
<b>Table N.5 -- Examples for recognition time depending on character height, speed and vertical beam width .....</b>	<b>91</b>
<b>Table N.6 -- Conversion from speed unit km/h to m/s .....</b>	<b>92</b>
<b>Table ZA.1.1 -- Relevant clauses for continuous VMS .....</b>	<b>112</b>
<b>Table ZA.1.2 -- Relevant clauses for discontinuous VMS .....</b>	<b>114</b>
<b>Table ZA.2 -- System of AVCP .....</b>	<b>115</b>
<b>Table ZA.3 -- Assignment of AVCP tasks for VMS under system 1 .....</b>	<b>116</b>