DIN EN 13384-1:2015-06 (E)

Chimneys - Thermal and fluid dynamic calculation methods - Part 1: Chimneys serving one heating appliance

Contents

Page

Foreword 5

1 Scope 6

2 Normative references 6

3 Terms and definitions 6

4 Symbols and abbreviations 10

5 Calculation method for non-balanced flue chimneys 14
5.1 General principles 14
5.2 Pressure requirements 15
5.2.1 Negative pressure chimneys 15
5.2.2 Positive pressure chimneys 16
5.3 Temperature requirement 16
5.4 Calculation procedure 17
5.5 Flue gas data characterising the heating appliance 18
5.5.1 General 18
5.5.2 Flue gas mass flow 18
5.5.3 Flue gas temperature 19
5.5.4 Minimum draught for the heating appliance (PW) for negative pressure chimney 19
5.5.5 Maximum draught for the heating appliance (PWmax) for negative pressure chimney 20
5.5.6 Maximum differential pressure of the heating appliance (PWO) for positive pressure chimney 20
5.5.7 Minimum differential pressure of the heating appliance (PWOmin) for positive pressure chimney 20
5.6 Characteristic data for the calculation 20
5.6.1 General 20
5.6.2 Mean value for roughness (r) 20
5.6.3 Thermal resistance (1/) 20
5.7 Basic values for the calculation 21
5.7.1 Air temperatures 21
5.7.2 External air pressure (pL) 23
5.7.3 Gas constant 23
5.7.4 Density of the external air (L) 24
5.7.5 Specific heat capacity of the flue gas (cp) 24
5.7.6 Condensing temperature (Tsp) 24
5.7.7 Correction factor for temperature instability (SH) 24
5.7.8 Flow safety coefficient (SE) 24
5.8 Determination of the temperatures 25
5.8.1 General 25
5.8.2 Calculation of the coefficient of cooling (K) 25
5.8.3 Coefficient of heat transmission (kb) 26
5.9 Determination of the density of the flue gas and the velocity of the flue gas 28
5.9.1 Density of the flue gas (m) 28
5.9.2 Velocity of the flue gas (wm) 28
5.10 Determination of the pressures 29
5.10.1 Pressure at the flue gas inlet into the chimney 29
5.10.2 Theoretical draught available due to chimney effect (PH) 30
5.10.3 Pressure resistance of the chimney (PR) 30

5.10.4 Wind velocity pressure (PL) ... 31
5.11 Minimum draught required at the flue gas inlet into the chimney and maximum allowed draught (PZe and PZemax) and maximum and minimum differential pressure at the flue gas inlet into the chimney (PZOe and PZOemin) ... 32
5.11.1 General ... 32
5.11.2 Minimum and maximum draught for the heating appliance (PW and PWmax) and maximum and minimum differential pressure of the heating appliance (PWO and PWOmin) ... 33
5.11.3 Effective pressure resistance of the connecting flue pipe (PFV) ... 33
5.11.4 Pressure resistance of the air supply (PB) ... 34
5.12 Calculation of the inner wall temperature at the chimney outlet (Tiob) ... 35

6 Secondary air for negative pressure chimneys ... 37
6.1 General ... 37
6.2 Calculation method ... 37
6.3 Basic values for the calculation of secondary air ... 37
6.3.1 General ... 37
6.3.2 Mixing calculations ... 37
6.4 Pressures ... 38
6.4.1 Pressure resistance for the air supply with secondary air (PBNL) ... 38
6.4.2 Draught required for the secondary air devices (PNL) ... 39
6.4.3 Pressure resistance for that part of the connecting flue pipe before the secondary air device (PFV1) ... 40
6.4.4 Pressure requirement with secondary air ... 41
6.5 Temperature requirement with secondary air ... 41

7 Calculation method for balanced flue chimneys ... 41
7.1 General principles ... 41
7.2 Pressure requirements ... 42
7.3 Temperature requirements ... 43
7.4 Calculation procedure ... 43
7.5 Flue gas data characterizing the heating appliance ... 43
7.6 Characteristic data for the calculation ... 44
7.7 Basic values for the calculation ... 44
7.7.1 Air temperatures ... 44
7.7.2 Other basic values ... 45
7.8 Determination of the temperatures ... 45
7.8.1 Non-concentric (separate) ducts ... 45
7.8.2 Concentric ducts - calculation based on a correction factor for heat radiation ... 45
7.8.3 Concentric ducts - calculation based on calculated heat radiation ... 60
7.8.4 Mean temperatures for pressure calculation ... 64
7.9 Determination of densities and velocities ... 65
7.9.1 Density and velocity of the flue gas ... 65
7.9.2 Density and velocity of the supply air ... 65
7.10 Determination of pressures ... 66
7.10.1 Pressure at the flue gas inlet into the chimney ... 66
7.10.2 Theoretical draught due to chimney effect in the chimney segment (PH) ... 66
7.10.3 Pressure resistance in the chimney segment (PR) ... 66
7.10.4 Wind velocity pressure (PL) ... 66
7.11 Minimum draught required at the flue gas inlet into the chimney and maximum allowed draught (PZe and PZemax) and maximum and minimum differential pressure at the flue gas inlet into the chimney (PZOe and PZOemin) ... 66
7.11.1 General ... 66
7.11.2 Minimum and maximum draught for the heating appliance (PW and PWmax) and maximum and minimum differential pressure of the heating appliance (PWO and PWOmin) ... 67
7.11.3 Effective pressure resistance of the connection pipe (PFV) ... 67
7.11.4 Pressure resistance of the air supply ... 67
7.12 Calculation of the inner wall temperature at the chimney outlet (Tiob) ... 70

8 Consideration of the condensation heat of the flue gas water vapour ... 70
8.1 General ... 70

8.2 Onset of condensation 71
8.3 Calculation of the flue gas temperature at the outlet of a chimney segment with condensation (j NsegK) 73

9 Consideration of chimney fans 78
9.1 General 78
9.2 Inline fans 79
9.3 Exhaust fans 80

Annex A (informative) Calculation of thermal resistance 82

Annex B (informative) Tables 83

Annex C (informative) Chimney outlet with regard to adjacent buildings 98

Annex D (informative) Determination of the gas constant R considering the condensation 99